

TABLES

Table 3.2
Washington County Sewer Council OLDS Tests

| Parcel Number | Finleyville-Elrama Road Address | Malfunctioning OLDS |
|-----------------------|--|----------------------------|
| 640-005-01-00-0009-01 | 3585 | |
| 640-005-02-00-0005-00 | 3976 | |
| 640-005-02-00-0006-00 | 3976 | |
| 640-005-02-00-0007-00 | 3984 | Passed |
| 640-005-01-00-0013-00 | 3991 | |
| 640-005-01-00-0014-00 | 3993 | |
| 640-005-01-00-0015-00 | 3997 | Passed |
| 640-005-02-00-0008-00 | 3990 | |
| 640-005-02-00-0009-00 | 3994 | |
| 640-005-02-00-0011-00 | 3998 | |
| 640-005-02-00-0012-00 | 4004 | |
| 640-005-02-00-0013-00 | 4008 | |
| 640-005-02-00-0014-00 | 4014 | |
| 640-005-02-00-0015-00 | 4014 | |
| 640-008-00-00-0077-00 | 4026 | |
| 640-008-00-00-0078-00 | 4028 | |
| 640-008-00-00-0079-00 | 4038 | Failed |
| 640-008-00-00-0080-00 | 4035 | |

Table 4.1
Equivalent Dwelling Unit, Gallons per day and BOD per day Summary

| Item # | Parcel Number | No. of Bedrooms | Gals per day | BOD (mg/l) per day |
|--------|-----------------------|-----------------|--------------|--------------------|
| 1 | 640-008-02-01-0001-00 | 3 | 400 | 0.9 |
| 2 | 640-008-00-00-0079-02 | 3 | 400 | 0.9 |
| 3 | 640-005-00-00-0021-01 | 3 | 400 | 0.9 |
| 4 | 640-005-00-00-0021-00 | 3 | 400 | 0.9 |
| 5 | 640-008-02-01-0002-00 | 3 | 400 | 0.9 |
| 6 | 640-005-00-00-0036-00 | 3 | 400 | 0.9 |
| 7 | 640-008-00-00-0079-01 | 3 | 400 | 0.9 |
| 8 | 640-008-00-00-0080-00 | 3 | 400 | 0.9 |
| 9 | 640-008-00-00-0079-00 | 3 | 400 | 0.9 |
| 10 | 640-008-00-00-0078-00 | 3 | 400 | 0.9 |
| 11 | 640-008-00-00-0077-00 | 3 | 400 | 0.9 |
| 12 | 640-005-02-00-0015-00 | 3 | 400 | 0.9 |
| 13 | 640-005-00-00-0022-01 | 3 | 400 | 0.9 |
| 14 | 640-005-00-00-0026-07 | 3 | 400 | 0.9 |
| 15 | 640-005-02-00-0014-00 | 3 | 400 | 0.9 |
| 16 | 640-005-02-00-0013-00 | 3 | 400 | 0.9 |
| 17 | 640-005-02-00-0012-00 | 3 | 400 | 0.9 |
| 18 | 640-005-02-00-0011-00 | 3 | 400 | 0.9 |
| 19 | 640-005-00-00-0026-00 | 3 | 400 | 0.9 |
| 20 | 640-005-02-00-0009-00 | 3 | 400 | 0.9 |
| 21 | 640-005-00-00-0022-00 | 3 | 400 | 0.9 |
| 22 | 640-005-01-00-0015-00 | 3 | 400 | 0.9 |
| 23 | 640-005-01-00-0014-00 | 3 | 400 | 0.9 |
| 24 | 640-005-01-00-0013-00 | 3 | 400 | 0.9 |
| 25 | 640-005-02-00-0008-00 | 3 | 400 | 0.9 |
| 26 | 640-005-01-00-0009-01 | 3 | 400 | 0.9 |
| 27 | 640-005-02-00-0007-00 | 3 | 400 | 0.9 |
| 28 | 640-005-01-00-0009-00 | 3 | 400 | 0.9 |
| 29 | 640-005-01-00-0012-00 | 3 | 400 | 0.9 |
| 30 | 640-005-01-00-0011-00 | 3 | 400 | 0.9 |
| 31 | 640-005-01-00-0010-00 | 3 | 400 | 0.9 |
| 32 | 640-005-07-00-0017-00 | 3 | 400 | 0.9 |
| 33 | 640-006-00-00-0001-00 | 3 | 400 | 0.9 |
| Total | | | 13200 | 29.7 |
| | | | 13200 | 30 |

*

Table 8.1 - Anticipated Implementation Schedule

| Task No. | Task Description | Projected Duration | Total Elapsed Time From Time Zero | Notes |
|----------|---|--------------------|-----------------------------------|---|
| 1 | Finalize Agreement between Union Township and PCSA | 30 Days | 30 Days | |
| 2 | Draft Act 537 Planning Revision via Special Study | 60 Days | 90 Days | |
| 3 | Initiate/Advertise 30 Day Public Comment Period | 30 Days | 120 Days | |
| 4 | Municipal Adoption of Act 537 Plan Special Study | 30 Days | 150 Days | |
| 5 | Submit Act 537 Plan Special Study to PaDEP | --- | --- | To be Submitted Immediately Following Adoption by Township |
| 6 | -Prepare Final Construction Docs and PCSA Review/Approval of Final Docs (Grinder Pump Alternative) -Survey/Design (Lift Station Alternative) | 120 Days | --- | Completed Concurrently with PaDEP Review of Act 537 Plan Revision (Below) |
| 7 | Receive Act 537 Plan Special Study Approval from PaDEP | 120 Days | 270 Days | Assume 120 Day Review Period (May be More or Less) |
| 8 | Submit Part II Permit Application | --- | --- | To Be Submitted Immediately Following PaDEP Approval of Act 537 Plan Revision |
| 9 | Receive Part II Permit Approval | 120 Days | 390 Days | Assume 120 Day PaDEP Review Period (May be More or Less) |
| 10 | Complete Right-of-way Acquisition | --- | --- | Completed Concurrently with PaDEP Part II Permit Review (Above) |
| 11 | Advertise/Issue Contract for Bid | 30 Days | 420 Days | |
| 12 | Open Bids | --- | --- | |
| 13 | Pre-Construction Meeting | 30 Days | 450 Days | |
| 14 | Construction | 180 Days | 630 Days | |

APPENDIX A

**CUSTOM SOIL RESOURCE REPORT
FOR GREENE AND WASHINGTON
COUNTIES, PENNSYLVANIA – ACT 537
FINLEYVILLE – ELRAMA ROAD
PLANNING AREA**

**TABLE 3.2 - OLDS Locations and Testing
 Finleyville-Elrama Road Planning Area
 Onlot Disposal System locations**



- Onlot Disposal system
- Onlot Disposal system – suspected malfunction – tested passed
- Onlot Disposal system – suspected malfunction – tested failed

TABLE 8.2 - Anticipated Implementation Schedule - LSSE

Peters Creek Sanitary Authority
 Finleyville-Elrama Road Sewer Line Extension
 Project Schedule / Status Update
 December 2023

Color Legend:
 Completed Tasks
 Anticipated Tasks
 Next Milestone

*Subject to Change

| Projected Timeline | Duration | March 2023 MOU Schedule | | | Updated Schedule Task | Slippage | Progress / Milestones |
|--------------------|----------|---------------------------------|---|----------------------------------|-----------------------|----------|--|
| | | Planning Track | Design / Construction Task | | | | |
| February 23 | N/A | | | | | | 2-2-23: PCSA / Union Township (UT) Public Meeting 2-27-23: PCSA Meeting Board Authorized Nor-East / Cooper Aerial Photography and Mapping 3-13-23: LSSE Set Aerial Photography Panels / Points 3-14-23: PCSA Special Board Meeting approving Memorandum of Understanding (MOU) 3-15-23: Nor-East / Cooper Completed Flight 3-14-23 through 3-22-23: LSSE Complete Aerial Control Location Task / Placed PA One Calls 3-22-23: LSSE forward Aerial Control to Nor East / Cooper 3-27-23: LSSE performed Supplemental PA One Call Surveys 9-27-23: PCSA Meeting - Board Approved LSSE Service Order Authorization 3-30-23: Coordinated with PaDEP on Planning Elements 4-4-23: LSSE coordinated meeting with UT and Bankson 4-11-23: Receipt of Aerial Mapping 4-26-23: PCSA and LSSE Conducted Project Field Review 5-22-23: Reviewed Preliminary Design Considerations with PCSA Board (Gilmore and L/S Property) 6-26-23: Reviewed Final Service Area Address List (Exhibit 13 of MOU) with PCSA Board 6-26-23: Review limiting segment Veronica/Victoria/Rebecca 3-27-23 through Mid July: Draft Act 537 Plan Special Study To Accommodate - L / S Alternative |
| March 23 | 0 | Agreement Finalized | Agreement Finalized | Agreement Finalized | | | |
| April 23 | 30 | | | | | | |
| May 23 | 60 | | | | | | |
| June 23 | 90 | Draft Act 537 Special Study | | | | | |
| July 23 | 120 | Advertise Act 537 Special Study | | | | | |
| August 23 | 150 | UT Adopt Act 537 Plan | | Draft Act 537 Special Study | 60 | | 8-17-23: PCSA and LSSE Conducted Field Review of Proposed Alignment 8-18-23: Geotech Proposals received for LS Site, Site Access to be Discussed with PCSA Board at August Meeting 8-28-23: Review Draft Act 537 Plan Special Study with PCSA Board 9-19-23: Joint meeting with UT |
| September 23 | 180 | | | | | | 9-19-23 through January 2024: Address UT Comments following execution of MOU amendment |
| October 23 | 210 | | | | | | 10-25-23: Discussed with PCSA Board reports of wildcat sewer parallel to FER 11-20-23: PCSA Board approved relocation of sewer FER due to wildcat sewer 11-20-23: PCSA Board authorized contractor to test pit wildcat sewer 11-21-23: MOU Amendment issued to UT |
| November 23 | 240 | | | | | | |
| December 23 | 270 | Receive PaDEP Planning Approval | Submit Amended Part II Permit Application | Execute MOU Amendment | | | January: LSSE to submit revised Act 537 Plan and response to UT comments. UT to authorize advertisement at January 16, 2024 meeting. |
| January 24 | 300 | | | Advertise Act 537 Special Study* | 180 | | January: Contractor to complete wildcat sewer test pit |

| Projected Timeline | Duration | March 2023 MOU Schedule | | Updated Schedule Task | Slippage | Progress / Milestones |
|--------------------|----------|-------------------------|---------------------------------|--|----------|--|
| | | Planning Track | Design / Construction Task | | | |
| February 24 | 330 | | | UT Adopt Act 537 Plan* | 180 | February/March: Schedule Meeting (Act 537 Planning Oriented) with Property Owners (if required, if necessary). |
| March 24 | 360 | | | Submit Act 537 Plan to PaDEP | | |
| April 24 | 390 | | Receive Part II Permit Approval | | | |
| May 24 | 420 | | Advertise for Bidding | Submit Amended Part II Permit Application* | 150 | Mid June '23 through May '24: Complete Design / E&S Approvals, etc. |
| June 24 | 450 | | Pre-Construction Meeting | | | |
| July 24 | 480 | | | | | Mid February '24 through July '24: Workshop Meeting with residents; ROW Acquisition |
| August 24 | 510 | | | | | |
| September 24 | 540 | | | Receive Part II Permit Approval | 180 | |
| October 24 | 570 | | | | | |
| November 24 | 600 | | | Advertise for Bidding | 210 | |
| December 24 | 630 | | Complete Construction | Open Bids | | |
| January 25 | 660 | | | Contract Document Execution | | |
| February 25 | 690 | | | Pre-Construction Meeting | 270 | |
| March 25 | 720 | | | Start Construction | | |
| April 25 | 750 | | | | | |
| May 25 | 780 | | | | | |
| June 25 | 810 | | | | | |
| July 25 | 840 | | | | | |
| August 25 | 870 | | | | | |
| September 25 | 900 | | | | | |
| October 25 | 930 | | | | | |
| November 25 | 960 | | | Complete Construction | 360 | |
| December 25 | 990 | | | | | |



United States
Department of
Agriculture


NRCS

Natural
Resources
Conservation
Service

A product of the National
Cooperative Soil Survey,
a joint effort of the United
States Department of
Agriculture and other
Federal agencies, State
agencies including the
Agricultural Experiment
Stations, and local
participants

Appendix A Custom Soil Resource Report for Greene and Washington Counties, Pennsylvania

Act 537 Finleyville - Elrama Road
Planning Area



Preface

Soil surveys contain information that affects land use planning in survey areas. They highlight soil limitations that affect various land uses and provide information about the properties of the soils in the survey areas. Soil surveys are designed for many different users, including farmers, ranchers, foresters, agronomists, urban planners, community officials, engineers, developers, builders, and home buyers. Also, conservationists, teachers, students, and specialists in recreation, waste disposal, and pollution control can use the surveys to help them understand, protect, or enhance the environment.

Various land use regulations of Federal, State, and local governments may impose special restrictions on land use or land treatment. Soil surveys identify soil properties that are used in making various land use or land treatment decisions. The information is intended to help the land users identify and reduce the effects of soil limitations on various land uses. The landowner or user is responsible for identifying and complying with existing laws and regulations.

Although soil survey information can be used for general farm, local, and wider area planning, onsite investigation is needed to supplement this information in some cases. Examples include soil quality assessments (<http://www.nrcs.usda.gov/wps/portal/nrcs/main/soils/health/>) and certain conservation and engineering applications. For more detailed information, contact your local USDA Service Center (<https://offices.sc.egov.usda.gov/locator/app?agency=nrcs>) or your NRCS State Soil Scientist (http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/contactus/?cid=nrcs142p2_053951).

Great differences in soil properties can occur within short distances. Some soils are seasonally wet or subject to flooding. Some are too unstable to be used as a foundation for buildings or roads. Clayey or wet soils are poorly suited to use as septic tank absorption fields. A high water table makes a soil poorly suited to basements or underground installations.

The National Cooperative Soil Survey is a joint effort of the United States Department of Agriculture and other Federal agencies, State agencies including the Agricultural Experiment Stations, and local agencies. The Natural Resources Conservation Service (NRCS) has leadership for the Federal part of the National Cooperative Soil Survey.

Information about soils is updated periodically. Updated information is available through the NRCS Web Soil Survey, the site for official soil survey information.

The U.S. Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, age, disability, and where applicable, sex, marital status, familial status, parental status, religion, sexual orientation, genetic information, political beliefs, reprisal, or because all or a part of an individual's income is derived from any public assistance program. (Not all prohibited bases apply to all programs.) Persons with disabilities who require

alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA's TARGET Center at (202) 720-2600 (voice and TDD). To file a complaint of discrimination, write to USDA, Director, Office of Civil Rights, 1400 Independence Avenue, S.W., Washington, D.C. 20250-9410 or call (800) 795-3272 (voice) or (202) 720-6382 (TDD). USDA is an equal opportunity provider and employer.

Contents

| | |
|---|-----|
| Preface..... | 2 |
| How Soil Surveys Are Made..... | 5 |
| Soil Map..... | 8 |
| Soil Map..... | 9 |
| Legend..... | 10 |
| Map Unit Legend..... | 12 |
| Map Unit Descriptions..... | 12 |
| Greene and Washington Counties, Pennsylvania..... | 15 |
| CaB—Culleoka channery silt loam, 3 to 8 percent slopes..... | 15 |
| CaC—Culleoka channery silt loam, 8 to 15 percent slopes..... | 16 |
| CaD—Culleoka channery silt loam, 15 to 25 percent slopes..... | 17 |
| DoB—Dormont silt loam, 3 to 8 percent slopes..... | 19 |
| DoC—Dormont silt loam, 8 to 15 percent slopes..... | 20 |
| GeC—Guernsey silt loam, 8 to 15 percent slopes..... | 22 |
| LbB—Library silty clay loam, 3 to 8 percent slopes..... | 23 |
| UdB—Udorthents, smoothed, gently sloping..... | 25 |
| UdD—Udorthents, smoothed, moderately steep..... | 26 |
| WeB—Weikert-Culleoka complex, 3 to 8 percent slopes..... | 27 |
| WeC—Weikert-Culleoka complex, 8 to 15 percent slopes..... | 29 |
| Soil Information for All Uses..... | 32 |
| Suitabilities and Limitations for Use..... | 32 |
| Land Classifications..... | 32 |
| Farmland Classification..... | 32 |
| Sanitary Facilities..... | 37 |
| Septic System AB Soil System (Alternate) (PA)..... | 38 |
| Septic System At-Grade Bed (Alternate) (PA)..... | 47 |
| Septic System CO-OP RFS III With At-Grade Bed (PA)..... | 56 |
| Septic System Free-Access Sand Filter - Drip Irrigation (PA)..... | 64 |
| Septic System Drip Irrigation (Alternate) (PA)..... | 72 |
| Septic System Free-Access Sand Filter With At-Grade Bed (PA)..... | 80 |
| Septic System In-Ground Bed (Conventional) (PA)..... | 88 |
| Septic System Subsurface Sand Filter Bed (Conventional) (PA)..... | 99 |
| Septic Tank Absorption Fields..... | 112 |
| Septic System CO-OP RFS III With Spray Irrigation (PA)..... | 122 |
| Septic System Spray Irrigation (PA)..... | 131 |
| Soil Reports..... | 141 |
| Sanitary Facilities..... | 141 |
| Sewage Disposal..... | 141 |
| References..... | 150 |
| Glossary..... | 152 |

How Soil Surveys Are Made

Soil surveys are made to provide information about the soils and miscellaneous areas in a specific area. They include a description of the soils and miscellaneous areas and their location on the landscape and tables that show soil properties and limitations affecting various uses. Soil scientists observed the steepness, length, and shape of the slopes; the general pattern of drainage; the kinds of crops and native plants; and the kinds of bedrock. They observed and described many soil profiles. A soil profile is the sequence of natural layers, or horizons, in a soil. The profile extends from the surface down into the unconsolidated material in which the soil formed or from the surface down to bedrock. The unconsolidated material is devoid of roots and other living organisms and has not been changed by other biological activity.

Currently, soils are mapped according to the boundaries of major land resource areas (MLRAs). MLRAs are geographically associated land resource units that share common characteristics related to physiography, geology, climate, water resources, soils, biological resources, and land uses (USDA, 2006). Soil survey areas typically consist of parts of one or more MLRA.

The soils and miscellaneous areas in a survey area occur in an orderly pattern that is related to the geology, landforms, relief, climate, and natural vegetation of the area. Each kind of soil and miscellaneous area is associated with a particular kind of landform or with a segment of the landform. By observing the soils and miscellaneous areas in the survey area and relating their position to specific segments of the landform, a soil scientist develops a concept, or model, of how they were formed. Thus, during mapping, this model enables the soil scientist to predict with a considerable degree of accuracy the kind of soil or miscellaneous area at a specific location on the landscape.

Commonly, individual soils on the landscape merge into one another as their characteristics gradually change. To construct an accurate soil map, however, soil scientists must determine the boundaries between the soils. They can observe only a limited number of soil profiles. Nevertheless, these observations, supplemented by an understanding of the soil-vegetation-landscape relationship, are sufficient to verify predictions of the kinds of soil in an area and to determine the boundaries.

Soil scientists recorded the characteristics of the soil profiles that they studied. They noted soil color, texture, size and shape of soil aggregates, kind and amount of rock fragments, distribution of plant roots, reaction, and other features that enable them to identify soils. After describing the soils in the survey area and determining their properties, the soil scientists assigned the soils to taxonomic classes (units). Taxonomic classes are concepts. Each taxonomic class has a set of soil characteristics with precisely defined limits. The classes are used as a basis for comparison to classify soils systematically. Soil taxonomy, the system of taxonomic classification used in the United States, is based mainly on the kind and character of soil properties and the arrangement of horizons within the profile. After the soil

Custom Soil Resource Report

scientists classified and named the soils in the survey area, they compared the individual soils with similar soils in the same taxonomic class in other areas so that they could confirm data and assemble additional data based on experience and research.

The objective of soil mapping is not to delineate pure map unit components; the objective is to separate the landscape into landforms or landform segments that have similar use and management requirements. Each map unit is defined by a unique combination of soil components and/or miscellaneous areas in predictable proportions. Some components may be highly contrasting to the other components of the map unit. The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The delineation of such landforms and landform segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, onsite investigation is needed to define and locate the soils and miscellaneous areas.

Soil scientists make many field observations in the process of producing a soil map. The frequency of observation is dependent upon several factors, including scale of mapping, intensity of mapping, design of map units, complexity of the landscape, and experience of the soil scientist. Observations are made to test and refine the soil-landscape model and predictions and to verify the classification of the soils at specific locations. Once the soil-landscape model is refined, a significantly smaller number of measurements of individual soil properties are made and recorded. These measurements may include field measurements, such as those for color, depth to bedrock, and texture, and laboratory measurements, such as those for content of sand, silt, clay, salt, and other components. Properties of each soil typically vary from one point to another across the landscape.

Observations for map unit components are aggregated to develop ranges of characteristics for the components. The aggregated values are presented. Direct measurements do not exist for every property presented for every map unit component. Values for some properties are estimated from combinations of other properties.

While a soil survey is in progress, samples of some of the soils in the area generally are collected for laboratory analyses and for engineering tests. Soil scientists interpret the data from these analyses and tests as well as the field-observed characteristics and the soil properties to determine the expected behavior of the soils under different uses. Interpretations for all of the soils are field tested through observation of the soils in different uses and under different levels of management. Some interpretations are modified to fit local conditions, and some new interpretations are developed to meet local needs. Data are assembled from other sources, such as research information, production records, and field experience of specialists. For example, data on crop yields under defined levels of management are assembled from farm records and from field or plot experiments on the same kinds of soil.

Predictions about soil behavior are based not only on soil properties but also on such variables as climate and biological activity. Soil conditions are predictable over long periods of time, but they are not predictable from year to year. For example, soil scientists can predict with a fairly high degree of accuracy that a given soil will have a high water table within certain depths in most years, but they cannot predict that a high water table will always be at a specific level in the soil on a specific date.

After soil scientists located and identified the significant natural bodies of soil in the survey area, they drew the boundaries of these bodies on aerial photographs and

Custom Soil Resource Report

identified each as a specific map unit. Aerial photographs show trees, buildings, fields, roads, and rivers, all of which help in locating boundaries accurately.


Soil Map

The soil map section includes the soil map for the defined area of interest, a list of soil map units on the map and extent of each map unit, and cartographic symbols displayed on the map. Also presented are various metadata about data used to produce the map, and a description of each soil map unit.

Custom Soil Resource Report Soil Map



Soil Map may not be valid at this scale.



MAP LEGEND

- Area of Interest (AOI)**
 - Area of Interest (AOI)
- Soils**
 - Soil Map Unit Polygons
 - Soil Map Unit Lines
 - Soil Map Unit Points
- Special Point Features**
 - Blowout
 - Borrow Pit
 - Clay Spot
 - Closed Depression
 - Gravel Pit
 - Gravelly Spot
 - Landfill
 - Lava Flow
 - Marsh or swamp
 - Mine or Quarry
 - Miscellaneous Water
 - Perennial Water
 - Rock Outcrop
 - Saline Spot
 - Sandy Spot
 - Severely Eroded Spot
 - Sinkhole
 - Slide or Slip
 - Sodic Spot
- Water Features**
 - Streams and Canals
- Transportation**
 - Rails
 - Interstate Highways
 - US Routes
 - Major Roads
 - Local Roads
- Background**
 - Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background



Custom Soil Resource Report

MAP LEGEND

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Map Unit Legend

| Map Unit Symbol | Map Unit Name | Acres In AOI | Percent of AOI |
|------------------------------------|--|--------------|----------------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | 7.2 | 16.5% |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | 8.2 | 18.6% |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | 0.4 | 0.9% |
| DoB | Dormont silt loam, 3 to 8 percent slopes | 4.9 | 11.2% |
| DoC | Dormont silt loam, 8 to 15 percent slopes | 7.6 | 17.3% |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | 1.0 | 2.3% |
| LbB | Library silty clay loam, 3 to 8 percent slopes | 2.9 | 6.5% |
| UdB | Udorthents, smoothed, gently sloping | 0.9 | 2.0% |
| UdD | Udorthents, smoothed, moderately steep | 1.6 | 3.6% |
| WeB | Weikert-Culleoka complex, 3 to 8 percent slopes | 7.4 | 16.8% |
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | 1.9 | 4.3% |
| Totals for Area of Interest | | 43.8 | 100.0% |

Map Unit Descriptions

The map units delineated on the detailed soil maps in a soil survey represent the soils or miscellaneous areas in the survey area. The map unit descriptions, along with the maps, can be used to determine the composition and properties of a unit.

A map unit delineation on a soil map represents an area dominated by one or more major kinds of soil or miscellaneous areas. A map unit is identified and named according to the taxonomic classification of the dominant soils. Within a taxonomic class there are precisely defined limits for the properties of the soils. On the landscape, however, the soils are natural phenomena, and they have the characteristic variability of all natural phenomena. Thus, the range of some observed properties may extend beyond the limits defined for a taxonomic class. Areas of soils of a single taxonomic class rarely, if ever, can be mapped without including areas of other taxonomic classes. Consequently, every map unit is made up of the soils or miscellaneous areas for which it is named and some minor components that belong to taxonomic classes other than those of the major soils.

Most minor soils have properties similar to those of the dominant soil or soils in the map unit, and thus they do not affect use and management. These are called

Custom Soil Resource Report

noncontrasting, or similar, components. They may or may not be mentioned in a particular map unit description. Other minor components, however, have properties and behavioral characteristics divergent enough to affect use or to require different management. These are called contrasting, or dissimilar, components. They generally are in small areas and could not be mapped separately because of the scale used. Some small areas of strongly contrasting soils or miscellaneous areas are identified by a special symbol on the maps. If included in the database for a given area, the contrasting minor components are identified in the map unit descriptions along with some characteristics of each. A few areas of minor components may not have been observed, and consequently they are not mentioned in the descriptions, especially where the pattern was so complex that it was impractical to make enough observations to identify all the soils and miscellaneous areas on the landscape.

The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The objective of mapping is not to delineate pure taxonomic classes but rather to separate the landscape into landforms or landform segments that have similar use and management requirements. The delineation of such segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, however, onsite investigation is needed to define and locate the soils and miscellaneous areas.

An identifying symbol precedes the map unit name in the map unit descriptions. Each description includes general facts about the unit and gives important soil properties and qualities.

Soils that have profiles that are almost alike make up a *soil series*. Except for differences in texture of the surface layer, all the soils of a series have major horizons that are similar in composition, thickness, and arrangement.

Soils of one series can differ in texture of the surface layer, slope, stoniness, salinity, degree of erosion, and other characteristics that affect their use. On the basis of such differences, a soil series is divided into *soil phases*. Most of the areas shown on the detailed soil maps are phases of soil series. The name of a soil phase commonly indicates a feature that affects use or management. For example, Alpha silt loam, 0 to 2 percent slopes, is a phase of the Alpha series.

Some map units are made up of two or more major soils or miscellaneous areas. These map units are complexes, associations, or undifferentiated groups.

A *complex* consists of two or more soils or miscellaneous areas in such an intricate pattern or in such small areas that they cannot be shown separately on the maps. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas. Alpha-Beta complex, 0 to 6 percent slopes, is an example.

An *association* is made up of two or more geographically associated soils or miscellaneous areas that are shown as one unit on the maps. Because of present or anticipated uses of the map units in the survey area, it was not considered practical or necessary to map the soils or miscellaneous areas separately. The pattern and relative proportion of the soils or miscellaneous areas are somewhat similar. Alpha-Beta association, 0 to 2 percent slopes, is an example.

An *undifferentiated group* is made up of two or more soils or miscellaneous areas that could be mapped individually but are mapped as one unit because similar interpretations can be made for use and management. The pattern and proportion of the soils or miscellaneous areas in a mapped area are not uniform. An area can

Custom Soil Resource Report

be made up of only one of the major soils or miscellaneous areas, or it can be made up of all of them. Alpha and Beta soils, 0 to 2 percent slopes, is an example.

Some surveys include *miscellaneous areas*. Such areas have little or no soil material and support little or no vegetation. Rock outcrop is an example.

Greene and Washington Counties, Pennsylvania

CaB—Culleoka channery silt loam, 3 to 8 percent slopes

Map Unit Setting

National map unit symbol: 2s5gm
Elevation: 720 to 1,610 feet
Mean annual precipitation: 37 to 48 inches
Mean annual air temperature: 49 to 53 degrees F
Frost-free period: 173 to 206 days
Farmland classification: All areas are prime farmland

Map Unit Composition

Culleoka and similar soils: 85 percent
Minor components: 15 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Culleoka

Setting

Landform: Hills
Landform position (two-dimensional): Backslope, shoulder, summit
Landform position (three-dimensional): Interfluve
Down-slope shape: Convex
Across-slope shape: Convex
Parent material: Fine-loamy residuum weathered from sandstone and shale

Typical profile

Ap - 0 to 10 inches: channery silt loam
Bt - 10 to 19 inches: channery silt loam
BC - 19 to 26 inches: very channery silt loam
C - 26 to 31 inches: very channery silt loam
R - 31 to 41 inches: bedrock

Properties and qualities

Slope: 3 to 8 percent
Depth to restrictive feature: 24 to 40 inches to lithic bedrock
Natural drainage class: Well drained
Capacity of the most limiting layer to transmit water (Ksat): Very low to high (0.00 to 2.00 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Available water storage in profile: Low (about 3.5 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 2e
Hydrologic Soil Group: B
Hydric soil rating: No

Minor Components

Dormont

Percent of map unit: 10 percent
Landform: Hills

Custom Soil Resource Report

Landform position (two-dimensional): Backslope, summit, shoulder
Landform position (three-dimensional): Side slope, interfluve
Down-slope shape: Linear
Across-slope shape: Convex, linear
Hydric soil rating: No

Lowell

Percent of map unit: 5 percent
Landform: Hills
Landform position (two-dimensional): Summit, backslope, shoulder
Landform position (three-dimensional): Side slope, interfluve
Down-slope shape: Convex
Across-slope shape: Linear, convex
Hydric soil rating: No

CaC—Culleoka channery silt loam, 8 to 15 percent slopes

Map Unit Setting

National map unit symbol: 2s5gn
Elevation: 720 to 1,610 feet
Mean annual precipitation: 37 to 48 inches
Mean annual air temperature: 49 to 53 degrees F
Frost-free period: 173 to 206 days
Farmland classification: Farmland of statewide importance

Map Unit Composition

Culleoka and similar soils: 80 percent
Minor components: 20 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Culleoka

Setting

Landform: Hills
Landform position (two-dimensional): Backslope, shoulder, summit
Landform position (three-dimensional): Interfluve
Down-slope shape: Convex
Across-slope shape: Convex
Parent material: Fine-loamy residuum weathered from sandstone and shale

Typical profile

Ap - 0 to 10 inches: channery silt loam
Bt - 10 to 19 inches: channery silt loam
BC - 19 to 26 inches: very channery silt loam
C - 26 to 31 inches: very channery silt loam
R - 31 to 41 inches: bedrock

Properties and qualities

Slope: 8 to 15 percent
Depth to restrictive feature: 24 to 40 inches to lithic bedrock
Natural drainage class: Well drained

Custom Soil Resource Report

Capacity of the most limiting layer to transmit water (Ksat): Very low to high (0.00 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None

Frequency of ponding: None

Available water storage in profile: Low (about 3.5 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 3e

Hydrologic Soil Group: B

Hydric soil rating: No

Minor Components

Dormont

Percent of map unit: 15 percent

Landform: Hills

Landform position (two-dimensional): Backslope, summit, shoulder

Landform position (three-dimensional): Side slope, interfluve

Down-slope shape: Linear

Across-slope shape: Convex, linear

Hydric soil rating: No

Lowell

Percent of map unit: 5 percent

Landform: Hills

Landform position (two-dimensional): Summit, backslope, shoulder

Landform position (three-dimensional): Side slope, interfluve

Down-slope shape: Convex

Across-slope shape: Linear, convex

Hydric soil rating: No

CaD—Culleoka channery silt loam, 15 to 25 percent slopes

Map Unit Setting

National map unit symbol: 2s5gp

Elevation: 720 to 1,610 feet

Mean annual precipitation: 37 to 48 inches

Mean annual air temperature: 49 to 53 degrees F

Frost-free period: 173 to 206 days

Farmland classification: Not prime farmland

Map Unit Composition

Culleoka and similar soils: 80 percent

Minor components: 20 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Custom Soil Resource Report

Description of Culleoka

Setting

Landform: Hills

Landform position (two-dimensional): Backslope, shoulder, summit

Landform position (three-dimensional): Interfluve

Down-slope shape: Convex

Across-slope shape: Convex

Parent material: Fine-loamy residuum weathered from sandstone and shale

Typical profile

Ap - 0 to 10 inches: channery silt loam

Bt - 10 to 19 inches: channery silt loam

BC - 19 to 26 inches: very channery silt loam

C - 26 to 31 inches: very channery silt loam

R - 31 to 41 inches: bedrock

Properties and qualities

Slope: 15 to 25 percent

Depth to restrictive feature: 24 to 40 inches to lithic bedrock

Natural drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Very low to high (0.00 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None

Frequency of ponding: None

Available water storage in profile: Low (about 3.5 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: B

Hydric soil rating: No

Minor Components

Dormont

Percent of map unit: 15 percent

Landform: Hills

Landform position (two-dimensional): Backslope, summit, shoulder

Landform position (three-dimensional): Side slope, interfluve

Down-slope shape: Linear

Across-slope shape: Convex, linear

Hydric soil rating: No

Lowell

Percent of map unit: 5 percent

Landform: Hills

Landform position (two-dimensional): Summit, backslope, shoulder

Landform position (three-dimensional): Side slope, interfluve

Down-slope shape: Convex

Across-slope shape: Linear, convex

Hydric soil rating: No

Custom Soil Resource Report

DoB—Dormont silt loam, 3 to 8 percent slopes

Map Unit Setting

National map unit symbol: 2s5gj
Elevation: 800 to 1,540 feet
Mean annual precipitation: 37 to 47 inches
Mean annual air temperature: 48 to 52 degrees F
Frost-free period: 173 to 197 days
Farmland classification: All areas are prime farmland

Map Unit Composition

Dormont and similar soils: 75 percent
Minor components: 25 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Dormont

Setting

Landform: Hills
Landform position (two-dimensional): Backslope, summit, shoulder
Landform position (three-dimensional): Side slope, interfluve
Down-slope shape: Linear
Across-slope shape: Concave, linear
Parent material: Fine-loamy residuum weathered from limestone, sandstone, and shale

Typical profile

Ap - 0 to 11 inches: silt loam
Bt1 - 11 to 21 inches: silt loam
Bt2 - 21 to 31 inches: silty clay loam
Bt3 - 31 to 46 inches: channery silty clay loam
Bt4 - 46 to 62 inches: channery silty clay loam
BC - 62 to 75 inches: channery silty clay loam

Properties and qualities

Slope: 3 to 8 percent
Depth to restrictive feature: More than 80 inches
Natural drainage class: Moderately well drained
Capacity of the most limiting layer to transmit water (Ksat): Low to moderately high (0.01 to 0.66 in/hr)
Depth to water table: About 24 to 44 inches
Frequency of flooding: None
Frequency of ponding: None
Available water storage in profile: Moderate (about 8.7 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 2e
Hydrologic Soil Group: D
Hydric soil rating: No

Custom Soil Resource Report

Minor Components

Culleoka

Percent of map unit: 10 percent

Landform: Hills

Landform position (two-dimensional): Backslope, shoulder, summit

Landform position (three-dimensional): Interfluve

Down-slope shape: Convex

Across-slope shape: Convex

Hydric soil rating: No

Lowell

Percent of map unit: 10 percent

Landform: Hills

Landform position (two-dimensional): Summit, backslope, shoulder

Landform position (three-dimensional): Side slope, interfluve

Down-slope shape: Convex

Across-slope shape: Linear, convex

Hydric soil rating: No

Guernsey

Percent of map unit: 5 percent

Landform: Hillslopes

Landform position (two-dimensional): Backslope, summit

Landform position (three-dimensional): Side slope, interfluve

Down-slope shape: Concave

Across-slope shape: Linear

Hydric soil rating: No

DoC—Dormont silt loam, 8 to 15 percent slopes

Map Unit Setting

National map unit symbol: 2s5gh

Elevation: 800 to 1,540 feet

Mean annual precipitation: 37 to 47 inches

Mean annual air temperature: 48 to 52 degrees F

Frost-free period: 173 to 197 days

Farmland classification: Farmland of statewide importance

Map Unit Composition

Dormont and similar soils: 70 percent

Minor components: 30 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Dormont

Setting

Landform: Hills

Landform position (two-dimensional): Backslope, summit, shoulder

Landform position (three-dimensional): Side slope, interfluve

Custom Soil Resource Report

Down-slope shape: Linear
Across-slope shape: Concave, linear
Parent material: Fine-loamy residuum weathered from limestone, sandstone, and shale

Typical profile

Ap - 0 to 11 inches: silt loam
Bt1 - 11 to 21 inches: silt loam
Bt2 - 21 to 31 inches: silty clay loam
Bt3 - 31 to 46 inches: channery silty clay loam
Bt4 - 46 to 62 inches: channery silty clay loam
BC - 62 to 75 inches: channery silty clay loam

Properties and qualities

Slope: 8 to 15 percent
Depth to restrictive feature: More than 80 inches
Natural drainage class: Moderately well drained
Capacity of the most limiting layer to transmit water (Ksat): Low to moderately high (0.01 to 0.66 in/hr)
Depth to water table: About 24 to 44 inches
Frequency of flooding: None
Frequency of ponding: None
Available water storage in profile: Moderate (about 8.7 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 3e
Hydrologic Soil Group: D
Hydric soil rating: No

Minor Components

Culleoka

Percent of map unit: 15 percent
Landform: Hills
Landform position (two-dimensional): Backslope, shoulder, summit
Landform position (three-dimensional): Interfluvium
Down-slope shape: Convex
Across-slope shape: Convex
Hydric soil rating: No

Lowell

Percent of map unit: 10 percent
Landform: Hills
Landform position (two-dimensional): Summit, backslope, shoulder
Landform position (three-dimensional): Side slope, interfluvium
Down-slope shape: Convex
Across-slope shape: Linear, convex
Hydric soil rating: No

Guernsey

Percent of map unit: 5 percent
Landform: Hills
Landform position (two-dimensional): Backslope, shoulder, summit
Landform position (three-dimensional): Side slope, head slope
Down-slope shape: Concave, linear
Across-slope shape: Linear, concave

Custom Soil Resource Report

Hydric soil rating: No

GeC—Guernsey silt loam, 8 to 15 percent slopes

Map Unit Setting

National map unit symbol: 2t32f
Elevation: 600 to 1,880 feet
Mean annual precipitation: 37 to 49 inches
Mean annual air temperature: 47 to 53 degrees F
Frost-free period: 165 to 205 days
Farmland classification: Farmland of statewide importance

Map Unit Composition

Guernsey and similar soils: 85 percent
Minor components: 15 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Guernsey

Setting

Landform: Hills
Landform position (two-dimensional): Summit, backslope, shoulder
Landform position (three-dimensional): Interfluvium, crest, side slope, head slope
Down-slope shape: Convex
Across-slope shape: Linear
Parent material: Colluvium derived from limestone and shale over residuum weathered from limestone and shale

Typical profile

Ap - 0 to 8 inches: silt loam
BE - 8 to 15 inches: silt loam
Bt1 - 15 to 22 inches: silty clay loam
Bt2 - 22 to 37 inches: silty clay
Btg - 37 to 54 inches: silty clay loam
2C - 54 to 60 inches: channery silt loam
2Cr - 60 to 70 inches: bedrock

Properties and qualities

Slope: 8 to 15 percent
Depth to restrictive feature: 59 to 62 inches to paralithic bedrock
Natural drainage class: Moderately well drained
Capacity of the most limiting layer to transmit water (Ksat): Moderately low to moderately high (0.06 to 0.20 in/hr)
Depth to water table: About 16 to 23 inches
Frequency of flooding: None
Frequency of ponding: None
Available water storage in profile: High (about 9.9 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 3e

Custom Soil Resource Report

Hydrologic Soil Group: C/D
Hydric soil rating: No

Minor Components

Berks

Percent of map unit: 5 percent
Landform: Hills
Landform position (two-dimensional): Summit, backslope, shoulder
Landform position (three-dimensional): Crest, interflue, side slope, head slope
Down-slope shape: Convex
Across-slope shape: Linear
Hydric soil rating: No

Westmoreland

Percent of map unit: 5 percent
Landform: Hills
Landform position (two-dimensional): Summit, backslope, shoulder
Landform position (three-dimensional): Crest, interflue, side slope, head slope
Down-slope shape: Convex
Across-slope shape: Linear
Hydric soil rating: No

Coshocton

Percent of map unit: 5 percent
Landform: Ridges
Landform position (two-dimensional): Summit, shoulder
Landform position (three-dimensional): Interflue
Down-slope shape: Convex
Across-slope shape: Linear
Hydric soil rating: No

LbB—Library silty clay loam, 3 to 8 percent slopes

Map Unit Setting

National map unit symbol: 1655
Elevation: 800 to 1,300 feet
Mean annual precipitation: 36 to 46 inches
Mean annual air temperature: 41 to 62 degrees F
Frost-free period: 130 to 160 days
Farmland classification: Farmland of statewide importance

Map Unit Composition

Library and similar soils: 70 percent
Minor components: 30 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Library

Setting

Landform: Hills

Custom Soil Resource Report

Landform position (two-dimensional): Summit
Landform position (three-dimensional): Base slope
Down-slope shape: Concave
Across-slope shape: Concave
Parent material: Clayey residuum weathered from limestone and shale

Typical profile

Ap - 0 to 11 inches: silt loam
Btg - 11 to 62 inches: silty clay
Cg - 62 to 76 inches: channery silty clay

Properties and qualities

Slope: 0 to 8 percent
Depth to restrictive feature: More than 80 inches
Natural drainage class: Somewhat poorly drained
Runoff class: Very high
Capacity of the most limiting layer to transmit water (Ksat): Moderately low to moderately high (0.06 to 0.20 in/hr)
Depth to water table: About 6 to 18 inches
Frequency of flooding: None
Frequency of ponding: None
Available water storage in profile: Moderate (about 7.6 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 3w
Hydrologic Soil Group: C/D
Hydric soil rating: No

Minor Components

Guernsey

Percent of map unit: 15 percent
Landform: Hills
Landform position (two-dimensional): Summit, backslope
Landform position (three-dimensional): Base slope
Down-slope shape: Linear, concave
Across-slope shape: Concave
Hydric soil rating: No

Culleoka

Percent of map unit: 10 percent
Landform: Hills
Landform position (two-dimensional): Backslope, shoulder, summit
Landform position (three-dimensional): Interfluvium
Down-slope shape: Convex
Across-slope shape: Convex
Hydric soil rating: No

Dormont

Percent of map unit: 5 percent
Landform: Hills
Landform position (two-dimensional): Backslope, summit, shoulder
Landform position (three-dimensional): Interfluvium
Down-slope shape: Linear, convex
Across-slope shape: Convex
Hydric soil rating: No

Custom Soil Resource Report

UdB—Udorthents, smoothed, gently sloping

Map Unit Setting

National map unit symbol: I659
Elevation: 1,000 to 1,500 feet
Mean annual precipitation: 36 to 50 inches
Mean annual air temperature: 41 to 62 degrees F
Frost-free period: 120 to 200 days
Farmland classification: Not prime farmland

Map Unit Composition

Udorthents and similar soils: 99 percent
Minor components: 1 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Udorthents

Setting

Down-slope shape: Linear
Across-slope shape: Linear
Parent material: Man made and altered materials from mixed rock types

Typical profile

H1 - 0 to 6 inches: very channery silt loam
H2 - 6 to 60 inches: very channery silt loam

Properties and qualities

Slope: 0 to 8 percent
Depth to restrictive feature: 40 to 72 inches to lithic bedrock
Natural drainage class: Well drained
Runoff class: Very low
Capacity of the most limiting layer to transmit water (Ksat): Moderately low to high
(0.06 to 6.00 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Available water storage in profile: Very low (about 2.9 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 4s
Hydrologic Soil Group: A
Hydric soil rating: No

Minor Components

Wet spots

Percent of map unit: 1 percent
Landform: Depressions
Hydric soil rating: Yes

Custom Soil Resource Report

UdD—Udorthents, smoothed, moderately steep

Map Unit Setting

National map unit symbol: I65b
Elevation: 1,000 to 1,500 feet
Mean annual precipitation: 36 to 50 inches
Mean annual air temperature: 41 to 62 degrees F
Frost-free period: 120 to 200 days
Farmland classification: Not prime farmland

Map Unit Composition

Udorthents and similar soils: 99 percent
Minor components: 1 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Udorthents

Setting

Down-slope shape: Linear
Across-slope shape: Linear
Parent material: Man made and altered materials from mixed rock types

Typical profile

H1 - 0 to 6 inches: very channery silt loam
H2 - 6 to 60 inches: very channery silt loam

Properties and qualities

Slope: 8 to 25 percent
Depth to restrictive feature: 40 to 72 inches to lithic bedrock
Natural drainage class: Well drained
Runoff class: Low
Capacity of the most limiting layer to transmit water (Ksat): Moderately low to high
(0.06 to 6.00 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Available water storage in profile: Very low (about 2.9 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 6e
Hydrologic Soil Group: A
Hydric soil rating: No

Minor Components

Wet spots

Percent of map unit: 1 percent
Landform: Depressions
Hydric soil rating: Yes

Custom Soil Resource Report

WeB—Weikert-Culleoka complex, 3 to 8 percent slopes

Map Unit Setting

National map unit symbol: l65k
Elevation: 500 to 1,600 feet
Mean annual precipitation: 36 to 50 inches
Mean annual air temperature: 41 to 62 degrees F
Frost-free period: 120 to 200 days
Farmland classification: Farmland of statewide importance

Map Unit Composition

Weikert and similar soils: 60 percent
Culleoka and similar soils: 30 percent
Minor components: 10 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Weikert

Setting

Landform: Hillslopes
Landform position (two-dimensional): Summit
Landform position (three-dimensional): Interfluve
Down-slope shape: Convex, linear
Across-slope shape: Linear, convex
Parent material: Residuum weathered from siltstone

Typical profile

H1 - 0 to 7 inches: channery silt loam
H2 - 7 to 19 inches: extremely channery silt loam
H3 - 19 to 23 inches: bedrock

Properties and qualities

Slope: 3 to 8 percent
Depth to restrictive feature: 10 to 20 inches to lithic bedrock
Natural drainage class: Somewhat excessively drained
Runoff class: Low
Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high (0.60 to 6.00 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Available water storage in profile: Very low (about 1.5 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 3e
Hydrologic Soil Group: D
Hydric soil rating: No

Custom Soil Resource Report

Description of Culleoka

Setting

Landform: Hills

Landform position (two-dimensional): Backslope, shoulder, summit

Down-slope shape: Convex

Across-slope shape: Convex

Parent material: Residuum weathered from nonacid siltstone, fine-grained sandstone, and shale

Typical profile

Ap - 0 to 10 inches: channery silt loam

Bt - 10 to 26 inches: channery silt loam

C - 26 to 31 inches: very channery silt loam

Properties and qualities

Slope: 3 to 8 percent

Depth to restrictive feature: 20 to 40 inches to lithic bedrock

Natural drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high (0.60 to 6.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None

Frequency of ponding: None

Available water storage in profile: Low (about 4.8 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 2e

Hydrologic Soil Group: B

Hydric soil rating: No

Minor Components

Dekalb

Percent of map unit: 5 percent

Hydric soil rating: No

Brooke

Percent of map unit: 3 percent

Landform: Hills

Landform position (two-dimensional): Summit

Landform position (three-dimensional): Interfluvium

Down-slope shape: Linear

Across-slope shape: Convex

Hydric soil rating: No

Dormont

Percent of map unit: 2 percent

Landform: Hills

Landform position (two-dimensional): Backslope, summit, shoulder

Landform position (three-dimensional): Interfluvium

Down-slope shape: Linear, convex

Across-slope shape: Convex

Hydric soil rating: No

WeC—Weikert-Culleoka complex, 8 to 15 percent slopes

Map Unit Setting

National map unit symbol: I65I
Elevation: 500 to 1,600 feet
Mean annual precipitation: 36 to 50 inches
Mean annual air temperature: 41 to 62 degrees F
Frost-free period: 120 to 200 days
Farmland classification: Not prime farmland

Map Unit Composition

Weikert and similar soils: 50 percent
Culleoka and similar soils: 40 percent
Minor components: 10 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Weikert

Setting

Landform: Hillslopes
Landform position (two-dimensional): Summit
Landform position (three-dimensional): Interfluve
Down-slope shape: Convex, linear
Across-slope shape: Linear, convex
Parent material: Residuum weathered from siltstone

Typical profile

H1 - 0 to 7 inches: channery silt loam
H2 - 7 to 19 inches: extremely channery silt loam
H3 - 19 to 23 inches: bedrock

Properties and qualities

Slope: 8 to 15 percent
Depth to restrictive feature: 10 to 20 inches to lithic bedrock
Natural drainage class: Somewhat excessively drained
Runoff class: Low
Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high (0.60 to 6.00 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Available water storage in profile: Very low (about 1.5 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 4e
Hydrologic Soil Group: D
Hydric soil rating: No

Custom Soil Resource Report

Description of Culleoka

Setting

Landform: Hillslopes

Landform position (two-dimensional): Backslope, shoulder, summit

Down-slope shape: Convex

Across-slope shape: Convex

Parent material: Residuum weathered from nonacid siltstone, fine-grained sandstone, and shale

Typical profile

Ap - 0 to 10 inches: channery silt loam

Bt - 10 to 26 inches: channery silt loam

C - 26 to 31 inches: very channery silt loam

Properties and qualities

Slope: 8 to 15 percent

Depth to restrictive feature: 20 to 40 inches to lithic bedrock

Natural drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high (0.60 to 6.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None

Frequency of ponding: None

Available water storage in profile: Low (about 4.8 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 3e

Hydrologic Soil Group: B

Hydric soil rating: No

Minor Components

Dormont

Percent of map unit: 5 percent

Landform: Hillslopes

Landform position (two-dimensional): Backslope, summit, shoulder

Landform position (three-dimensional): Head slope, side slope

Down-slope shape: Linear, concave

Across-slope shape: Convex

Hydric soil rating: No

Brooke

Percent of map unit: 5 percent

Landform: Hills

Landform position (two-dimensional): Summit

Landform position (three-dimensional): Side slope

Down-slope shape: Linear

Across-slope shape: Convex

Hydric soil rating: No

Custom Soil Resource Report

█

█

█

Soil Information for All Uses

Suitabilities and Limitations for Use

The Suitabilities and Limitations for Use section includes various soil interpretations displayed as thematic maps with a summary table for the soil map units in the selected area of interest. A single value or rating for each map unit is generated by aggregating the interpretive ratings of individual map unit components. This aggregation process is defined for each interpretation.

Land Classifications

Land Classifications are specified land use and management groupings that are assigned to soil areas because combinations of soil have similar behavior for specified practices. Most are based on soil properties and other factors that directly influence the specific use of the soil. Example classifications include ecological site classification, farmland classification, irrigated and nonirrigated land capability classification, and hydric rating.

Farmland Classification


Farmland classification identifies map units as prime farmland, farmland of statewide importance, farmland of local importance, or unique farmland. It identifies the location and extent of the soils that are best suited to food, feed, fiber, forage, and oilseed crops. NRCS policy and procedures on prime and unique farmlands are published in the "Federal Register," Vol. 43, No. 21, January 31, 1978.

Custom Soil Resource Report Map—Farmland Classification



Soil Map may not be valid at this scale.

Map Scale: 1:4,310 if printed on A portrait (8.5" x 11") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge ticks: UTM Zone 17N WGS84

MAP INFORMATION

Streams and Canals

Transportation

+++ Rails

Interstate Highways

US Routes

Major Roads

Local Roads

Background

Aerial Photography

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
Web Soil Survey URL:
Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties,
Pennsylvania
Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background

Custom Soil Resource Report

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Table—Farmland Classification

| Map unit symbol | Map unit name | Rating | Acres in AOI | Percent of AOI |
|------------------------------------|--|----------------------------------|--------------|----------------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | All areas are prime farmland | 7.2 | 16.5% |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | Farmland of statewide importance | 8.2 | 18.6% |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | Not prime farmland | 0.4 | 0.9% |
| DoB | Dormont silt loam, 3 to 8 percent slopes | All areas are prime farmland | 4.9 | 11.2% |
| DoC | Dormont silt loam, 8 to 15 percent slopes | Farmland of statewide importance | 7.6 | 17.3% |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Farmland of statewide importance | 1.0 | 2.3% |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Farmland of statewide importance | 2.9 | 6.5% |
| UdB | Udorthents, smoothed, gently sloping | Not prime farmland | 0.9 | 2.0% |
| UdD | Udorthents, smoothed, moderately steep | Not prime farmland | 1.6 | 3.6% |
| WeB | Welkert-Culleoka complex, 3 to 8 percent slopes | Farmland of statewide importance | 7.4 | 18.8% |
| WeC | Welkert-Culleoka complex, 8 to 15 percent slopes | Not prime farmland | 1.9 | 4.3% |
| Totals for Area of Interest | | | 43.8 | 100.0% |

Rating Options—Farmland Classification

Aggregation Method: No Aggregation Necessary

Tie-break Rule: Lower

Sanitary Facilities

Sanitary Facilities interpretations are tools designed to guide the user in site selection for the safe disposal of sewage and solid waste. Example interpretations include septic tank absorption fields, sewage lagoons, and sanitary landfills.

Septic System AB Soil System (Alternate) (PA)

This system is currently listed as an alternate system in the Pennsylvania regulations. It is a subsurface system of effluent distribution that includes a septic tank, a dosing tank, a recirculation subsurface sand filter, UV disinfection, and final treatment and disposal in an at-grade absorption area (aggregate material above the natural soil). Only the part of the soils between depths of 0 and 16 inches is considered when the soils are rated.

The soil properties and site features considered are those that affect absorption of the effluent and construction and maintenance of the system and those that may affect public health. These include depth to a water table, depth to bedrock, content of rock fragments, flooding, slope, and saturated hydraulic conductivity (Ksat). Flooding is a serious problem because it can result in improper treatment of the effluent and contamination of ground water or surface water. If Ksat is too fast or too slow, if the content of rock fragments is too high, or if the water table is too close to the surface, the effluent can contaminate the ground water. If this system is improperly installed on the steeper slopes, the effluent could flow along the surface of the soils. Additional grading may be needed in areas downslope from the system.

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. "Slightly limited" indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. "Moderately limited" indicates that the soil has features that are somewhat favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

These ratings do not preclude the need for onsite investigation to determine the limitations affecting system placement. This septic system requires a soil morphological evaluation, which must be conducted by a qualified soil scientist.

The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer are determined by the aggregation method chosen, which is displayed on the report. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is

Custom Soil Resource Report

presented to help the user better understand the percentage of each map unit that has the rating presented.


Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the Selected Soil Interpretations report with this interpretation included from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.

Custom Soil Resource Report
Map—Septic System AB Soil System (Alternate) (PA)



Soil Map may not be valid at this scale.

Map Scale: 1:4,310 if printed on A portrait (8.5" x 11") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 17N WGS84

MAP LEGEND

- Area of Interest (AOI)**
 - Area of Interest (AOI)
- Soils**
 - Soil Rating Polygons**
 - Very limited
 - Moderately limited
 - Slightly limited
 - Not limited
 - Not rated or not available
 - Soil Rating Lines**
 - Very limited
 - Moderately limited
 - Slightly limited
 - Not limited
 - Not rated or not available
 - Soil Rating Points**
 - Very limited
 - Moderately limited
 - Slightly limited
 - Not limited
 - Not rated or not available
- Water Features**
 - Streams and Canals
- Transportation**
 - Rails
 - Interstate Highways
- Background**
 - US Routes
 - Major Roads
 - Local Roads
 - Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background

Custom Soil Resource Report

MAP LEGEND

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Tables—Septic System AB Soil System (Alternate) (PA)

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|------------------------|--|--------------------|--------------------------|--|--------------|----------------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | Slightly limited | Culleoka (85%) | Slope (0.40) | 7.2 | 18.5% |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Dormont (10%) | Slope (0.35) | | |
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Lowell (5%) | Slope (0.40) | | |
| Potential karst (0.30) | | | | | | |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | Moderately limited | Culleoka (80%) | Too steep (0.85) | 8.2 | 18.6% |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Dormont (15%) | Too steep (0.85) | | |
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Lowell (5%) | Too steep (0.85) | | |
| Potential karst (0.30) | | | | | | |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | Very limited | Culleoka (80%) | Too steep (1.00) | 0.4 | 0.9% |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Dormont (15%) | Too steep (1.00) | | |
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Lowell (5%) | Too steep (1.00) | | |
| Potential karst (0.30) | | | | | | |
| DoB | Dormont silt loam, 3 to 8 percent slopes | Slightly limited | Dormont (75%) | Slope (0.35) | 4.9 | 11.2% |
| | | | | Potential karst (0.30) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|--------------------|--------------------------|--|--------------|----------------|
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Culleoka (10%) | Slope (0.35) | | |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Lowell (10%) | Slope (0.35) | | |
| | | | | Potential karst (0.30) | | |
| | | | Guernsey (5%) | Low potential seasonal high water table (0.42) | | |
| | | | | Slope (0.35) | | |
| | | | | Potential karst (0.30) | | |
| DoC | Dormont silt loam, 8 to 15 percent slopes | Moderately limited | Dormont (70%) | Too steep (0.85) | 7.6 | 17.3% |
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Culleoka (15%) | Too steep (0.85) | | |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Lowell (10%) | Too steep (0.85) | | |
| | | | | Potential karst (0.30) | | |
| | | | Guernsey (5%) | Too steep (0.85) | | |
| | | | | Low potential seasonal high water table (0.42) | | |
| | | | | Potential karst (0.30) | | |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Moderately limited | Guernsey (85%) | Too steep (0.85) | 1.0 | 2.3% |
| | | | | Low potential seasonal high water table (0.42) | | |
| | | | | Potential karst (0.30) | | |
| | | | Berks (5%) | Too steep (0.85) | | |
| | | | | Potential bedrock near 16" (0.28) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|--------------------|--------------------------|---|--------------|----------------|
| | | | Westmoreland (5%) | Too steep (0.85) Potential bedrock near 16" (0.01) | | |
| | | | Coshocton (5%) | Too steep (0.85) Potential seasonal high water table (0.84) | | |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Moderately limited | Library (70%) | Seasonal high water table (0.92) Slope (0.31) Potential karst (0.30) | 2.9 | 6.5% |
| UdB | Udorthents, smoothed, gently sloping | Slightly limited | Udorthents (99%) | Slope (0.31) | 0.9 | 2.0% |
| UdD | Udorthents, smoothed, moderately steep | Very limited | Udorthents (99%) | Too steep (1.00) | 1.6 | 3.6% |
| | | | Wet spots (1%) | Miscellaneous area (1.00) Seasonal high water table (1.00) Slope (0.18) | | |
| WeB | Weikert-Culleoka complex, 3 to 8 percent slopes | Moderately limited | Weikert (60%) | Potential bedrock near 16" (0.70) Slope (0.40) Slight voided fragments (0.09) | 7.4 | 16.8% |
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | Moderately limited | Weikert (50%) | Too steep (0.85) Potential bedrock near 16" (0.70) Slight voided fragments (0.09) | 1.9 | 4.3% |
| | | | Culleoka (40%) | Too steep (0.85) Potential bedrock near 16" (0.22) | | |
| | | | Brooke (5%) | Too steep (0.85) Potential bedrock near 16" (0.25) | | |
| | | | Dormont (5%) | Too steep (0.85) Potential karst (0.30) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|------------------------------------|---------------|--------|--------------------------|--|--------------|----------------|
| | | | | Low potential seasonal high water table (0.01) | | |
| Totals for Area of Interest | | | | | 43.8 | 100.0% |

| Rating | Acres in AOI | Percent of AOI |
|------------------------------------|--------------|----------------|
| Moderately limited | 28.8 | 65.8% |
| Slightly limited | 13.0 | 29.7% |
| Very limited | 2.0 | 4.5% |
| Totals for Area of Interest | 43.8 | 100.0% |

Rating Options—Septic System AB Soil System (Alternate) (PA)

Aggregation Method: Dominant Condition

Aggregation is the process by which a set of component attribute values is reduced to a single value that represents the map unit as a whole.

A map unit is typically composed of one or more "components". A component is either some type of soil or some nonsoil entity, e.g., rock outcrop. For the attribute being aggregated, the first step of the aggregation process is to derive one attribute value for each of a map unit's components. From this set of component attributes, the next step of the aggregation process derives a single value that represents the map unit as a whole. Once a single value for each map unit is derived, a thematic map for soil map units can be rendered. Aggregation must be done because, on any soil map, map units are delineated but components are not.

For each of a map unit's components, a corresponding percent composition is recorded. A percent composition of 60 indicates that the corresponding component typically makes up approximately 60% of the map unit. Percent composition is a critical factor in some, but not all, aggregation methods.

The aggregation method "Dominant Condition" first groups like attribute values for the components in a map unit. For each group, percent composition is set to the sum of the percent composition of all components participating in that group. These groups now represent "conditions" rather than components. The attribute value associated with the group with the highest cumulative percent composition is returned. If more than one group shares the highest cumulative percent composition, the corresponding "tie-break" rule determines which value should be returned. The "tie-break" rule indicates whether the lower or higher group value should be returned in the case of a percent composition tie. The result returned by this aggregation method represents the dominant condition throughout the map unit only when no tie has occurred.

Component Percent Cutoff: None Specified

Custom Soil Resource Report

Components whose percent composition is below the cutoff value will not be considered. If no cutoff value is specified, all components in the database will be considered. The data for some contrasting soils of minor extent may not be in the database, and therefore are not considered.

Tie-break Rule: Higher

The tie-break rule indicates which value should be selected from a set of multiple candidate values, or which value should be selected in the event of a percent composition tie.

Septic System At-Grade Bed (Alternate) (PA)

This system is currently listed as an alternate system in the Pennsylvania regulations. It distributes effluent from a septic tank and pumping tank into distribution lines in aggregate material placed on the surface of the natural soil. The aggregate material is at least 10 inches thick. Only the part of the soils between depths of 0 and 48 inches is considered when the soils are rated.

The soil properties and site features considered are those that affect absorption of the effluent and construction and maintenance of the system and those that may affect public health. These include depth to a water table, depth to bedrock, content of rock fragments, flooding, slope, and saturated hydraulic conductivity (Ksat). Flooding is a serious problem because it can result in improper treatment of the effluent and contamination of ground water or surface water. If Ksat is too fast or too slow, if the content of rock fragments is too high, or if the water table is too close to the surface, the effluent can contaminate the ground water. If this system is improperly installed on the steeper slopes, the effluent could flow along the surface of the soils. Additional grading may be needed in areas downslope from the system.

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. "Slightly limited" indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. "Moderately limited" indicates that the soil has features that are somewhat favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer

Custom Soil Resource Report

are determined by the aggregation method chosen, which is displayed on the report. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is presented to help the user better understand the percentage of each map unit that has the rating presented.

Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the Selected Soil Interpretations report with this interpretation included from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.

Custom Soil Resource Report
 Map—Septic System At-Grade Bed (Alternate) (PA)















Map Scale: 1:4,310 if printed on A portrait (8.5" x 11") sheet.

0 50 100 200 300 Meters

0 200 400 800 1200 Feet

Map projection: Web Mercator Corner coordinates: WGS84 Edge ticks: UTM Zone 17N WGS84

MAP LEGEND

-  Area of Interest (AOI)
-  Area of Interest (AOI)
- Soils**
- Soil Rating Polygons**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
- Soil Rating Lines**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
- Soil Rating Points**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
- Water Features**
-  Streams and Canals
- Transportation**
-  Rails
-  Interstate Highways
-  US Routes
-  Major Roads
-  Local Roads
-  Background
-  Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background



Custom Soil Resource Report

MAP LEGEND

MAP INFORMATION

Imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Tables—Septic System At-Grade Bed (Alternate) (PA)

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------------------------|--|--------------|--------------------------|----------------------------------|--------------|----------------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | Very limited | Culleoka (85%) | Bedrock, above 48" (1.00) | 7.2 | 16.5% |
| | | | | Slope (0.40) | | |
| | | | Dormont (10%) | Seasonal high water table (1.00) | | |
| | | | | Slow percolation 12-20" (1.00) | | |
| | | | | Slope (0.35) | | |
| Potential karst (0.30) | | | | | | |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | Very limited | Culleoka (80%) | Bedrock, above 48" (1.00) | 8.2 | 18.6% |
| | | | | Too steep (0.85) | | |
| | | | Dormont (15%) | Seasonal high water table (1.00) | | |
| | | | | Slow percolation 12-20" (1.00) | | |
| | | | | Too steep (0.85) | | |
| Potential karst (0.30) | | | | | | |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | Very limited | Culleoka (80%) | Bedrock, above 48" (1.00) | 0.4 | 0.9% |
| | | | | Too steep (1.00) | | |
| | | | Dormont (15%) | Seasonal high water table (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-20" (1.00) | | |
| | | | Lowell (5%) | Potential karst (0.30) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-20" (0.50) | | |
| Potential karst (0.30) | | | | | | |
| Potential bedrock near 48" (0.04) | | | | | | |
| DoB | Dormont silt loam, 3 to 8 percent slopes | Very limited | Dormont (75%) | Seasonal high water table (1.00) | 4.9 | 11.2% |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|--------------|--------------------------|----------------------------------|--------------|----------------|
| | | | | Slow percolation 12-20" (1.00) | | |
| | | | | Slope (0.35) | | |
| | | | | Potential karst (0.30) | | |
| | | | Culleoka (10%) | Bedrock, above 48" (1.00) | | |
| | | | | Slope (0.35) | | |
| | | | Guernsey (5%) | Seasonal high water table (1.00) | | |
| | | | | Slow percolation 12-20" (0.58) | | |
| | | | | Slope (0.35) | | |
| | | | | Potential karst (0.30) | | |
| DoC | Dormont silt loam, 8 to 15 percent slopes | Very limited | Dormont (70%) | Seasonal high water table (1.00) | 7.8 | 17.3% |
| | | | | Slow percolation 12-20" (1.00) | | |
| | | | | Too steep (0.85) | | |
| | | | | Potential karst (0.30) | | |
| | | | Culleoka (15%) | Bedrock, above 48" (1.00) | | |
| | | | | Too steep (0.85) | | |
| | | | Guernsey (5%) | Seasonal high water table (1.00) | | |
| | | | | Too steep (0.85) | | |
| | | | | Slow percolation 12-20" (0.58) | | |
| | | | | Potential karst (0.30) | | |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Very limited | Guernsey (85%) | Seasonal high water table (1.00) | 1.0 | 2.3% |
| | | | | Too steep (0.85) | | |
| | | | | Slow percolation 12-20" (0.58) | | |
| | | | | Potential karst (0.30) | | |
| | | | Berks (5%) | Bedrock, above 48" (1.00) | | |
| | | | | Too steep (0.85) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|------------------|--------------------------|---|--------------|----------------|
| | | | Westmoreland (5%) | Bedrock, above 48" (1.00) Too steep (0.85) | | |
| | | | Coshocton (5%) | Seasonal high water table (1.00) Too steep (0.85) Slow percolation 12-20" (0.79) Potential bedrock near 48" (0.10) | | |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Very limited | Library (70%) | Seasonal high water table (1.00) Slow percolation 12-20" (1.00) Slope (0.31) Potential karst (0.30) | 2.9 | 6.5% |
| | | | Guernsey (15%) | Seasonal high water table (1.00) Slope (0.35) Potential karst (0.30) Potential bedrock near 48" (0.20) | | |
| | | | Culleoka (10%) | Bedrock, above 48" (1.00) Slope (0.40) | | |
| | | | Dormont (5%) | Seasonal high water table (1.00) Slope (0.31) Potential karst (0.30) | | |
| UdB | Udorthents, smoothed, gently sloping | Slightly limited | Udorthents (99%) | Slope (0.31) Potential fast percolation 12-20" (0.17) | 0.9 | 2.0% |
| UdD | Udorthents, smoothed, moderately steep | Very limited | Udorthents (99%) | Too steep (1.00) Potential fast percolation 12-20" (0.17) | 1.6 | 3.6% |
| | | | Wet spots (1%) | Seasonal high water table (1.00) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|----------------------------------|--|--------------|--------------------------|--|--------------|----------------|
| WeB | Weikert-Culleoka complex, 3 to 8 percent slopes | Very limited | | Miscellaneous area (1.00) | 7.4 | 16.8% |
| | | | | Slope (0.18) | | |
| | | | Weikert (60%) | Bedrock, above 48" (1.00) | | |
| | | | | Slope (0.40) | | |
| | | | | Slight voided fragments (0.09) | | |
| | | | Culleoka (30%) | Bedrock, above 48" (1.00) | | |
| | | | | Slope (0.40) | | |
| | | | Dekalb (5%) | Bedrock, above 48" (1.00) | | |
| | | | | Potential fast percolation 12-20" (0.50) | | |
| | | | Brooke (3%) | Slope (0.40) | | |
| | | | | Bedrock, above 48" (1.00) | | |
| | | | | Slow percolation 12-20" (1.00) | | |
| | | | Dormont (2%) | Slope (0.40) | | |
| Seasonal high water table (1.00) | | | | | | |
| Slope (0.31) | | | | | | |
| | Potential karst (0.30) | | | | | |
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | Very limited | Weikert (50%) | Bedrock, above 48" (1.00) | 1.9 | 4.3% |
| | | | | Too steep (0.85) | | |
| | | | | Slight voided fragments (0.09) | | |
| | | | Culleoka (40%) | Bedrock, above 48" (1.00) | | |
| | | | | Too steep (0.85) | | |
| | | | Brooke (5%) | Bedrock, above 48" (1.00) | | |
| | | | | Slow percolation 12-20" (1.00) | | |
| | | | | Too steep (0.85) | | |
| | | | Dormont (5%) | Seasonal high water table (1.00) | | |
| | | | | | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres In AOI | Percent of AOI |
|------------------------------------|---------------|--------|--------------------------|--|--------------|----------------|
| | | | | Too steep (0.85) Potential karst (0.30) | | |
| Totals for Area of Interest | | | | | 43.8 | 100.0% |

| Rating | Acres In AOI | Percent of AOI |
|------------------------------------|--------------|----------------|
| Very limited | 42.8 | 98.0% |
| Slightly limited | 0.9 | 2.0% |
| Totals for Area of Interest | 43.8 | 100.0% |

Rating Options—Septic System At-Grade Bed (Alternate) (PA)

Aggregation Method: Dominant Condition

Component Percent Cutoff: None Specified

Tie-break Rule: Higher

Septic System CO-OP RFS III With At-Grade Bed (PA)

This system is currently listed as an alternate system in the Pennsylvania regulations. It distributes effluent from a septic tank and pumping tank into distribution lines in aggregate material placed on the surface of the natural soil. The aggregate material is at least 10 inches thick. Only the part of the soils between depths of 0 and 16 inches is considered when the soils are rated.

The soil properties and site features considered are those that affect absorption of the effluent and construction and maintenance of the system and those that may affect public health. These include depth to a water table, depth to bedrock, content of rock fragments, flooding, slope, and saturated hydraulic conductivity (Ksat). Flooding is a serious problem because it can result in improper treatment of the effluent and contamination of ground water or surface water. If Ksat is too fast or too slow, if the content of rock fragments is too high, or if the water table is too close to the surface, the effluent can contaminate the ground water. If this system is improperly installed on the steeper slopes, the effluent could flow along the surface of the soils. Additional grading may be needed in areas downslope from the system.

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. "Slightly limited" indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. "Moderately limited" indicates that the soil has features that are somewhat favorable for the specified use. The

Custom Soil Resource Report

limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer are determined by the aggregation method chosen, which is displayed on the report. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is presented to help the user better understand the percentage of each map unit that has the rating presented.

Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the Selected Soil Interpretations report with this interpretation included from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.

Custom Soil Resource Report
 Map—Septic System CO-OP RFS III With At-Grade Bed (PA)



Map Scale: 1:4,310 if printed on A portrait (8.5" x 11") sheet.

0 50 100 200 300 Meters

0 200 400 800 1200 Feet

Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 17N WGS84

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.
























Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background

MAP LEGEND

-  Area of Interest (AOI)
-  Area of Interest (AOI)
- Soils**
- Soil Rating Polygons**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
- Soil Rating Lines**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
- Soil Rating Points**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
- Water Features**
-  Streams and Canals
- Transportation**
-  Rails
-  Interstate Highways
-  US Routes
-  Major Roads
-  Local Roads
- Background**
-  Aerial Photography

Custom Soil Resource Report

MAP LEGEND

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Tables—Septic System CO-OP RFS III With At-Grade Bed (PA)

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres In AOI | Percent of AOI |
|------------------------|--|---|--------------------------|--|--------------|----------------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | Slightly limited (soil morphological evaluation needed) | Culleoka (85%) | Slope (0.40) | 7.2 | 16.5% |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Dormont (10%) | Slope (0.35) | | |
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Lowell (5%) | Slope (0.40) | | |
| Potential karst (0.30) | | | | | | |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | Moderately limited (soil morphological evaluation needed) | Culleoka (80%) | Too steep (0.85) | 8.2 | 18.6% |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Dormont (15%) | Too steep (0.85) | | |
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Lowell (5%) | Too steep (0.85) | | |
| Potential karst (0.30) | | | | | | |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | Very limited (soil morphological evaluation needed) | Culleoka (80%) | Too steep (1.00) | 0.4 | 0.9% |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Dormont (15%) | Too steep (1.00) | | |
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Lowell (5%) | Too steep (1.00) | | |
| Potential karst (0.30) | | | | | | |
| DoB | Dormont silt loam, 3 to 8 percent slopes | Slightly limited (soil morphological evaluation needed) | Dormont (75%) | Slope (0.35) | 4.9 | 11.2% |
| | | | | Potential karst (0.30) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres In AOI | Percent of AOI |
|-----------------|--|---|--------------------------|--|--------------|----------------|
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Culleoka (10%) | Slope (0.35) Potential bedrock near 16" (0.22) | | |
| | | | Lowell (10%) | Slope (0.35) Potential karst (0.30) | | |
| | | | Guernsey (5%) | Low potential seasonal high water table (0.42) Slope (0.35) Potential karst (0.30) | | |
| DoC | Dormont silt loam, 8 to 15 percent slopes | Moderately limited (soil morphological evaluation needed) | Dormont (70%) | Too steep (0.85) Potential karst (0.30) Low potential seasonal high water table (0.02) | 7.6 | 17.3% |
| | | | Culleoka (15%) | Too steep (0.85) Potential bedrock near 16" (0.22) | | |
| | | | Lowell (10%) | Too steep (0.85) Potential karst (0.30) | | |
| | | | Guernsey (5%) | Too steep (0.85) Low potential seasonal high water table (0.42) Potential karst (0.30) | | |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Moderately limited (soil morphological evaluation needed) | Guernsey (85%) | Too steep (0.85) Low potential seasonal high water table (0.42) Potential karst (0.30) | 1.0 | 2.3% |
| | | | Berks (5%) | Too steep (0.85) Potential bedrock near 16" (0.28) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|---|--------------------------|---|--------------|----------------|
| | | | Westmoreland (5%) | Too steep (0.85) Potential bedrock near 16" (0.01) | | |
| | | | Coshocton (5%) | Too steep (0.85) Potential seasonal high water table (0.84) | | |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Moderately limited (soil morphological evaluation needed) | Library (70%) | Seasonal high water table (0.92) Slope (0.31) Potential karst (0.30) | 2.9 | 6.5% |
| UdB | Udortheints, smoothed, gently sloping | Slightly limited (soil morphological evaluation needed) | Udortheints (99%) | Slope (0.31) | 0.9 | 2.0% |
| UdD | Udortheints, smoothed, moderately steep | Very limited (soil morphological evaluation needed) | Udortheints (99%) | Too steep (1.00) | 1.6 | 3.6% |
| | | | Wet spots (1%) | Seasonal high water table (1.00) Miscellaneous area (1.00) Slope (0.18) | | |
| WeB | Weikert-Culleoka complex, 3 to 8 percent slopes | Moderately limited (soil morphological evaluation needed) | Weikert (60%) | Potential bedrock near 16" (0.70) Slope (0.40) Slight voided fragments (0.09) | 7.4 | 16.8% |
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | Moderately limited (soil morphological evaluation needed) | Weikert (50%) | Too steep (0.85) Potential bedrock near 16" (0.70) Slight voided fragments (0.09) | 1.9 | 4.3% |
| | | | Culleoka (40%) | Too steep (0.85) Potential bedrock near 16" (0.22) | | |
| | | | Brooke (5%) | Too steep (0.85) Potential bedrock near 16" (0.25) | | |
| | | | Dormont (5%) | Too steep (0.85) Potential karst (0.30) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|------------------------------------|---------------|--------|--------------------------|--|--------------|----------------|
| | | | | Low potential seasonal high water table (0.01) | | |
| Totals for Area of Interest | | | | | 43.8 | 100.0% |

| Rating | Acres in AOI | Percent of AOI |
|---|--------------|----------------|
| Moderately limited (soil morphological evaluation needed) | 28.8 | 65.8% |
| Slightly limited (soil morphological evaluation needed) | 13.0 | 29.7% |
| Very limited (soil morphological evaluation needed) | 2.0 | 4.5% |
| Totals for Area of Interest | 43.8 | 100.0% |

Rating Options—Septic System CO-OP RFS III With At-Grade Bed (PA)

Aggregation Method: Dominant Condition

Component Percent Cutoff: None Specified

Tie-break Rule: Higher

Septic System Free-Access Sand Filter - Drip Irrigation (PA)

This system is currently listed as an alternate system in the Pennsylvania regulations. It distributes effluent from a septic tank into a free-access sand filter and hydraulic filtration unit and then into the natural soil. The maximum depth of the drip tubing is 12 inches. Only the part of the soils between depths of 0 and 20 inches is considered when the soils are rated.

The soil properties and site features considered are those that affect absorption of the effluent and construction and maintenance of the system and those that may affect public health. These include depth to a water table, depth to bedrock, content of rock fragments, flooding, slope, and saturated hydraulic conductivity (Ksat). Flooding is a serious problem because it can result in improper treatment of the effluent and contamination of ground water or surface water. If Ksat is too fast or too slow, if the content of rock fragments is too high, or if the water table is too close to the surface, the effluent can contaminate the ground water. If this system is improperly installed on the steeper slopes, the effluent could flow along the surface of the soils. Additional grading may be needed in areas downslope from the system.

Custom Soil Resource Report

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. "Slightly limited" indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. "Moderately limited" indicates that the soil has features that are somewhat favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.


Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

These ratings do not preclude the need for onsite investigation to determine the limitations affecting system placement. This septic system requires a soil morphological evaluation, which must be conducted by a qualified soil scientist.

The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer are determined by the aggregation method chosen, which is displayed on the report. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is presented to help the user better understand the percentage of each map unit that has the rating presented.

Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the Selected Soil Interpretations report with this interpretation included from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.

Custom Soil Resource Report
 Map—Septic System Free-Access Sand Filter - Drip Irrigation (PA)



Soil Map may not be valid at this scale.


Map Scale: 1:4,310 if printed on A portrait (8.5" x 11") sheet.

0 50 100 200 300 Meters

0 200 400 600 1200 Feet

Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 17N WGS84

MAP LEGEND

| | |
|--|--|
|  Area of Interest (AOI) |  US Routes |
|  Area of Interest (AOI) |  Major Roads |
|  Soils |  Local Roads |
|  Soil Rating Polygons |  Background |
|  Very limited |  Aerial Photography |
|  Moderately limited | |
|  Slightly limited | |
|  Not limited | |
|  Not rated or not available | |
|  Soil Rating Lines | |
|  Very limited | |
|  Moderately limited | |
|  Slightly limited | |
|  Not limited | |
|  Not rated or not available | |
|  Soil Rating Points | |
|  Very limited | |
|  Moderately limited | |
|  Slightly limited | |
|  Not limited | |
|  Not rated or not available | |
|  Water Features | |
|  Streams and Canals | |
|  Transportation | |
|  Rails | |
|  Interstate Highways | |

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background



Custom Soil Resource Report

MAP LEGEND

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Tables—Septic System Free-Access Sand Filter - Drip Irrigation (PA)

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|--------------------|--------------------------|--|--------------|----------------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | Slightly limited | Culleoka (85%) | Potential bedrock near 20" (0.23) | 7.2 | 16.5% |
| | | | | Slope (0.12) | | |
| | | | Dormont (10%) | Low potential seasonal high water table (0.45) | | |
| | | | | Potential karst (0.30) | | |
| | | | Slope (0.08) | | | |
| | | | Lowell (5%) | Potential karst (0.30) | | |
| | | | | Slope (0.12) | | |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | Slightly limited | Culleoka (80%) | Slope (0.46) | 8.2 | 18.6% |
| | | | | Potential bedrock near 20" (0.23) | | |
| | | | Dormont (15%) | Slope (0.46) | | |
| | | | | Low potential seasonal high water table (0.45) | | |
| | | | Potential karst (0.30) | | | |
| | | | Lowell (5%) | Slope (0.46) | | |
| | | | | Potential karst (0.30) | | |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | Moderately limited | Culleoka (80%) | Too steep (0.92) | 0.4 | 0.9% |
| | | | | Potential bedrock near 20" (0.23) | | |
| | | | Dormont (15%) | Too steep (0.92) | | |
| | | | | Low potential seasonal high water table (0.45) | | |
| | | | Potential karst (0.30) | | | |
| | | | Lowell (5%) | Too steep (0.92) | | |
| | | | | Potential karst (0.30) | | |
| DoB | Dormont silt loam, 3 to 8 percent slopes | Slightly limited | Dormont (75%) | Low potential seasonal high water table (0.45) | 4.9 | 11.2% |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|---|--------------------|--------------------------|--|--------------|----------------|
| | | | | Potential karst (0.30) Slope (0.08) | | |
| | | | Culleoka (10%) | Potential bedrock near 20" (0.23) Slope (0.08) | | |
| | | | Lowell (10%) | Potential karst (0.30) Slope (0.08) | | |
| DoC | Dormont silt loam, 8 to 15 percent slopes | Slightly limited | Dormont (70%) | Slope (0.46) Low potential seasonal high water table (0.45) Potential karst (0.30) | 7.6 | 17.3% |
| | | | Culleoka (15%) | Slope (0.46) Potential bedrock near 20" (0.23) | | |
| | | | Lowell (10%) | Slope (0.46) Potential karst (0.30) | | |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Moderately limited | Guernsey (85%) | Potential seasonal high water table (0.84) Slope (0.46) Potential karst (0.30) | 1.0 | 2.3% |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Very limited | Library (70%) | Potential seasonal high water table (1.00) Potential karst (0.30) Slope (0.05) | 2.9 | 6.5% |
| UdB | Udorthents, smoothed, gently sloping | Slightly limited | Udorthents (99%) | Slope (0.05) | 0.9 | 2.0% |
| UdD | Udorthents, smoothed, moderately steep | Moderately limited | Udorthents (99%) | Slope (0.80) | 1.6 | 3.6% |
| WeB | Weikert-Culleoka complex, 3 to 8 percent slopes | Very limited | Weikert (60%) | Bedrock, above 20" (1.00) Slope (0.12) | 7.4 | 16.8% |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------------------|--|--------------|--------------------------|---------------------------------|--------------|----------------|
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | Very limited | Weikert (50%) | Slight voided fragments (0.09) | 1.9 | 4.3% |
| | | | | Bedrock, above 20" (1.00) | | |
| | | | | Slope (0.46) | | |
| Totals for Area of Interest | | | | | 43.8 | 100.0% |

| Rating | Acres in AOI | Percent of AOI |
|-----------------------------|--------------|----------------|
| Slightly limited | 28.8 | 65.6% |
| Very limited | 12.1 | 27.6% |
| Moderately limited | 3.0 | 6.7% |
| Totals for Area of Interest | 43.8 | 100.0% |

Rating Options—Septic System Free-Access Sand Filter - Drip Irrigation (PA)

Aggregation Method: Dominant Condition

Aggregation is the process by which a set of component attribute values is reduced to a single value that represents the map unit as a whole.

A map unit is typically composed of one or more "components". A component is either some type of soil or some nonsoil entity, e.g., rock outcrop. For the attribute being aggregated, the first step of the aggregation process is to derive one attribute value for each of a map unit's components. From this set of component attributes, the next step of the aggregation process derives a single value that represents the map unit as a whole. Once a single value for each map unit is derived, a thematic map for soil map units can be rendered. Aggregation must be done because, on any soil map, map units are delineated but components are not.

For each of a map unit's components, a corresponding percent composition is recorded. A percent composition of 60 indicates that the corresponding component typically makes up approximately 60% of the map unit. Percent composition is a critical factor in some, but not all, aggregation methods.

The aggregation method "Dominant Condition" first groups like attribute values for the components in a map unit. For each group, percent composition is set to the sum of the percent composition of all components participating in that group. These groups now represent "conditions" rather than components. The attribute value associated with the group with the highest cumulative percent composition is returned. If more than one group shares the highest cumulative percent composition, the corresponding "tie-break" rule determines which value should be

Custom Soil Resource Report

returned. The "tie-break" rule indicates whether the lower or higher group value should be returned in the case of a percent composition tie. The result returned by this aggregation method represents the dominant condition throughout the map unit only when no tie has occurred.

Component Percent Cutoff: None Specified

Components whose percent composition is below the cutoff value will not be considered. If no cutoff value is specified, all components in the database will be considered. The data for some contrasting soils of minor extent may not be in the database, and therefore are not considered.

Tie-break Rule: Higher

The tie-break rule indicates which value should be selected from a set of multiple candidate values, or which value should be selected in the event of a percent composition tie.

Septic System Drip Irrigation (Alternate) (PA)

This system is currently listed as an alternate system in the Pennsylvania regulations. It is a subsurface system of drip tubing that distributes effluent from a septic tank, intermittent sand filter tank, and hydraulic filtration unit into the natural soil. The maximum depth of the drip tubing is 12 inches. Only the part of the soils between depths of 0 and 20 inches is considered when the soils are rated.

The soil properties and site features considered are those that affect absorption of the effluent and construction and maintenance of the system and those that may affect public health. These include depth to a water table, depth to bedrock, content of rock fragments, flooding, slope, and saturated hydraulic conductivity (Ksat). Flooding is a serious problem because it can result in improper treatment of the effluent and contamination of ground water or surface water. If Ksat is too fast or too slow, if the content of rock fragments is too high, or if the water table is too close to the surface, the effluent can contaminate the ground water. If this system is improperly installed on the steeper slopes, the effluent could flow along the surface of the soils. Additional grading may be needed in areas downslope from the system.

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. "Slightly limited" indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. "Moderately limited" indicates that the soil has features that are somewhat favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Custom Soil Resource Report


Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

These ratings do not preclude the need for onsite investigation to determine the limitations affecting system placement. This septic system requires a soil morphological evaluation, which must be conducted by a qualified soil scientist.


The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer are determined by the aggregation method chosen, which is displayed on the report. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is presented to help the user better understand the percentage of each map unit that has the rating presented.

Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the Selected Soil Interpretations report with this interpretation included from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.


Custom Soil Resource Report
 Map—Septic System Drip Irrigation (Alternate) (PA)



Soil Map may not be valid at this scale.



MAP LEGEND



MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background



Custom Soil Resource Report

MAP LEGEND

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Tables—Septic System Drip Irrigation (Alternate) (PA)

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|--------------------|--------------------------|--|--------------|----------------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | Slightly limited | Culleoka (85%) | Potential bedrock near 20" (0.23) | 7.2 | 16.5% |
| | | | | Slope (0.12) | | |
| | | | Dormont (10%) | Low potential seasonal high water table (0.45) | | |
| | | | | Potential karst (0.30) | | |
| | | | Lowell (5%) | Slope (0.08) | | |
| | | | | Potential karst (0.30) | | |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | Slightly limited | Culleoka (80%) | Slope (0.46) | 8.2 | 18.6% |
| | | | | Potential bedrock near 20" (0.23) | | |
| | | | Dormont (15%) | Slope (0.46) | | |
| | | | | Low potential seasonal high water table (0.45) | | |
| | | | Lowell (5%) | Potential karst (0.30) | | |
| | | | | Slope (0.46) | | |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | Moderately limited | Culleoka (80%) | Too steep (0.92) | 0.4 | 0.9% |
| | | | | Potential bedrock near 20" (0.23) | | |
| | | | Dormont (15%) | Too steep (0.92) | | |
| | | | | Low potential seasonal high water table (0.45) | | |
| | | | Lowell (5%) | Potential karst (0.30) | | |
| | | | | Too steep (0.92) | | |
| DoB | Dormont silt loam, 3 to 8 percent slopes | Slightly limited | Dormont (75%) | Low potential seasonal high water table (0.45) | 4.9 | 11.2% |
| | | | | Potential karst (0.30) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|---|--------------------|--------------------------|--|--------------|----------------|
| | | | | Potential karst (0.30) | | |
| | | | | Slope (0.08) | | |
| | | | Culleoka (10%) | Potential bedrock near 20° (0.23) | | |
| | | | | Slope (0.08) | | |
| | | | Lowell (10%) | Potential karst (0.30) | | |
| | | | | Slope (0.08) | | |
| DoC | Dormont silt loam, 8 to 15 percent slopes | Slightly limited | Dormont (70%) | Slope (0.46) | 7.6 | 17.3% |
| | | | | Low potential seasonal high water table (0.45) | | |
| | | | | Potential karst (0.30) | | |
| | | | Culleoka (15%) | Slope (0.46) | | |
| | | | | Potential bedrock near 20° (0.23) | | |
| | | | Lowell (10%) | Slope (0.46) | | |
| | | | | Potential karst (0.30) | | |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Moderately limited | Guernsey (85%) | Potential seasonal high water table (0.84) | 1.0 | 2.3% |
| | | | | Slope (0.46) | | |
| | | | | Potential karst (0.30) | | |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Very limited | Library (70%) | Potential seasonal high water table (1.00) | 2.9 | 6.5% |
| | | | | Potential karst (0.30) | | |
| | | | | Slope (0.05) | | |
| UdB | Udorthents, smoothed, gently sloping | Slightly limited | Udorthents (99%) | Slope (0.05) | 0.9 | 2.0% |
| UdD | Udorthents, smoothed, moderately steep | Moderately limited | Udorthents (99%) | Slope (0.80) | 1.8 | 3.6% |
| WeB | Weikert-Culleoka complex, 3 to 8 percent slopes | Very limited | Weikert (60%) | Bedrock, above 20° (1.00) | 7.4 | 16.8% |
| | | | | Slope (0.12) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|------------------------------------|--|--------------|--------------------------|---|--------------|----------------|
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | Very limited | Weikert (50%) | Slight voided fragments (0.09) Bedrock, above 20" (1.00) Slope (0.46) Slight voided fragments (0.09) | 1.9 | 4.3% |
| Totals for Area of Interest | | | | | 43.8 | 100.0% |

| Rating | Acres in AOI | Percent of AOI |
|------------------------------------|--------------|----------------|
| Slightly limited | 28.8 | 65.6% |
| Very limited | 12.1 | 27.6% |
| Moderately limited | 3.0 | 6.7% |
| Totals for Area of Interest | 43.8 | 100.0% |

Rating Options—Septic System Drip Irrigation (Alternate) (PA)

Aggregation Method: Dominant Condition

Aggregation is the process by which a set of component attribute values is reduced to a single value that represents the map unit as a whole.

A map unit is typically composed of one or more "components". A component is either some type of soil or some nonsoil entity, e.g., rock outcrop. For the attribute being aggregated, the first step of the aggregation process is to derive one attribute value for each of a map unit's components. From this set of component attributes, the next step of the aggregation process derives a single value that represents the map unit as a whole. Once a single value for each map unit is derived, a thematic map for soil map units can be rendered. Aggregation must be done because, on any soil map, map units are delineated but components are not.

For each of a map unit's components, a corresponding percent composition is recorded. A percent composition of 60 indicates that the corresponding component typically makes up approximately 60% of the map unit. Percent composition is a critical factor in some, but not all, aggregation methods.

The aggregation method "Dominant Condition" first groups like attribute values for the components in a map unit. For each group, percent composition is set to the sum of the percent composition of all components participating in that group. These groups now represent "conditions" rather than components. The attribute value associated with the group with the highest cumulative percent composition is returned. If more than one group shares the highest cumulative percent composition, the corresponding "tie-break" rule determines which value should be returned. The "tie-break" rule indicates whether the lower or higher group value

Custom Soil Resource Report

should be returned in the case of a percent composition tie. The result returned by this aggregation method represents the dominant condition throughout the map unit only when no tie has occurred.

Component Percent Cutoff: None Specified

Components whose percent composition is below the cutoff value will not be considered. If no cutoff value is specified, all components in the database will be considered. The data for some contrasting soils of minor extent may not be in the database, and therefore are not considered.

Tie-break Rule: Higher

The tie-break rule indicates which value should be selected from a set of multiple candidate values, or which value should be selected in the event of a percent composition tie.

Septic System Free-Access Sand Filter With At-Grade Bed (PA)

This system is currently listed as an alternate system in the Pennsylvania regulations. It distributes effluent from a septic tank into a free-access sand filter and pumping tank and then into distribution lines in aggregate material placed on the surface of the natural soil. The aggregate material is at least 10 inches thick. Only the part of the soils between depths of 0 and 20 inches is considered when the soils are rated.

The soil properties and site features considered are those that affect absorption of the effluent and construction and maintenance of the system and those that may affect public health. These include depth to a water table, depth to bedrock, content of rock fragments, flooding, slope, and saturated hydraulic conductivity (Ksat). Flooding is a serious problem because it can result in improper treatment of the effluent and contamination of ground water or surface water. If Ksat is too fast or too slow, if the content of rock fragments is too high, or if the water table is too close to the surface, the effluent can contaminate the ground water. If this system is improperly installed on the steeper slopes, the effluent could flow along the surface of the soils. Additional grading may be needed in areas downslope from the system.

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. "Slightly limited" indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. "Moderately limited" indicates that the soil has features that are somewhat favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.


Custom Soil Resource Report

Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).


The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer are determined by the aggregation method chosen, which is displayed on the report. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is presented to help the user better understand the percentage of each map unit that has the rating presented.

Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the Selected Soil Interpretations report with this interpretation included from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.

Custom Soil Resource Report
 Map—Septic System Free-Access Sand Filter With At-Grade Bed (PA)



Soil Map may not be valid at this scale.



MAP LEGEND

- Area of Interest (AOI)**
 Area of Interest (AOI)
- Soils**
Soil Rating Polygons
 Very limited
 Moderately limited
 Slightly limited
 Not limited
 Not rated or not available
- Soil Rating Lines**
 Very limited
 Moderately limited
 Slightly limited
 Not limited
 Not rated or not available
- Soil Rating Points**
 Very limited
 Moderately limited
 Slightly limited
 Not limited
 Not rated or not available
- Water Features**
 Streams and Canals
- Transportation**
 Rails
 Interstate Highways

- US Routes
- Major Roads
- Local Roads
- Background
- Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background

MAP LEGEND

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Tables—Septic System Free-Access Sand Filter With At-Grade Bed (PA)

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|--------------------------------|--|--------------------|--------------------------|--|--------------|----------------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | Slightly limited | Culleoka (85%) | Slope (0.40) | 7.2 | 16.5% |
| | | | | Potential bedrock near 20" (0.23) | | |
| | | | Lowell (5%) | Slow percolation 12-20" (0.50) | | |
| | | | | Slope (0.40) | | |
| | Potential karst (0.30) | | | | | |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | Moderately limited | Culleoka (80%) | Too steep (0.85) | 8.2 | 18.6% |
| | | | | Potential bedrock near 20" (0.23) | | |
| | | | Lowell (5%) | Too steep (0.85) | | |
| | | | | Slow percolation 12-20" (0.50) | | |
| | Potential karst (0.30) | | | | | |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | Very limited | Culleoka (80%) | Too steep (1.00) | 0.4 | 0.9% |
| | | | | Potential bedrock near 20" (0.23) | | |
| | | | Dormont (15%) | Too steep (1.00) | | |
| | | | | Slow percolation 12-20" (1.00) | | |
| | | | | Low potential seasonal high water table (0.45) | | |
| | | | | Potential karst (0.30) | | |
| | | | Lowell (5%) | Too steep (1.00) | | |
| Slow percolation 12-20" (0.50) | | | | | | |
| | Potential karst (0.30) | | | | | |
| DoB | Dormont silt loam, 3 to 8 percent slopes | Very limited | Dormont (75%) | Slow percolation 12-20" (1.00) | 4.9 | 11.2% |
| | | | | Low potential seasonal high water table (0.45) | | |
| | | | | Slope (0.35) | | |
| | | | | Potential karst (0.30) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|--------------------|-----------------------------------|--|--------------|----------------|
| DoC | Dormont silt loam, 8 to 15 percent slopes | Very limited | Dormont (70%) | Slow percolation 12-20" (1.00) | 7.6 | 17.3% |
| | | | | Too steep (0.85) | | |
| | | | | Low potential seasonal high water table (0.45) | | |
| | | | | Potential karst (0.30) | | |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Moderately limited | Guernsey (85%) | Potential seasonal high water table (0.94) | 1.0 | 2.3% |
| | | | | Too steep (0.85) | | |
| | | | | Slow percolation 12-20" (0.58) | | |
| | | | | Potential karst (0.30) | | |
| | | | Berks (5%) | Too steep (0.85) | | |
| | | | Potential bedrock near 20" (0.32) | | | |
| | | | Westmoreland (5%) | Too steep (0.85) | | |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Very limited | Library (70%) | Potential seasonal high water table (1.00) | 2.9 | 6.5% |
| | | | | Slow percolation 12-20" (1.00) | | |
| | | | | Slope (0.31) | | |
| | | | | Potential karst (0.30) | | |
| UdB | Udorthents, smoothed, gently sloping | Slightly limited | Udorthents (99%) | Slope (0.31) | 0.9 | 2.0% |
| | | | | Potential fast percolation 12-20" (0.17) | | |
| UdD | Udorthents, smoothed, moderately steep | Very limited | Udorthents (99%) | Too steep (1.00) | 1.6 | 3.6% |
| | | | | Potential fast percolation 12-20" (0.17) | | |
| | | | Wet spots (1%) | Potential seasonal high water table (1.00) | | |
| | | | Miscellaneous area (1.00) | Slope (0.18) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres In AOI | Percent of AOI |
|------------------------------------|--|--------------|--------------------------|-----------------------------------|--------------|----------------|
| WeB | Weikert-Culleoka complex, 3 to 8 percent slopes | Very limited | Weikert (60%) | Bedrock, above 20" (1.00) | 7.4 | 16.8% |
| | | | | Slope (0.40) | | |
| | | | | Slight voided fragments (0.09) | | |
| | | | Brooke (3%) | Slow percolation 12-20" (1.00) | | |
| | | | | Slope (0.40) | | |
| | | | | Potential bedrock near 20" (0.27) | | |
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | Very limited | Weikert (50%) | Bedrock, above 20" (1.00) | 1.9 | 4.3% |
| | | | | Too steep (0.85) | | |
| | | | | Slight voided fragments (0.09) | | |
| | | | Brooke (5%) | Slow percolation 12-20" (1.00) | | |
| | | | | Too steep (0.85) | | |
| | | | | Potential bedrock near 20" (0.27) | | |
| Totals for Area of Interest | | | | | 43.8 | 100.0% |

| Rating | Acres In AOI | Percent of AOI |
|------------------------------------|--------------|----------------|
| Very limited | 26.6 | 60.7% |
| Moderately limited | 9.1 | 20.9% |
| Slightly limited | 8.1 | 18.5% |
| Totals for Area of Interest | 43.8 | 100.0% |

Rating Options—Septic System Free-Access Sand Filter With At-Grade Bed (PA)

Aggregation Method: Dominant Condition

Aggregation is the process by which a set of component attribute values is reduced to a single value that represents the map unit as a whole.

A map unit is typically composed of one or more "components". A component is either some type of soil or some nonsoil entity, e.g., rock outcrop. For the attribute being aggregated, the first step of the aggregation process is to derive one attribute value for each of a map unit's components. From this set of component attributes, the next step of the aggregation process derives a single value that represents the map unit as a whole. Once a single value for each map unit is derived, a thematic

Custom Soil Resource Report

map for soil map units can be rendered. Aggregation must be done because, on any soil map, map units are delineated but components are not.

For each of a map unit's components, a corresponding percent composition is recorded. A percent composition of 60 indicates that the corresponding component typically makes up approximately 60% of the map unit. Percent composition is a critical factor in some, but not all, aggregation methods.

The aggregation method "Dominant Condition" first groups like attribute values for the components in a map unit. For each group, percent composition is set to the sum of the percent composition of all components participating in that group. These groups now represent "conditions" rather than components. The attribute value associated with the group with the highest cumulative percent composition is returned. If more than one group shares the highest cumulative percent composition, the corresponding "tie-break" rule determines which value should be returned. The "tie-break" rule indicates whether the lower or higher group value should be returned in the case of a percent composition tie. The result returned by this aggregation method represents the dominant condition throughout the map unit only when no tie has occurred.

Component Percent Cutoff: None Specified

Components whose percent composition is below the cutoff value will not be considered. If no cutoff value is specified, all components in the database will be considered. The data for some contrasting soils of minor extent may not be in the database, and therefore are not considered.

Tie-break Rule: Higher

The tie-break rule indicates which value should be selected from a set of multiple candidate values, or which value should be selected in the event of a percent composition tie.

Septic System In-Ground Bed (Conventional) (PA)

This is a system of subsurface lines that distribute effluent from a septic tank into the natural soil. The distribution lines are at a minimum depth of 12 inches. Only the part of the soils between depths of 0 and 60 inches is considered when the soils are rated.

The soil properties and site features considered are those that affect absorption of the effluent and construction and maintenance of the system and those that may affect public health. These include depth to a water table, depth to bedrock, content of rock fragments, flooding, slope, and saturated hydraulic conductivity (Ksat). Flooding is a serious problem because it can result in improper treatment of the effluent and contamination of ground water or surface water. If Ksat is too fast or too slow, if the content of rock fragments is too high, or if the water table is too close to the surface, the effluent can contaminate the ground water. If this system is improperly installed on the steeper slopes, the effluent could flow along the surface of the soils. Additional grading may be needed in areas downslope from the system.

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the

Custom Soil Resource Report

specified use. Good performance and very low maintenance can be expected. "Slightly limited" indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. "Moderately limited" indicates that the soil has features that are somewhat favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer are determined by the aggregation method chosen, which is displayed on the report. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is presented to help the user better understand the percentage of each map unit that has the rating presented.


Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the Selected Soil Interpretations report with this interpretation included from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.

Custom Soil Resource Report
Map—Septic System In-Ground Bed (Conventional) (PA)























Soil Map may not be valid at this scale.

Map Scale: 1:4,310 if printed on A portrait (8.5" x 11") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 17N WGS84

MAP LEGEND

-  Area of Interest (AOI)
-  Area of Interest (AOI)
- Soils**
- Soil Rating Polygons**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
- Soil Rating Lines**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
- Soil Rating Points**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
- Water Features**
-  Streams and Canals
- Transportation**
-  Rails
-  Interstate Highways
-  US Routes
-  Major Roads
-  Local Roads
-  Background
-  Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background

Custom Soil Resource Report

MAP LEGEND

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Tables—Septic System In-Ground Bed (Conventional) (PA)

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI | | | | | |
|-----------------|--|--------------|--------------------------|---|----------------|---------------------------|--------------|----------------|--|-----|-------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | Very limited | Culleoka (85%) | Bedrock, above 60" (1.00) | 7.2 | 16.5% | | | | | |
| | | | | Too steep (0.88) | | | | | | | |
| | | | | Potential slow percolation >12" (0.01) | | | | | | | |
| | | | Dormont (10%) | Seasonal high water table (1.00) | | | | | | | |
| | | | | Slow percolation >12" (1.00) | | | | | | | |
| | | | | Slope (0.72) | | | | | | | |
| | | | Lowell (5%) | Potential karst (0.30) | | | | | | | |
| | | | | Slow percolation >12" (1.00) | | | | | | | |
| | | | | Bedrock, above 60" (1.00) | | | | | | | |
| | | | CaC | Culleoka channery silt loam, 8 to 15 percent slopes | | | Very limited | Culleoka (80%) | Bedrock, above 60" (1.00) | 8.2 | 18.6% |
| | | | | | | | | | Too steep (1.00) | | |
| | | | | | | | | | Potential slow percolation >12" (0.01) | | |
| Dormont (15%) | Seasonal high water table (1.00) | | | | | | | | | | |
| | Too steep (1.00) | | | | | | | | | | |
| | Slow percolation >12" (1.00) | | | | | | | | | | |
| Lowell (5%) | Potential karst (0.30) | | | | | | | | | | |
| | Too steep (1.00) | | | | | | | | | | |
| | Slow percolation >12" (1.00) | | | | | | | | | | |
| CaD | Culleoka channery silt | Very limited | | | Culleoka (80%) | Bedrock, above 60" (1.00) | | 0.4 | 0.9% | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres In AOI | Percent of AOI |
|-----------------|--|--------------|--------------------------|--|--------------|----------------|
| | loam, 15 to 25 percent slopes | | | Too steep (1.00) | | |
| | | | | Potential slow percolation >12" (0.01) | | |
| | | | Dormont (15%) | Seasonal high water table (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation >12" (1.00) | | |
| | | | | Potential karst (0.30) | | |
| | | | Lowell (5%) | Too steep (1.00) | | |
| | | | | Slow percolation >12" (1.00) | | |
| | | | | Bedrock, above 60" (1.00) | | |
| | | | | Potential karst (0.30) | | |
| DoB | Dormont silt loam, 3 to 8 percent slopes | Very limited | Dormont (75%) | Seasonal high water table (1.00) | 4.9 | 11.2% |
| | | | | Slow percolation >12" (1.00) | | |
| | | | | Slope (0.72) | | |
| | | | | Potential karst (0.30) | | |
| | | | Culleoka (10%) | Bedrock, above 60" (1.00) | | |
| | | | | Slope (0.72) | | |
| | | | | Potential slow percolation >12" (0.01) | | |
| | | | Lowell (10%) | Slow percolation >12" (1.00) | | |
| | | | | Bedrock, above 60" (1.00) | | |
| | | | | Slope (0.72) | | |
| | | | | Potential karst (0.30) | | |
| | | | Guemsey (5%) | Seasonal high water table (1.00) | | |
| | | | | Slow percolation >12" (1.00) | | |
| | | | | Bedrock, above 60" (1.00) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI | |
|------------------------------|--|--------------|--------------------------|----------------------------------|--------------|----------------|--|
| DoC | Dormont silt loam, 8 to 15 percent slopes | Very limited | | Slope (0.72) | 7.6 | 17.3% | |
| | | | | Potential karst (0.30) | | | |
| | | | Dormont (70%) | Seasonal high water table (1.00) | | | |
| | | | | Too steep (1.00) | | | |
| | | | | Slow percolation >12" (1.00) | | | |
| | | | | Potential karst (0.30) | | | |
| | | | | Culleoka (15%) | | | Bedrock, above 60" (1.00) |
| | | | | | | | Too steep (1.00) |
| | | | | | | | Potential slow percolation >12" (0.01) |
| | | | | Lowell (10%) | | | Too steep (1.00) |
| | | | | | | | Slow percolation >12" (1.00) |
| | | | | | | | Bedrock, above 60" (1.00) |
| | | | Potential karst (0.30) | | | | |
| | | | Guernsey (5%) | Seasonal high water table (1.00) | | | |
| Too steep (1.00) | | | | | | | |
| Slow percolation >12" (1.00) | | | | | | | |
| Bedrock, above 60" (1.00) | | | | | | | |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Very limited | Guernsey (85%) | Seasonal high water table (1.00) | 1.0 | 2.3% | |
| | | | | Too steep (1.00) | | | |
| | | | | Slow percolation >12" (1.00) | | | |
| | | | | Bedrock, above 60" (1.00) | | | |
| | | | | Potential karst (0.30) | | | |
| | | | | Berks (5%) | | | Bedrock, above 60" (1.00) |
| | | | | | | | Too steep (1.00) |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|--------------|--------------------------|---|--------------|----------------|
| | | | Westmoreland (5%) | Too steep (1.00) Bedrock, above 60" (1.00) Slow percolation >12" (0.89) | | |
| | | | Coshocton (5%) | Seasonal high water table (1.00) Too steep (1.00) Slow percolation >12" (1.00) Bedrock, above 60" (1.00) | | |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Very limited | Library (70%) | Seasonal high water table (1.00) Slow percolation >12" (1.00) Slope (0.50) Potential karst (0.30) | 2.9 | 6.6% |
| | | | Guernsey (15%) | Seasonal high water table (1.00) Slow percolation >12" (1.00) Bedrock, above 60" (1.00) Slope (0.72) Potential karst (0.30) | | |
| | | | Culleoka (10%) | Bedrock, above 60" (1.00) Too steep (0.88) Potential slow percolation >12" (0.01) | | |
| | | | Dormont (5%) | Seasonal high water table (1.00) Slow percolation >12" (1.00) Slope (0.50) Potential karst (0.30) | | |
| UdB | Udorthents, smoothed, gently sloping | Very limited | Udorthents (99%) | Bedrock, above 60" (1.00) | 0.9 | 2.0% |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|---|--------------|--------------------------|--|--------------|----------------|
| | | | | Slope (0.50) | | |
| | | | Wet spots (1%) | Miscellaneous area (1.00) | | |
| | | | | Seasonal high water table (1.00) | | |
| | | | | Slow percolation >12" (1.00) | | |
| | | | | Slope (0.13) | | |
| UdD | Udorthents, smoothed, moderately steep | Very limited | Udorthents (99%) | Too steep (1.00) | 1.6 | 3.6% |
| | | | | Bedrock, above 60" (1.00) | | |
| | | | Wet spots (1%) | Miscellaneous area (1.00) | | |
| | | | | Seasonal high water table (1.00) | | |
| | | | | Slow percolation >12" (1.00) | | |
| | | | | Slope (0.13) | | |
| WeB | Weikert-Culleoka complex, 3 to 8 percent slopes | Very limited | Weikert (60%) | Bedrock, above 60" (1.00) | 7.4 | 16.8% |
| | | | | Too steep (0.88) | | |
| | | | | Slight voided fragments (0.09) | | |
| | | | Culleoka (30%) | Bedrock, above 60" (1.00) | | |
| | | | | Too steep (0.88) | | |
| | | | | Potential slow percolation >12" (0.01) | | |
| | | | Dekalb (5%) | Bedrock, above 60" (1.00) | | |
| | | | | Fast percolation >12" (1.00) | | |
| | | | | Too steep (0.88) | | |
| | | | Brooke (3%) | Bedrock, above 60" (1.00) | | |
| | | | | Slow percolation >12" (1.00) | | |
| | | | | Too steep (0.88) | | |
| | | | Dormont (2%) | Seasonal high water table (1.00) | | |
| | | | | Slow percolation >12" (1.00) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|------------------------------------|--|--------------|--------------------------|--|--------------|----------------|
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | Very limited | | Slope (0.50) | 1.9 | 4.3% |
| | | | | Potential karst (0.30) | | |
| | | | Weikert (50%) | Bedrock, above 60" (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slight voided fragments (0.09) | | |
| | | | Culleoka (40%) | Bedrock, above 60" (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Potential slow percolation >12" (0.01) | | |
| | | | Brooke (5%) | Bedrock, above 80" (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation >12" (1.00) | | |
| | | | Dormont (5%) | Seasonal high water table (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation >12" (1.00) | | |
| | Potential karst (0.30) | | | | | |
| Totals for Area of Interest | | | | | 43.8 | 100.0% |
| Rating | | Acres in AOI | Percent of AOI | | | |
| Very limited | | 43.8 | 100.0% | | | |
| Totals for Area of Interest | | 43.8 | 100.0% | | | |

Rating Options—Septic System In-Ground Bed (Conventional) (PA)

Aggregation Method: Dominant Condition

Component Percent Cutoff: None Specified

Tie-break Rule: Higher

Septic System Subsurface Sand Filter Bed (Conventional) (PA)

This is a subsurface system of lines that distribute effluent from a septic tank into a sand filter above the natural soil. The distribution lines are at a minimum depth of 36 to 60 inches. The part of the soils between depths of 0 and 72 inches is considered when the soils are rated.

The soil properties and site features considered are those that affect absorption of the effluent and construction and maintenance of the system and those that may affect public health. These include depth to a water table, depth to bedrock, content of rock fragments, flooding, slope, and saturated hydraulic conductivity (Ksat). Flooding is a serious problem because it can result in improper treatment of the effluent and contamination of ground water or surface water. If Ksat is too fast or too slow, if the content of rock fragments is too high, or if the water table is too close to the surface, the effluent can contaminate the ground water. If this system is improperly installed on the steeper slopes, the effluent could flow along the surface of the soils. Additional grading may be needed in areas downslope from the system.

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. "Slightly limited" indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. "Moderately limited" indicates that the soil has features that are somewhat favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer are determined by the aggregation method chosen, which is displayed on the report. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is presented to help the user better understand the percentage of each map unit that has the rating presented.


Custom Soil Resource Report

Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the Selected Soil Interpretations report with this interpretation included from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.

Custom Soil Resource Report
 Map—Septic System Subsurface Sand Filter Bed (Conventional) (PA)
















Map Scale: 1:4,310 if printed on A portrait (8.5" x 11") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 17N WGS84

MAP LEGEND

-  Area of Interest (AOI)
-  Area of Interest (AOI)
- Soils**
- Soil Rating Polygons**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
-  Not rated or not available
- Soil Rating Lines**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
-  Not rated or not available
- Soil Rating Points**
-  Very limited
-  Moderately limited
-  Slightly limited
-  Not limited
-  Not rated or not available
-  Not rated or not available
- Water Features**
-  Streams and Canals
- Transportation**
-  Rails
-  Interstate Highways
-  US Routes
-  Major Roads
-  Local Roads
-  Background
-  Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background

Custom Soil Resource Report

MAP LEGEND

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Tables—Septic System Subsurface Sand Filter Bed
(Conventional) (PA)

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres In AOI | Percent of AOI |
|-----------------|--|--------------|--------------------------|--|--------------|----------------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | Very limited | Culleoka (85%) | Bedrock, above 72" (1.00) | 7.2 | 16.5% |
| | | | | Slow percolation 12-36"; see criteria (0.96) | | |
| | | | | Too steep (0.88) | | |
| | | | Dormont (10%) | Seasonal high water table (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Slope (0.72) | | |
| | | | Lowell (5%) | Potential karst (0.30) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | Very limited | Culleoka (80%) | Bedrock, above 72" (1.00) | 8.2 | 18.6% |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (0.96) | | |
| | | | Dormont (15%) | Seasonal high water table (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|--------------|--------------------------|---|--------------|----------------|
| | | | Lowell (5%) | Potential karst (0.30) Too steep (1.00) Slow percolation 12-36"; see criteria (1.00) Slow percolation 36-60" (1.00) Bedrock, above 72" (1.00) Potential karst (0.30) | | |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | Very limited | Culleoka (80%) | Bedrock, above 72" (1.00) Too steep (1.00) Slow percolation 12-36"; see criteria (0.96) | 0.4 | 0.9% |
| | | | Dormont (15%) | Seasonal high water table (1.00) Too steep (1.00) Slow percolation 12-36"; see criteria (1.00) Slow percolation 36-60" (1.00) Potential karst (0.30) | | |
| | | | Lowell (5%) | Too steep (1.00) Slow percolation 12-36"; see criteria (1.00) Slow percolation 36-60" (1.00) Bedrock, above 72" (1.00) Potential karst (0.30) | | |
| DoB | Dormont silt loam, 3 to 8 percent slopes | Very limited | Dormont (75%) | Seasonal high water table (1.00) Slow percolation 12-36"; see criteria (1.00) Slow percolation 36-60" (1.00) Slope (0.72) | 4.9 | 11.2% |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|---|--------------|--------------------------|--|--------------|----------------|
| | | | | Potential karst (0.30) | | |
| | | | Culleoka (10%) | Bedrock, above 72" (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (0.96) | | |
| | | | | Slope (0.72) | | |
| | | | Lowell (10%) | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Bedrock, above 72" (1.00) | | |
| | | | | Slope (0.72) | | |
| | | | | Potential karst (0.30) | | |
| | | | Guernsey (5%) | Seasonal high water table (1.00) | | |
| | | | | Bedrock, above 72" (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Slope (0.72) | | |
| DoC | Dormont silt loam, 8 to 15 percent slopes | Very limited | Dormont (70%) | Seasonal high water table (1.00) | 7.6 | 17.3% |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Potential karst (0.30) | | |
| | | | Culleoka (15%) | Bedrock, above 72" (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (0.96) | | |
| | | | Lowell (10%) | Too steep (1.00) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres In AOI | Percent of AOI |
|-----------------|--|--------------|--------------------------|--|--------------|----------------|
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Bedrock, above 72" (1.00) | | |
| | | | | Potential karst (0.30) | | |
| | | | Guernsey (5%) | Seasonal high water table (1.00) | | |
| | | | | Bedrock, above 72" (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Very limited | Guernsey (85%) | Seasonal high water table (1.00) | 1.0 | 2.3% |
| | | | | Bedrock, above 72" (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | Berks (5%) | Bedrock, above 72" (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-38"; see criteria (0.96) | | |
| | | | Westmoreland (5%) | Bedrock, above 72" (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-38"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (0.97) | | |
| | | | Coshocton (5%) | Seasonal high water table (1.00) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|--------------|--------------------------|--|--------------|----------------|
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Bedrock, above 72" (1.00) | | |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Very limited | Library (70%) | Seasonal high water table (1.00) | 2.9 | 6.5% |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Slope (0.50) | | |
| | | | | Potential karst (0.30) | | |
| | | | Guernsey (15%) | Seasonal high water table (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Bedrock, above 72" (1.00) | | |
| | | | | Slope (0.72) | | |
| | | | Culleoka (10%) | Bedrock, above 72" (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (0.86) | | |
| | | | | Too steep (0.88) | | |
| | | | Dormont (5%) | Seasonal high water table (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Slope (0.50) | | |
| | | | | Potential karst (0.30) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|---|--------------|--------------------------|--|--------------|----------------|
| UdB | Udortheints, smoothed, gently sloping | Very limited | Udortheints (99%) | Bedrock, above 72" (1.00) | 0.9 | 2.0% |
| | | | | Slow percolation 12-36"; see criteria (0.53) | | |
| | | | | Slope (0.50) | | |
| | | | Wet spots (1%) | Seasonal high water table (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Miscellaneous area (1.00) | | |
| Slope (0.13) | | | | | | |
| UdD | Udortheints, smoothed, moderately steep | Very limited | Udortheints (99%) | Bedrock, above 72" (1.00) | 1.6 | 3.6% |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (0.53) | | |
| | | | Wet spots (1%) | Seasonal high water table (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Miscellaneous area (1.00) | | |
| Slope (0.13) | | | | | | |
| WeB | Weikert-Culleoka complex, 3 to 8 percent slopes | Very limited | Weikert (60%) | Bedrock, above 72" (1.00) | 7.4 | 16.8% |
| | | | | Slow percolation 12-36"; see criteria (0.94) | | |
| | | | | Too steep (0.88) | | |
| | | | Culleoka (30%) | Slight voided fragments (0.09) | | |
| | | | | Bedrock, above 72" (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (0.96) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|--------------|--------------------------|--|--------------|----------------|
| | | | | Too steep (0.88) | | |
| | | | Dekalb (5%) | Bedrock, above 72" (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (0.94) | | |
| | | | | Too steep (0.88) | | |
| | | | Brooke (3%) | Bedrock, above 72" (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Too steep (0.88) | | |
| | | | Dormont (2%) | Seasonal high water table (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Slope (0.50) | | |
| | | | | Potential karst (0.30) | | |
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | Very limited | Weikert (50%) | Bedrock, above 72" (1.00) | 1.9 | 4.3% |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (0.84) | | |
| | | | | Slight voided fragments (0.09) | | |
| | | | Culleoka (40%) | Bedrock, above 72" (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (0.96) | | |
| | | | Brooke (5%) | Bedrock, above 72" (1.00) | | |
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | Dormont (5%) | Seasonal high water table (1.00) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|------------------------------------|---------------|--------|--------------------------|--|--------------|----------------|
| | | | | Too steep (1.00) | | |
| | | | | Slow percolation 12-36"; see criteria (1.00) | | |
| | | | | Slow percolation 36-60" (1.00) | | |
| | | | | Potential karst (0.30) | | |
| Totals for Area of Interest | | | | | 43.8 | 100.0% |

| Rating | Acres in AOI | Percent of AOI |
|------------------------------------|--------------|----------------|
| Very limited | 43.8 | 100.0% |
| Totals for Area of Interest | 43.8 | 100.0% |

Rating Options—Septic System Subsurface Sand Filter Bed (Conventional) (PA)

Aggregation Method: Dominant Condition

Aggregation is the process by which a set of component attribute values is reduced to a single value that represents the map unit as a whole.

A map unit is typically composed of one or more "components". A component is either some type of soil or some nonsoil entity, e.g., rock outcrop. For the attribute being aggregated, the first step of the aggregation process is to derive one attribute value for each of a map unit's components. From this set of component attributes, the next step of the aggregation process derives a single value that represents the map unit as a whole. Once a single value for each map unit is derived, a thematic map for soil map units can be rendered. Aggregation must be done because, on any soil map, map units are delineated but components are not.

For each of a map unit's components, a corresponding percent composition is recorded. A percent composition of 60 indicates that the corresponding component typically makes up approximately 60% of the map unit. Percent composition is a critical factor in some, but not all, aggregation methods.

The aggregation method "Dominant Condition" first groups like attribute values for the components in a map unit. For each group, percent composition is set to the sum of the percent composition of all components participating in that group. These groups now represent "conditions" rather than components. The attribute value associated with the group with the highest cumulative percent composition is returned. If more than one group shares the highest cumulative percent composition, the corresponding "tie-break" rule determines which value should be returned. The "tie-break" rule indicates whether the lower or higher group value should be returned in the case of a percent composition tie. The result returned by this aggregation method represents the dominant condition throughout the map unit only when no tie has occurred.

Custom Soil Resource Report

Component Percent Cutoff: None Specified

Components whose percent composition is below the cutoff value will not be considered. If no cutoff value is specified, all components in the database will be considered. The data for some contrasting soils of minor extent may not be in the database, and therefore are not considered.

Tie-break Rule: Higher

The tie-break rule indicates which value should be selected from a set of multiple candidate values, or which value should be selected in the event of a percent composition tie.

Septic Tank Absorption Fields

Septic tank absorption fields are areas in which effluent from a septic tank is distributed into the soil through subsurface tiles or perforated pipe. Only that part of the soil between depths of 24 and 60 inches is evaluated. The ratings are based on the soil properties that affect absorption of the effluent, construction and maintenance of the system, and public health. Saturated hydraulic conductivity (Ksat), depth to a water table, ponding, depth to bedrock or a cemented pan, and flooding affect absorption of the effluent. Stones and boulders, ice, and bedrock or a cemented pan interfere with installation. Subsidence interferes with installation and maintenance. Excessive slope may cause lateral seepage and surfacing of the effluent in downslope areas.

Some soils are underlain by loose sand and gravel or fractured bedrock at a depth of less than 4 feet below the distribution lines. In these soils the absorption field may not adequately filter the effluent, particularly when the system is new. As a result, the ground water may become contaminated.

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. "Somewhat limited" indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).


The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer are determined by the aggregation method chosen. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those

Custom Soil Resource Report


that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is presented to help the user better understand the percentage of each map unit that has the rating presented.

Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the equivalent report from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.






















Custom Soil Resource Report
Map—Septic Tank Absorption Fields



Soil Map may not be valid at this scale.



MAP LEGEND

- Area of Interest (AOI)
 - Area of Interest (AOI) 
 - Background 
 - Aerial Photography 
- Soils
 - Soil Rating Polygons
 - Very limited 
 - Somewhat limited 
 - Not limited 
 - Not rated or not available 
 - Soil Rating Lines
 - Very limited 
 - Somewhat limited 
 - Not limited 
 - Not rated or not available 
 - Soil Rating Points
 - Very limited 
 - Somewhat limited 
 - Not limited 
 - Not rated or not available 
- Water Features
 - Streams and Canals 
- Transportation
 - Rails 
 - Interstate Highways 
 - US Routes 
 - Major Roads 
 - Local Roads 

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background

MAP LEGEND

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Tables—Septic Tank Absorption Fields

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|--|--------------|--------------------------|---------------------------------|--------------|----------------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | Very limited | Culleoka (85%) | Depth to bedrock (1.00) | 7.2 | 16.5% |
| | | | | Seepage, bottom layer (1.00) | | |
| | | | Dormont (10%) | Depth to saturated zone (1.00) | | |
| | | | | Slow water movement (1.00) | | |
| | | | Lowell (5%) | Slow water movement (1.00) | | |
| | | | | Depth to bedrock (0.28) | | |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | Very limited | Culleoka (80%) | Depth to bedrock (1.00) | 8.2 | 18.6% |
| | | | | Seepage, bottom layer (1.00) | | |
| | | | | Slope (0.63) | | |
| | | | Dormont (15%) | Depth to saturated zone (1.00) | | |
| | | | | Slow water movement (1.00) | | |
| | | | | Slope (0.63) | | |
| Lowell (5%) | Slow water movement (1.00) | | | | | |
| | Slope (0.63) | | | | | |
| | Depth to bedrock (0.28) | | | | | |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | Very limited | Culleoka (80%) | Depth to bedrock (1.00) | 0.4 | 0.9% |
| | | | | Slope (1.00) | | |
| | | | | Seepage, bottom layer (1.00) | | |
| | | | Dormont (15%) | Depth to saturated zone (1.00) | | |
| | | | | Slope (1.00) | | |
| | | | | Slow water movement (1.00) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|---|--------------|--------------------------|---|--------------|----------------|
| | | | Lowell (5%) | Slope (1.00) Slow water movement (1.00) Depth to bedrock (0.28) | | |
| DoB | Dormont silt loam, 3 to 8 percent slopes | Very limited | Dormont (75%) | Depth to saturated zone (1.00) Slow water movement (1.00) | 4.9 | 11.2% |
| | | | Culleoka (10%) | Depth to bedrock (1.00) Seepage, bottom layer (1.00) | | |
| | | | Lowell (10%) | Slow water movement (1.00) Depth to bedrock (0.28) | | |
| | | | Guernsey (5%) | Depth to saturated zone (1.00) Slow water movement (1.00) Depth to bedrock (0.25) | | |
| DoC | Dormont silt loam, 8 to 15 percent slopes | Very limited | Dormont (70%) | Depth to saturated zone (1.00) Slow water movement (1.00) Slope (0.63) | 7.6 | 17.3% |
| | | | Culleoka (15%) | Depth to bedrock (1.00) Seepage, bottom layer (1.00) Slope (0.63) | | |
| | | | Lowell (10%) | Slow water movement (1.00) Slope (0.63) Depth to bedrock (0.28) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres In AOI | Percent of AOI |
|-----------------|--|--------------------------------|--------------------------|---------------------------------|--------------|----------------|
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Very limited | Guernsey (5%) | Depth to saturated zone (1.00) | 1.0 | 2.3% |
| | | | | Slow water movement (1.00) | | |
| | | | | Slope (0.63) | | |
| | | | | Depth to bedrock (0.25) | | |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Very limited | Guernsey (85%) | Depth to saturated zone (1.00) | 2.9 | 6.5% |
| | | | | Slow water movement (1.00) | | |
| | | | | Slope (0.63) | | |
| | | | | Depth to bedrock (0.25) | | |
| | | | Berks (5%) | Depth to bedrock (1.00) | | |
| | | | | Seepage, bottom layer (1.00) | | |
| | | | | Slope (0.63) | | |
| | | | | Large stones (0.09) | | |
| | | | Coshocton (5%) | Depth to saturated zone (1.00) | | |
| | | | | Slow water movement (1.00) | | |
| | Slope (0.63) | | | | | |
| | Depth to bedrock (0.34) | | | | | |
| | Library (70%) | Depth to saturated zone (1.00) | 2.9 | 6.5% | | |
| | Slow water movement (1.00) | | | | | |
| Guernsey (15%) | Depth to saturated zone (1.00) | | | | | |
| | Slow water movement (1.00) | | | | | |
| | | Depth to bedrock (0.45) | | | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|---|--------------|--------------------------|--|--------------|----------------|
| | | | Culleoka (10%) | Depth to bedrock (1.00) Seepage, bottom layer (1.00) | | |
| | | | Dormont (5%) | Depth to saturated zone (1.00) Slow water movement (1.00) | | |
| UdB | Udortheints, smoothed, gently sloping | Very limited | Udortheints (99%) | Filtering capacity (1.00) Seepage, bottom layer (1.00) Depth to bedrock (0.25) | 0.9 | 2.0% |
| | | | Wet spots (1%) | Depth to saturated zone (1.00) Slow water movement (1.00) | | |
| UdD | Udortheints, smoothed, moderately steep | Very limited | Udortheints (99%) | Filtering capacity (1.00) Slope (1.00) Seepage, bottom layer (1.00) Depth to bedrock (0.25) | 1.6 | 3.6% |
| | | | Wet spots (1%) | Depth to saturated zone (1.00) Slow water movement (1.00) | | |
| WeB | Welkert-Culleoka complex, 3 to 8 percent slopes | Very limited | Welkert (60%) | Depth to bedrock (1.00) Seepage, bottom layer (1.00) | 7.4 | 16.8% |
| | | | Culleoka (30%) | Depth to bedrock (1.00) Seepage, bottom layer (1.00) | | |
| | | | Dekalb (5%) | Depth to bedrock (1.00) Seepage, bottom layer (1.00) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|------------------------------------|--|--------------|--------------------------|---------------------------------|--------------|----------------|
| | | | Brooke (3%) | Slow water movement (1.00) | | |
| | | | | Depth to bedrock (1.00) | | |
| | | | Dormont (2%) | Depth to saturated zone (1.00) | | |
| | | | | Slow water movement (1.00) | | |
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | Very limited | Weikert (50%) | Depth to bedrock (1.00) | 1.9 | 4.3% |
| | | | | Seepage, bottom layer (1.00) | | |
| | | | | Slope (0.63) | | |
| | | | Culleoka (40%) | Depth to bedrock (1.00) | | |
| | | | | Seepage, bottom layer (1.00) | | |
| | | | | Slope (0.63) | | |
| | | | Brooke (5%) | Slow water movement (1.00) | | |
| | | | | Depth to bedrock (1.00) | | |
| | | | | Slope (0.63) | | |
| | | | Dormont (5%) | Depth to saturated zone (1.00) | | |
| | | | | Slow water movement (1.00) | | |
| | | | | Slope (0.63) | | |
| Totals for Area of Interest | | | | | 43.8 | 100.0% |

| Rating | Acres in AOI | Percent of AOI |
|------------------------------------|--------------|----------------|
| Very limited | 43.8 | 100.0% |
| Totals for Area of Interest | 43.8 | 100.0% |

Rating Options—Septic Tank Absorption Fields

Aggregation Method: Dominant Condition

Aggregation is the process by which a set of component attribute values is reduced to a single value that represents the map unit as a whole.

Custom Soil Resource Report

A map unit is typically composed of one or more "components". A component is either some type of soil or some nonsoil entity, e.g., rock outcrop. For the attribute being aggregated, the first step of the aggregation process is to derive one attribute value for each of a map unit's components. From this set of component attributes, the next step of the aggregation process derives a single value that represents the map unit as a whole. Once a single value for each map unit is derived, a thematic map for soil map units can be rendered. Aggregation must be done because, on any soil map, map units are delineated but components are not.

For each of a map unit's components, a corresponding percent composition is recorded. A percent composition of 60 indicates that the corresponding component typically makes up approximately 60% of the map unit. Percent composition is a critical factor in some, but not all, aggregation methods.

The aggregation method "Dominant Condition" first groups like attribute values for the components in a map unit. For each group, percent composition is set to the sum of the percent composition of all components participating in that group. These groups now represent "conditions" rather than components. The attribute value associated with the group with the highest cumulative percent composition is returned. If more than one group shares the highest cumulative percent composition, the corresponding "tie-break" rule determines which value should be returned. The "tie-break" rule indicates whether the lower or higher group value should be returned in the case of a percent composition tie. The result returned by this aggregation method represents the dominant condition throughout the map unit only when no tie has occurred.

Component Percent Cutoff: None Specified

Components whose percent composition is below the cutoff value will not be considered. If no cutoff value is specified, all components in the database will be considered. The data for some contrasting soils of minor extent may not be in the database, and therefore are not considered.

Tie-break Rule: Higher

The tie-break rule indicates which value should be selected from a set of multiple candidate values, or which value should be selected in the event of a percent composition tie.

Septic System CO-OP RFS III With Spray Irrigation (PA)

This system is currently listed as an alternate system in the Pennsylvania regulations. It distributes effluent from a septic tank into a free-access recirculating filter, through a manufacturer-required disinfection unit, and then through spray heads that disperse the effluent onto the surface of the soil. Only the part of the soils between depths of 0 and 16 inches is considered when the soils are rated.

The soil properties and site features considered are those that affect absorption of the effluent and construction and maintenance of the system and those that may affect public health. These include depth to a water table, depth to bedrock, content of rock fragments, flooding, slope, and saturated hydraulic conductivity (Ksat). Flooding is a serious problem because it can result in improper treatment of the effluent and contamination of ground water or surface water. If Ksat is too fast or too slow, if the content of rock fragments is too high, or if the water table is too close to

Custom Soil Resource Report

the surface, the effluent can contaminate the ground water. If this system is improperly installed on the steeper slopes, the effluent could flow along the surface of the soils. Additional grading may be needed in areas downslope from the system.

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. "Slightly limited" indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. "Moderately limited" indicates that the soil has features that are somewhat favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer are determined by the aggregation method chosen, which is displayed on the report. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is presented to help the user better understand the percentage of each map unit that has the rating presented.


Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the Selected Soil Interpretations report with this interpretation included from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.

Custom Soil Resource Report
Map—Septic System CO-OP RFS III With Spray Irrigation (PA)



Soil Map may not be valid at this scale.

Map Scale: 1:4,310 if printed on A portrait (8.5" x 11") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 17N WGS84

MAP LEGEND

- Area of Interest (AOI)**
 - Area of Interest (AOI)
- Soils**
 - Very limited
 - Moderately limited
 - Slightly limited
 - Not limited
 - Not rated or not available
- Soil Rating Polygons**
 - Very limited
 - Moderately limited
 - Slightly limited
 - Not limited
 - Not rated or not available
- Soil Rating Lines**
 - Very limited
 - Moderately limited
 - Slightly limited
 - Not limited
 - Not rated or not available
- Soil Rating Points**
 - Very limited
 - Moderately limited
 - Slightly limited
 - Not limited
 - Not rated or not available
- Water Features**
 - Streams and Canals
- Transportation**
 - Rails
 - Interstate Highways
- US Routes**
- Major Roads**
- Local Roads**
- Background**
 - Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background

Custom Soil Resource Report

MAP LEGEND

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Tables—Septic System CO-OP RFS III With Spray Irrigation (PA)

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI | |
|-----------------|--|--------------------|--------------------------|---|--------------|----------------|---|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | Slightly limited | Culleoka (85%) | Slope 0-12%; see land cover criteria (0.50) Potential bedrock near 16" (0.22) | 7.2 | 16.5% | |
| | | | Dormont (10%) | Slope 0-12%; see land cover criteria (0.50) Potential karst (0.30) Low potential seasonal high water table (0.02) | | | |
| | | | Lowell (5%) | Slope 0-12%; see land cover criteria (0.50) Potential karst (0.30) | | | |
| | | | | | | | |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | Slightly limited | Culleoka (80%) | Slope 0-12%; see land cover criteria (0.50) Potential bedrock near 16" (0.22) | 8.2 | 18.6% | |
| | | | Dormont (15%) | Slope 0-12%; see land cover criteria (0.50) Potential karst (0.30) Low potential seasonal high water table (0.02) | | | |
| | | | | Lowell (5%) | | | Slope 0-12%; see land cover criteria (0.50) Potential karst (0.30) |
| | | | | | | | |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | Moderately limited | Culleoka (80%) | Slope 0-25%; see land cover criteria (0.75) Potential bedrock near 16" (0.22) | 0.4 | 0.9% | |
| | | | Dormont (15%) | Slope 0-25%; see land cover criteria (0.75) | | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|---|------------------|--------------------------|--|--------------|----------------|
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Lowell (5%) | Slope 0-25%; see land cover criteria (0.75) | | |
| | | | | Potential karst (0.30) | | |
| DoB | Dormont silt loam, 3 to 8 percent slopes | Slightly limited | Dormont (75%) | Slope 0-12%; see land cover criteria (0.50) | 4.9 | 11.2% |
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Culleoka (10%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Lowell (10%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Potential karst (0.30) | | |
| | | | Guernsey (5%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Low potential seasonal high water table (0.42) | | |
| | | | | Potential karst (0.30) | | |
| DoC | Dormont silt loam, 8 to 15 percent slopes | Slightly limited | Dormont (70%) | Slope 0-12%; see land cover criteria (0.50) | 7.6 | 17.3% |
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Culleoka (15%) | Slope 0-12%; see land cover criteria (0.50) | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|---|--------------------|--------------------------|--|--------------|----------------|
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Lowell (10%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Potential karst (0.30) | | |
| | | | Guernsey (5%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Low potential seasonal high water table (0.42) | | |
| | | | | Potential karst (0.30) | | |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Slightly limited | Guernsey (85%) | Slope 0-12%; see land cover criteria (0.50) | 1.0 | 2.3% |
| | | | | Low potential seasonal high water table (0.42) | | |
| | | | | Potential karst (0.30) | | |
| | | | Berks (5%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Potential bedrock near 16" (0.28) | | |
| | | | Westmoreland (5%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Potential bedrock near 16" (0.01) | | |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Moderately limited | Library (70%) | Seasonal high water table (0.92) | 2.9 | 6.5% |
| | | | | Potential karst (0.30) | | |
| UdB | Udorthents, smoothed, gently sloping | Not limited | Udorthents (99%) | | 0.9 | 2.0% |
| UdD | Udorthents, smoothed, moderately steep | Moderately limited | Udorthents (99%) | Slope 0-25%; see land cover criteria (0.75) | 1.6 | 3.8% |
| WeB | Weikert-Culleoka complex, 3 to 8 percent slopes | Moderately limited | Weikert (60%) | Potential bedrock near 16" (0.70) | 7.4 | 16.8% |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------------------|--|--------------------|--------------------------|---|--------------|----------------|
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | Moderately limited | Weikert (50%) | Slope 0-12%; see land cover criteria (0.50) | 1.9 | 4.3% |
| | | | | Slight voided fragments (0.09) | | |
| | | | | Potential bedrock near 16" (0.70) | | |
| | | | | Slope 0-12%; see land cover criteria (0.50) | | |
| Totals for Area of Interest | | | | | 43.8 | 100.0% |

| Rating | Acres in AOI | Percent of AOI |
|-----------------------------|--------------|----------------|
| Slightly limited | 28.9 | 65.9% |
| Moderately limited | 14.1 | 32.1% |
| Not limited | 0.9 | 2.0% |
| Totals for Area of Interest | 43.8 | 100.0% |

Rating Options—Septic System CO-OP RFS III With Spray Irrigation (PA)

Aggregation Method: Dominant Condition

Aggregation is the process by which a set of component attribute values is reduced to a single value that represents the map unit as a whole.

A map unit is typically composed of one or more "components". A component is either some type of soil or some nonsoil entity, e.g., rock outcrop. For the attribute being aggregated, the first step of the aggregation process is to derive one attribute value for each of a map unit's components. From this set of component attributes, the next step of the aggregation process derives a single value that represents the map unit as a whole. Once a single value for each map unit is derived, a thematic map for soil map units can be rendered. Aggregation must be done because, on any soil map, map units are delineated but components are not.

For each of a map unit's components, a corresponding percent composition is recorded. A percent composition of 60 indicates that the corresponding component typically makes up approximately 60% of the map unit. Percent composition is a critical factor in some, but not all, aggregation methods.

The aggregation method "Dominant Condition" first groups like attribute values for the components in a map unit. For each group, percent composition is set to the sum of the percent composition of all components participating in that group. These

Custom Soil Resource Report

groups now represent "conditions" rather than components. The attribute value associated with the group with the highest cumulative percent composition is returned. If more than one group shares the highest cumulative percent composition, the corresponding "tie-break" rule determines which value should be returned. The "tie-break" rule indicates whether the lower or higher group value should be returned in the case of a percent composition tie. The result returned by this aggregation method represents the dominant condition throughout the map unit only when no tie has occurred.

Component Percent Cutoff: None Specified

Components whose percent composition is below the cutoff value will not be considered. If no cutoff value is specified, all components in the database will be considered. The data for some contrasting soils of minor extent may not be in the database, and therefore are not considered.

Tie-break Rule: Higher

The tie-break rule indicates which value should be selected from a set of multiple candidate values, or which value should be selected in the event of a percent composition tie.

Septic System Spray Irrigation (PA)

This is a system of pressurized lines that distribute effluent from a septic tank into a sand filter tank and chlorination system and then through spray heads that disperse the effluent onto the surface of the soil. Only the part of the soils between depths of 0 and 16 inches is considered when the soils are rated.

The soil properties and site features considered are those that affect absorption of the effluent and construction and maintenance of the system and those that may affect public health. These include depth to a water table, depth to bedrock, content of rock fragments, flooding, slope, and saturated hydraulic conductivity (Ksat). Flooding is a serious problem because it can result in improper treatment of the effluent and contamination of ground water or surface water. If Ksat is too fast or too slow, if the content of rock fragments is too high, or if the water table is too close to the surface, the effluent can contaminate the ground water. If this system is improperly installed on the steeper slopes, the effluent could flow along the surface of the soils. Additional grading may be needed in areas downslope from the system.

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. "Slightly limited" indicates that the soil has features that are favorable for the specified use. The limitations are minor and can be easily overcome. Good performance and low maintenance can be expected. "Moderately limited" indicates that the soil has features that are somewhat favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Custom Soil Resource Report

Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

These ratings do not preclude the need for onsite investigation to determine the limitations affecting system placement.


The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer are determined by the aggregation method chosen, which is displayed on the report. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is presented to help the user better understand the percentage of each map unit that has the rating presented.

Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the Selected Soil Interpretations report with this interpretation included from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.

Custom Soil Resource Report
 Map—Septic System Spray Irrigation (PA)



Map Scale: 1:4,310 if printed on A portrait (8.5" x 11") sheet.



Map projection: Web Mercator Corner coordinates: WGS84 Edge ties: UTM Zone 17N WGS84

MAP LEGEND

- Area of Interest (AOI)
 - Area of Interest (AOI)
- Soils
 - Soil Rating Polygons
 - Very limited
 - Moderately limited
 - Slightly limited
 - Not limited
 - Not rated or not available
 - Soil Rating Lines
 - Very limited
 - Moderately limited
 - Slightly limited
 - Not limited
 - Not rated or not available
 - Soil Rating Points
 - Very limited
 - Moderately limited
 - Slightly limited
 - Not limited
 - Not rated or not available
- Water Features
 - Streams and Canals
- Transportation
 - Rails
 - Interstate Highways
- US Routes
- Major Roads
- Local Roads
- Background
 - Aerial Photography

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service
 Web Soil Survey URL:
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Greene and Washington Counties, Pennsylvania
 Survey Area Data: Version 16, Sep 19, 2018

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Mar 27, 2011—Mar 23, 2017

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background

Custom Soil Resource Report

MAP LEGEND

MAP INFORMATION

imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Custom Soil Resource Report

Tables—Septic System Spray Irrigation (PA)

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|------------------------|--|--------------------|--------------------------|--|--------------|----------------|
| CaB | Culleoka channery silt loam, 3 to 8 percent slopes | Slightly limited | Culleoka (85%) | Slope 0-12%; see land cover criteria (0.50) | 7.2 | 16.5% |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Dormont (10%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Lowell (5%) | Slope 0-12%; see land cover criteria (0.50) | | |
| Potential karst (0.30) | | | | | | |
| CaC | Culleoka channery silt loam, 8 to 15 percent slopes | Slightly limited | Culleoka (80%) | Slope 0-12%; see land cover criteria (0.50) | 8.2 | 18.6% |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Dormont (15%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Potential karst (0.30) | | |
| | | | | Low potential seasonal high water table (0.02) | | |
| | | | Lowell (5%) | Slope 0-12%; see land cover criteria (0.50) | | |
| Potential karst (0.30) | | | | | | |
| CaD | Culleoka channery silt loam, 15 to 25 percent slopes | Moderately limited | Culleoka (80%) | Slope 0-25%; see land cover criteria (0.75) | 0.4 | 0.9% |
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Dormont (15%) | Slope 0-25%; see land cover criteria (0.75) | | |
| | | | | | | |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI | |
|-----------------|---|------------------|--------------------------|--|--------------|----------------|---|
| DoB | Dormont silt loam, 3 to 8 percent slopes | Slightly limited | | Potential karst (0.30) | 4.9 | 11.2% | |
| | | | | Low potential seasonal high water table (0.02) | | | |
| | | | Lowell (5%) | Slope 0-25%; see land cover criteria (0.75) | | | |
| | | | | Potential karst (0.30) | | | |
| | | | Dormont (75%) | Slope 0-12%; see land cover criteria (0.50) | | | |
| | | | | Potential karst (0.30) | | | |
| | | | | Low potential seasonal high water table (0.02) | | | |
| | | | Culleoka (10%) | Slope 0-12%; see land cover criteria (0.50) | | | |
| | | | | Potential bedrock near 16" (0.22) | | | |
| | | | | Lowell (10%) | | | Slope 0-12%; see land cover criteria (0.50) |
| DoC | Dormont silt loam, 8 to 15 percent slopes | Slightly limited | | Potential karst (0.30) | 7.6 | 17.3% | |
| | | | | Low potential seasonal high water table (0.02) | | | |
| | | | Guernsey (5%) | Slope 0-12%; see land cover criteria (0.50) | | | |
| | | | | Low potential seasonal high water table (0.42) | | | |
| | | | Dormont (70%) | Slope 0-12%; see land cover criteria (0.50) | | | |
| | | | | Potential karst (0.30) | | | |
| | | | | Low potential seasonal high water table (0.02) | | | |
| | | | | Culleoka (15%) | | | Slope 0-12%; see land cover criteria (0.50) |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|-----------------|---|--------------------|--------------------------|--|--------------|----------------|
| | | | | Potential bedrock near 16" (0.22) | | |
| | | | Lowell (10%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Potential karst (0.30) | | |
| | | | Guernsey (5%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Low potential seasonal high water table (0.42) | | |
| | | | | Potential karst (0.30) | | |
| GeC | Guernsey silt loam, 8 to 15 percent slopes | Slightly limited | Guernsey (85%) | Slope 0-12%; see land cover criteria (0.50) | 1.0 | 2.3% |
| | | | | Low potential seasonal high water table (0.42) | | |
| | | | | Potential karst (0.30) | | |
| | | | Berks (5%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Potential bedrock near 16" (0.28) | | |
| | | | Westmoreland (5%) | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Potential bedrock near 16" (0.01) | | |
| LbB | Library silty clay loam, 3 to 8 percent slopes | Moderately limited | Library (70%) | Seasonal high water table (0.92) | 2.9 | 6.5% |
| | | | | Potential karst (0.30) | | |
| UdB | Udorthents, smoothed, gently sloping | Not limited | Udorthents (99%) | | 0.9 | 2.0% |
| UdD | Udorthents, smoothed, moderately steep | Moderately limited | Udorthents (99%) | Slope 0-25%; see land cover criteria (0.75) | 1.6 | 3.6% |
| WeB | Weikert-Culleoka complex, 3 to 8 percent slopes | Moderately limited | Weikert (60%) | Potential bedrock near 16" (0.70) | 7.4 | 16.8% |

Custom Soil Resource Report

| Map unit symbol | Map unit name | Rating | Component name (percent) | Rating reasons (numeric values) | Acres in AOI | Percent of AOI |
|------------------------------------|--|--------------------|--------------------------|---|--------------|----------------|
| | | | | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Slight voided fragments (0.09) | | |
| WeC | Weikert-Culleoka complex, 8 to 15 percent slopes | Moderately limited | Weikert (50%) | Potential bedrock near 16" (0.70) | 1.9 | 4.3% |
| | | | | Slope 0-12%; see land cover criteria (0.50) | | |
| | | | | Slight voided fragments (0.09) | | |
| Totals for Area of Interest | | | | | 43.8 | 100.0% |

| Rating | Acres in AOI | Percent of AOI |
|------------------------------------|--------------|----------------|
| Slightly limited | 28.9 | 65.9% |
| Moderately limited | 14.1 | 32.1% |
| Not limited | 0.9 | 2.0% |
| Totals for Area of Interest | 43.8 | 100.0% |

Rating Options—Septic System Spray Irrigation (PA)

Aggregation Method: Dominant Condition

Aggregation is the process by which a set of component attribute values is reduced to a single value that represents the map unit as a whole.

A map unit is typically composed of one or more "components". A component is either some type of soil or some nonsoil entity, e.g., rock outcrop. For the attribute being aggregated, the first step of the aggregation process is to derive one attribute value for each of a map unit's components. From this set of component attributes, the next step of the aggregation process derives a single value that represents the map unit as a whole. Once a single value for each map unit is derived, a thematic map for soil map units can be rendered. Aggregation must be done because, on any soil map, map units are delineated but components are not.

For each of a map unit's components, a corresponding percent composition is recorded. A percent composition of 60 indicates that the corresponding component typically makes up approximately 60% of the map unit. Percent composition is a critical factor in some, but not all, aggregation methods.

The aggregation method "Dominant Condition" first groups like attribute values for the components in a map unit. For each group, percent composition is set to the sum of the percent composition of all components participating in that group. These groups now represent "conditions" rather than components. The attribute value

Custom Soil Resource Report

associated with the group with the highest cumulative percent composition is returned. If more than one group shares the highest cumulative percent composition, the corresponding "tie-break" rule determines which value should be returned. The "tie-break" rule indicates whether the lower or higher group value should be returned in the case of a percent composition tie. The result returned by this aggregation method represents the dominant condition throughout the map unit only when no tie has occurred.

Component Percent Cutoff: None Specified

Components whose percent composition is below the cutoff value will not be considered. If no cutoff value is specified, all components in the database will be considered. The data for some contrasting soils of minor extent may not be in the database, and therefore are not considered.

Tie-break Rule: Higher

The tie-break rule indicates which value should be selected from a set of multiple candidate values, or which value should be selected in the event of a percent composition tie.

Soil Reports

The Soil Reports section includes various formatted tabular and narrative reports (tables) containing data for each selected soil map unit and each component of each unit. No aggregation of data has occurred as is done in reports in the Soil Properties and Qualities and Suitabilities and Limitations sections.

The reports contain soil interpretive information as well as basic soil properties and qualities. A description of each report (table) is included.

Sanitary Facilities

This folder contains a collection of tabular reports that present soil interpretations related to sanitary facilities. The reports (tables) include all selected map units and components for each map unit, limiting features and interpretive ratings. Sanitary facilities interpretations are tools designed to guide the user in site selection for the safe disposal of sewage and solid waste. Example interpretations include septic tank absorption fields, sewage lagoons, and sanitary landfills.

Sewage Disposal

This table shows the degree and kind of soil limitations that affect septic tank absorption fields and sewage lagoons. The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect these uses. *Not limited* indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. *Somewhat limited* indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. *Very limited* indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings in the table indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

Septic tank absorption fields are areas in which effluent from a septic tank is distributed into the soil through subsurface tiles or perforated pipe. Only that part of the soil between depths of 24 and 72 inches or between a depth of 24 inches and a restrictive layer is evaluated. The ratings are based on the soil properties that affect absorption of the effluent, construction and maintenance of the system, and public health. Saturated hydraulic conductivity (Ksat), depth to a water table, ponding, depth to bedrock or a cemented pan, and flooding affect absorption of the effluent. Stones and boulders, ice, and bedrock or a cemented pan interfere with installation.

Custom Soil Resource Report

Subsidence interferes with installation and maintenance. Excessive slope may cause lateral seepage and surfacing of the effluent in downslope areas.

Some soils are underlain by loose sand and gravel or fractured bedrock at a depth of less than 4 feet below the distribution lines. In these soils the absorption field may not adequately filter the effluent, particularly when the system is new. As a result, the ground water may become contaminated.

Sewage lagoons are shallow ponds constructed to hold sewage while aerobic bacteria decompose the solid and liquid wastes. Lagoons should have a nearly level floor surrounded by cut slopes or embankments of compacted soil. Nearly impervious soil material for the lagoon floor and sides is required to minimize seepage and contamination of ground water. Considered in the ratings are slope, saturated hydraulic conductivity (Ksat), depth to a water table, ponding, depth to bedrock or a cemented pan, flooding, large stones, and content of organic matter.

Saturated hydraulic conductivity (Ksat) is a critical property affecting the suitability for sewage lagoons. Most porous soils eventually become sealed when they are used as sites for sewage lagoons. Until sealing occurs, however, the hazard of pollution is severe. Soils that have a Ksat rate of more than 14 micrometers per second are too porous for the proper functioning of sewage lagoons. In these soils, seepage of the effluent can result in contamination of the ground water. Ground-water contamination is also a hazard if fractured bedrock is within a depth of 40 inches, if the water table is high enough to raise the level of sewage in the lagoon, or if floodwater overtops the lagoon.

A high content of organic matter is detrimental to proper functioning of the lagoon because it inhibits aerobic activity. Slope, bedrock, and cemented pans can cause construction problems, and large stones can hinder compaction of the lagoon floor. If the lagoon is to be uniformly deep throughout, the slope must be gentle enough and the soil material must be thick enough over bedrock or a cemented pan to make land smoothing practical.

Information in this table is intended for land use planning, for evaluating land use alternatives, and for planning site investigations prior to design and construction. The information, however, has limitations. For example, estimates and other data generally apply only to that part of the soil between the surface and a depth of 5 to 7 feet. Because of the map scale, small areas of different soils may be included within the mapped areas of a specific soil.

The information is not site specific and does not eliminate the need for onsite investigation of the soils or for testing and analysis by personnel experienced in the design and construction of engineering works.

Government ordinances and regulations that restrict certain land uses or impose specific design criteria were not considered in preparing the information in this table. Local ordinances and regulations should be considered in planning, in site selection, and in design.

Report—Sewage Disposal

[Onsite investigation may be needed to validate the interpretations in this table and to confirm the identity of the soil on a given site. The numbers in the value columns range from 0.01 to 1.00. The larger the value, the greater the potential limitation. The table shows only the top five limitations for any given soil. The soil may have additional limitations]

Custom Soil Resource Report

| Sewage Disposal—Greene and Washington Counties, Pennsylvania | | | | | |
|--|------------------|------------------------------------|-------|------------------------------------|-------|
| Map symbol and soil name | Pct. of map unit | Septic tank absorption fields | | Sewage lagoons | |
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| CaB—Culleoka channery silt loam, 3 to 8 percent slopes | 85 | Very limited | | Very limited | |
| Culleoka | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Seepage, bottom layer | 1.00 | Seepage | 1.00 |
| | | | | Slope | 0.92 |
| Dormont | 10 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Depth to saturated zone | 1.00 |
| | | Slow water movement | 1.00 | Slope | 0.68 |
| Lowell | 5 | Very limited | | Somewhat limited | |
| | | Slow water movement | 1.00 | Slope | 0.92 |
| | | Depth to bedrock | 0.28 | | |
| CaC—Culleoka channery silt loam, 8 to 15 percent slopes | 80 | Very limited | | Very limited | |
| Culleoka | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Seepage, bottom layer | 1.00 | Slope | 1.00 |
| | | Slope | 0.63 | Seepage | 1.00 |
| Dormont | 15 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Slope | 1.00 |
| | | Slow water movement | 1.00 | Depth to saturated zone | 1.00 |
| | | Slope | 0.63 | | |
| Lowell | 5 | Very limited | | Very limited | |
| | | Slow water movement | 1.00 | Slope | 1.00 |
| | | Slope | 0.63 | | |
| | | Depth to bedrock | 0.28 | | |

Custom Soil Resource Report

| Sewage Disposal—Greene and Washington Counties, Pennsylvania | | | | | |
|--|------------------|------------------------------------|-------|------------------------------------|-------|
| Map symbol and soil name | Pct. of map unit | Septic tank absorption fields | | Sewage lagoons | |
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| CaD—Culleoka channery silt loam, 15 to 25 percent slopes | | | | | |
| Culleoka | 80 | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Slope | 1.00 | Slope | 1.00 |
| | | Seepage, bottom layer | 1.00 | Seepage | 1.00 |
| Dormont | 15 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Slope | 1.00 |
| | | Slope | 1.00 | Depth to saturated zone | 1.00 |
| | | Slow water movement | 1.00 | | |
| Lowell | 5 | Very limited | | Very limited | |
| | | Slope | 1.00 | Slope | 1.00 |
| | | Slow water movement | 1.00 | | |
| | | Depth to bedrock | 0.28 | | |
| DoB—Dormont silt loam, 3 to 8 percent slopes | | | | | |
| Dormont | 75 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Depth to saturated zone | 1.00 |
| | | Slow water movement | 1.00 | Slope | 0.68 |
| Culleoka | 10 | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Seepage, bottom layer | 1.00 | Seepage | 1.00 |
| | | | | Slope | 0.68 |
| Lowell | 10 | Very limited | | Somewhat limited | |
| | | Slow water movement | 1.00 | Slope | 0.68 |
| | | Depth to bedrock | 0.28 | | |
| Guernsey | 6 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Depth to saturated zone | 1.00 |
| | | Slow water movement | 1.00 | Slope | 0.68 |
| | | Depth to bedrock | 0.25 | Seepage | 0.50 |

Custom Soil Resource Report

| Sewage Disposal—Greene and Washington Counties, Pennsylvania | | | | | |
|--|------------------|------------------------------------|-------|------------------------------------|-------|
| Map symbol and soil name | Pct. of map unit | Septic tank absorption fields | | Sewage lagoons | |
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| DoC—Dormont silt loam, 8 to 15 percent slopes | | | | | |
| Dormont | 70 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Slope | 1.00 |
| | | Slow water movement | 1.00 | Depth to saturated zone | 1.00 |
| | | Slope | 0.63 | | |
| Culleoka | 15 | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Seepage, bottom layer | 1.00 | Slope | 1.00 |
| | | Slope | 0.63 | Seepage | 1.00 |
| Lowell | 10 | Very limited | | Very limited | |
| | | Slow water movement | 1.00 | Slope | 1.00 |
| | | Slope | 0.63 | | |
| | | Depth to bedrock | 0.28 | | |
| Guemsey | 5 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Slope | 1.00 |
| | | Slow water movement | 1.00 | Depth to saturated zone | 1.00 |
| | | Slope | 0.63 | Seepage | 0.50 |
| | | Depth to bedrock | 0.25 | | |

Custom Soil Resource Report

| Sewage Disposal—Greene and Washington Counties, Pennsylvania | | | | | |
|--|------------------|------------------------------------|-------|------------------------------------|-------|
| Map symbol and soil name | Pct. of map unit | Septic tank absorption fields | | Sewage lagoons | |
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| GeC—Guernsey silt loam, 8 to 15 percent slopes | | | | | |
| Guernsey | 85 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Slope | 1.00 |
| | | Slow water movement | 1.00 | Depth to saturated zone | 1.00 |
| | | Slope | 0.63 | Seepage | 0.50 |
| | | Depth to bedrock | 0.25 | | |
| Berks | 5 | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Seepage bottom layer | 1.00 | Slope | 1.00 |
| | | Slope | 0.63 | Seepage | 1.00 |
| | | Large stones | 0.09 | Large stones | 0.40 |
| Coshocton | 5 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Slope | 1.00 |
| | | Slow water movement | 1.00 | Depth to saturated zone | 1.00 |
| | | Slope | 0.63 | Depth to hard bedrock | 0.01 |
| | | Depth to bedrock | 0.34 | | |
| Westmoreland | 5 | Somewhat limited | | Very limited | |
| | | Depth to bedrock | 0.98 | Organic matter content | 1.00 |
| | | Slope | 0.63 | Slope | 1.00 |
| | | Slow water movement | 0.47 | Depth to soft bedrock | 0.88 |
| | | | | Seepage | 0.63 |
| | | | | Depth to hard bedrock | 0.42 |

Custom Soil Resource Report

| Sewage Disposal—Greene and Washington Counties, Pennsylvania | | | | | |
|--|------------------|------------------------------------|-------|------------------------------------|-------|
| Map symbol and soil name | Pct. of map unit | Septic tank absorption fields | | Sewage lagoons | |
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| LbB—Library silty clay loam, 3 to 8 percent slopes | | | | | |
| Library | 70 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Depth to saturated zone | 1.00 |
| | | Slow water movement | 1.00 | Slope | 0.32 |
| Guernsey | 15 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Depth to saturated zone | 1.00 |
| | | Slow water movement | 1.00 | Slope | 0.68 |
| | | Depth to bedrock | 0.45 | Seepage | 0.28 |
| | | | | Depth to hard bedrock | 0.05 |
| Culleoka | 10 | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Seepage, bottom layer | 1.00 | Seepage | 1.00 |
| | | | | Slope | 0.92 |
| Dormont | 5 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Depth to saturated zone | 1.00 |
| | | Slow water movement | 1.00 | Slope | 0.32 |
| | | | | Seepage | 0.21 |
| UdB—Udorthents, smoothed, gently sloping | | | | | |
| Udorthents | 99 | Very limited | | Very limited | |
| | | Filtering capacity | 1.00 | Seepage | 1.00 |
| | | Seepage, bottom layer | 1.00 | Slope | 0.32 |
| | | Depth to bedrock | 0.25 | | |
| Wet spots | 1 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Depth to saturated zone | 1.00 |
| | | Slow water movement | 1.00 | Seepage | 0.28 |
| UdD—Udorthents, smoothed, moderately steep | | | | | |
| Udorthents | 99 | Very limited | | Very limited | |
| | | Filtering capacity | 1.00 | Slope | 1.00 |
| | | Slope | 1.00 | Seepage | 1.00 |
| | | Seepage, bottom layer | 1.00 | | |
| | | Depth to bedrock | 0.25 | | |
| Wet spots | 1 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Depth to saturated zone | 1.00 |
| | | Slow water movement | 1.00 | Seepage | 0.28 |

Custom Soil Resource Report

| Sewage Disposal—Greene and Washington Counties, Pennsylvania | | | | | |
|--|------------------|------------------------------------|-------|------------------------------------|-------|
| Map symbol and soil name | Pct. of map unit | Septic tank absorption fields | | Sewage lagoons | |
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| WeB—Weikert-Culleoka complex, 3 to 8 percent slopes | | | | | |
| Weikert | 60 | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Seepage, bottom layer | 1.00 | Seepage | 1.00 |
| | | | | Slope | 0.92 |
| Culleoka | 30 | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Seepage, bottom layer | 1.00 | Seepage | 1.00 |
| | | | | Slope | 0.92 |
| Dekalb | 5 | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Seepage, bottom layer | 1.00 | Seepage | 1.00 |
| | | | | Slope | 0.92 |
| Brooke | 3 | Very limited | | Very limited | |
| | | Slow water movement | 1.00 | Depth to hard bedrock | 1.00 |
| | | Depth to bedrock | 1.00 | Slope | 0.92 |
| Dormont | 2 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Depth to saturated zone | 1.00 |
| | | Slow water movement | 1.00 | Slope | 0.32 |
| | | | | Seepage | 0.21 |

Custom Soil Resource Report

| Sewage Disposal—Greene and Washington Counties, Pennsylvania | | | | | |
|--|------------------|------------------------------------|-------|------------------------------------|-------|
| Map symbol and soil name | Pct. of map unit | Septic tank absorption fields | | Sewage lagoons | |
| | | Rating class and limiting features | Value | Rating class and limiting features | Value |
| WeC—Weikert-Culleoka complex, 8 to 15 percent slopes | | | | | |
| Weikert | 50 | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Seepage, bottom layer | 1.00 | Slope | 1.00 |
| | | Slope | 0.63 | Seepage | 1.00 |
| Culleoka | 40 | Very limited | | Very limited | |
| | | Depth to bedrock | 1.00 | Depth to hard bedrock | 1.00 |
| | | Seepage, bottom layer | 1.00 | Slope | 1.00 |
| | | Slope | 0.63 | Seepage | 1.00 |
| Brooke | 5 | Very limited | | Very limited | |
| | | Slow water movement | 1.00 | Depth to hard bedrock | 1.00 |
| | | Depth to bedrock | 1.00 | Slope | 1.00 |
| | | Slope | 0.63 | | |
| Dormont | 5 | Very limited | | Very limited | |
| | | Depth to saturated zone | 1.00 | Slope | 1.00 |
| | | Slow water movement | 1.00 | Depth to saturated zone | 1.00 |
| | | Slope | 0.63 | Seepage | 0.21 |

References

- American Association of State Highway and Transportation Officials (AASHTO). 2004. Standard specifications for transportation materials and methods of sampling and testing. 24th edition.
- American Society for Testing and Materials (ASTM). 2005. Standard classification of soils for engineering purposes. ASTM Standard D2487-00.
- Cowardin, L.M., V. Carter, F.C. Golet, and E.T. LaRoe. 1979. Classification of wetlands and deep-water habitats of the United States. U.S. Fish and Wildlife Service FWS/OBS-79/31.
- Federal Register. July 13, 1994. Changes in hydric soils of the United States.
- Federal Register. September 18, 2002. Hydric soils of the United States.
- Hurt, G.W., and L.M. Vasilas, editors. Version 6.0, 2006. Field indicators of hydric soils in the United States.
- National Research Council. 1995. Wetlands: Characteristics and boundaries.
- Soil Survey Division Staff. 1993. Soil survey manual. Soil Conservation Service. U.S. Department of Agriculture Handbook 18. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_054262
- Soil Survey Staff. 1999. Soil taxonomy: A basic system of soil classification for making and interpreting soil surveys. 2nd edition. Natural Resources Conservation Service, U.S. Department of Agriculture Handbook 436. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053577
- Soil Survey Staff. 2010. Keys to soil taxonomy. 11th edition. U.S. Department of Agriculture, Natural Resources Conservation Service. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053580
- Tiner, R.W., Jr. 1985. Wetlands of Delaware. U.S. Fish and Wildlife Service and Delaware Department of Natural Resources and Environmental Control, Wetlands Section.
- United States Army Corps of Engineers, Environmental Laboratory. 1987. Corps of Engineers wetlands delineation manual. Waterways Experiment Station Technical Report Y-87-1.
- United States Department of Agriculture, Natural Resources Conservation Service. National forestry manual. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/home/?cid=nrcs142p2_053374
- United States Department of Agriculture, Natural Resources Conservation Service. National range and pasture handbook. <http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/landuse/rangepasture/?cid=stelprdb1043084>

Custom Soil Resource Report

United States Department of Agriculture, Natural Resources Conservation Service. National soil survey handbook, title 430-VI. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/scientists/?cid=nrcs142p2_054242

United States Department of Agriculture, Natural Resources Conservation Service. 2006. Land resource regions and major land resource areas of the United States, the Caribbean, and the Pacific Basin. U.S. Department of Agriculture Handbook 296. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053624

United States Department of Agriculture, Soil Conservation Service. 1961. Land capability classification. U.S. Department of Agriculture Handbook 210. http://www.nrcs.usda.gov/Internet/FSE_DOCUMENTS/nrcs142p2_052290.pdf

Glossary

Many of the terms relating to landforms, geology, and geomorphology are defined in more detail in the following National Soil Survey Handbook link: "National Soil Survey Handbook."

ABC soil

A soil having an A, a B, and a C horizon.

Ablation till

Loose, relatively permeable earthy material deposited during the downwasting of nearly static glacial ice, either contained within or accumulated on the surface of the glacier.

AC soil

A soil having only an A and a C horizon. Commonly, such soil formed in recent alluvium or on steep, rocky slopes.

Aeration, soil

The exchange of air in soil with air from the atmosphere. The air in a well aerated soil is similar to that in the atmosphere; the air in a poorly aerated soil is considerably higher in carbon dioxide and lower in oxygen.

Aggregate, soil

Many fine particles held in a single mass or cluster. Natural soil aggregates, such as granules, blocks, or prisms, are called peds. Clods are aggregates produced by tillage or logging.

Alkali (sodic) soil

A soil having so high a degree of alkalinity (pH 8.5 or higher) or so high a percentage of exchangeable sodium (15 percent or more of the total exchangeable bases), or both, that plant growth is restricted.

Alluvial cone

A semiconical type of alluvial fan having very steep slopes. It is higher, narrower, and steeper than a fan and is composed of coarser and thicker layers of material deposited by a combination of alluvial episodes and (to a much lesser degree) landslides (debris flow). The coarsest materials tend to be concentrated at the apex of the cone.

Custom Soil Resource Report

Alluvial fan

A low, outspread mass of loose materials and/or rock material, commonly with gentle slopes. It is shaped like an open fan or a segment of a cone. The material was deposited by a stream at the place where it issues from a narrow mountain valley or upland valley or where a tributary stream is near or at its junction with the main stream. The fan is steepest near its apex, which points upstream, and slopes gently and convexly outward (downstream) with a gradual decrease in gradient.

Alluvium

Unconsolidated material, such as gravel, sand, silt, clay, and various mixtures of these, deposited on land by running water.

Alpha,alpha-dipyridyl

A compound that when dissolved in ammonium acetate is used to detect the presence of reduced iron (Fe II) in the soil. A positive reaction implies reducing conditions and the likely presence of redoximorphic features.

Animal unit month (AUM)

The amount of forage required by one mature cow of approximately 1,000 pounds weight, with or without a calf, for 1 month.

Aquic conditions

Current soil wetness characterized by saturation, reduction, and redoximorphic features.

Argillic horizon

A subsoil horizon characterized by an accumulation of illuvial clay.

Arroyo

The flat-floored channel of an ephemeral stream, commonly with very steep to vertical banks cut in unconsolidated material. It is usually dry but can be transformed into a temporary watercourse or short-lived torrent after heavy rain within the watershed.

Aspect

The direction toward which a slope faces. Also called slope aspect.

Association, soil

A group of soils or miscellaneous areas geographically associated in a characteristic repeating pattern and defined and delineated as a single map unit.

Available water capacity (available moisture capacity)

The capacity of soils to hold water available for use by most plants. It is commonly defined as the difference between the amount of soil water at field moisture capacity and the amount at wilting point. It is commonly expressed as inches of water per inch of soil. The capacity, in inches, in a 60-inch profile or to a limiting layer is expressed as:

Custom Soil Resource Report

Very low: 0 to 3

Low: 3 to 6

Moderate: 6 to 9

High: 9 to 12

Very high: More than 12

Backslope

The position that forms the steepest and generally linear, middle portion of a hillslope. In profile, backslopes are commonly bounded by a convex shoulder above and a concave footslope below.

Backswamp

A flood-plain landform. Extensive, marshy or swampy, depressed areas of flood plains between natural levees and valley sides or terraces.

Badland

A landscape that is intricately dissected and characterized by a very fine drainage network with high drainage densities and short, steep slopes and narrow interfluves. Badlands develop on surfaces that have little or no vegetative cover overlying unconsolidated or poorly cemented materials (clays, silts, or sandstones) with, in some cases, soluble minerals, such as gypsum or halite.

Bajada

A broad, gently inclined alluvial piedmont slope extending from the base of a mountain range out into a basin and formed by the lateral coalescence of a series of alluvial fans. Typically, it has a broadly undulating transverse profile, parallel to the mountain front, resulting from the convexities of component fans. The term is generally restricted to constructional slopes of intermontane basins.

Basal area

The area of a cross section of a tree, generally referring to the section at breast height and measured outside the bark. It is a measure of stand density, commonly expressed in square feet.

Base saturation

The degree to which material having cation-exchange properties is saturated with exchangeable bases (sum of Ca, Mg, Na, and K), expressed as a percentage of the total cation-exchange capacity.

Base slope (geomorphology)

A geomorphic component of hills consisting of the concave to linear (perpendicular to the contour) slope that, regardless of the lateral shape, forms an apron or wedge at the bottom of a hillside dominated by colluvium and slope-wash sediments (for example, slope alluvium).

Bedding plane

A planar or nearly planar bedding surface that visibly separates each successive layer of stratified sediment or rock (of the same or different lithology)

Custom Soil Resource Report

from the preceding or following layer; a plane of deposition. It commonly marks a change in the circumstances of deposition and may show a parting, a color difference, a change in particle size, or various combinations of these. The term is commonly applied to any bedding surface, even one that is conspicuously bent or deformed by folding.

Bedding system

A drainage system made by plowing, grading, or otherwise shaping the surface of a flat field. It consists of a series of low ridges separated by shallow, parallel dead furrows.

Bedrock

The solid rock that underlies the soil and other unconsolidated material or that is exposed at the surface.

Bedrock-controlled topography

A landscape where the configuration and relief of the landforms are determined or strongly influenced by the underlying bedrock.

Bench terrace

A raised, level or nearly level strip of earth constructed on or nearly on a contour, supported by a barrier of rocks or similar material, and designed to make the soil suitable for tillage and to prevent accelerated erosion.

Bisequum

Two sequences of soil horizons, each of which consists of an illuvial horizon and the overlying eluvial horizons.

Blowout (map symbol)

A saucer-, cup-, or trough-shaped depression formed by wind erosion on a preexisting dune or other sand deposit, especially in an area of shifting sand or loose soil or where protective vegetation is disturbed or destroyed. The adjoining accumulation of sand derived from the depression, where recognizable, is commonly included. Blowouts are commonly small.

Borrow pit (map symbol)

An open excavation from which soil and underlying material have been removed, usually for construction purposes.

Bottom land

An informal term loosely applied to various portions of a flood plain.

Boulders

Rock fragments larger than 2 feet (60 centimeters) in diameter.

Breaks

A landscape or tract of steep, rough or broken land dissected by ravines and gullies and marking a sudden change in topography.

Custom Soil Resource Report

Breast height

An average height of 4.5 feet above the ground surface; the point on a tree where diameter measurements are ordinarily taken.

Brush management

Use of mechanical, chemical, or biological methods to make conditions favorable for reseeding or to reduce or eliminate competition from woody vegetation and thus allow understory grasses and forbs to recover. Brush management increases forage production and thus reduces the hazard of erosion. It can improve the habitat for some species of wildlife.

Butte

An isolated, generally flat-topped hill or mountain with relatively steep slopes and talus or precipitous cliffs and characterized by summit width that is less than the height of bounding escarpments; commonly topped by a caprock of resistant material and representing an erosion remnant carved from flat-lying rocks.

Cable yarding

A method of moving felled trees to a nearby central area for transport to a processing facility. Most cable yarding systems involve use of a drum, a pole, and wire cables in an arrangement similar to that of a rod and reel used for fishing. To reduce friction and soil disturbance, felled trees generally are reeled in while one end is lifted or the entire log is suspended.

Calcareous soil

A soil containing enough calcium carbonate (commonly combined with magnesium carbonate) to effervesce visibly when treated with cold, dilute hydrochloric acid.

Caliche

A general term for a prominent zone of secondary carbonate accumulation in surficial materials in warm, subhumid to arid areas. Caliche is formed by both geologic and pedologic processes. Finely crystalline calcium carbonate forms a nearly continuous surface-coating and void-filling medium in geologic (parent) materials. Cementation ranges from weak in nonindurated forms to very strong in indurated forms. Other minerals (e.g., carbonates, silicate, and sulfate) may occur as accessory cements. Most petrocalcic horizons and some calcic horizons are caliche.

California bearing ratio (CBR)

The load-supporting capacity of a soil as compared to that of standard crushed limestone, expressed as a ratio. First standardized in California. A soil having a CBR of 16 supports 16 percent of the load that would be supported by standard crushed limestone, per unit area, with the same degree of distortion.

Canopy

The leafy crown of trees or shrubs. (See Crown.)

Custom Soil Resource Report

Canyon

A long, deep, narrow valley with high, precipitous walls in an area of high local relief.

Capillary water

Water held as a film around soil particles and in tiny spaces between particles. Surface tension is the adhesive force that holds capillary water in the soil.

Catena

A sequence, or "chain," of soils on a landscape that formed in similar kinds of parent material and under similar climatic conditions but that have different characteristics as a result of differences in relief and drainage.

Cation

An ion carrying a positive charge of electricity. The common soil cations are calcium, potassium, magnesium, sodium, and hydrogen.

Cation-exchange capacity

The total amount of exchangeable cations that can be held by the soil, expressed in terms of milliequivalents per 100 grams of soil at neutrality (pH 7.0) or at some other stated pH value. The term, as applied to soils, is synonymous with base-exchange capacity but is more precise in meaning.

Catsteps

See Terracettes.

Cement rock

Shaly limestone used in the manufacture of cement.

Channery soil material

Soil material that has, by volume, 15 to 35 percent thin, flat fragments of sandstone, shale, slate, limestone, or schist as much as 6 inches (15 centimeters) along the longest axis. A single piece is called a channer.

Chemical treatment

Control of unwanted vegetation through the use of chemicals.

Chiseling

Tillage with an implement having one or more soil-penetrating points that shatter or loosen hard, compacted layers to a depth below normal plow depth.

Cirque

A steep-walled, semicircular or crescent-shaped, half-bowl-like recess or hollow, commonly situated at the head of a glaciated mountain valley or high on the side of a mountain. It was produced by the erosive activity of a mountain glacier. It commonly contains a small round lake (tarn).

Custom Soil Resource Report

Clay

As a soil separate, the mineral soil particles less than 0.002 millimeter in diameter. As a soil textural class, soil material that is 40 percent or more clay, less than 45 percent sand, and less than 40 percent silt.

Clay depletions

See Redoximorphic features.

Clay film

A thin coating of oriented clay on the surface of a soil aggregate or lining pores or root channels. Synonyms: clay coating, clay skin.

Clay spot (map symbol)

A spot where the surface texture is silty clay or clay in areas where the surface layer of the soils in the surrounding map unit is sandy loam, loam, silt loam, or coarser.

Claypan

A dense, compact subsoil layer that contains much more clay than the overlying materials, from which it is separated by a sharply defined boundary. The layer restricts the downward movement of water through the soil. A claypan is commonly hard when dry and plastic and sticky when wet.

Climax plant community

The stabilized plant community on a particular site. The plant cover reproduces itself and does not change so long as the environment remains the same.

Coarse textured soil

Sand or loamy sand.

Cobble (or cobblestone)

A rounded or partly rounded fragment of rock 3 to 10 inches (7.6 to 25 centimeters) in diameter.

Cobbly soil material

Material that has 15 to 35 percent, by volume, rounded or partially rounded rock fragments 3 to 10 inches (7.6 to 25 centimeters) in diameter. Very cobbly soil material has 35 to 60 percent of these rock fragments, and extremely cobbly soil material has more than 60 percent.

COLE (coefficient of linear extensibility)

See Linear extensibility.

Colluvium

Unconsolidated, unsorted earth material being transported or deposited on side slopes and/or at the base of slopes by mass movement (e.g., direct gravitational action) and by local, unconcentrated runoff.

Custom Soil Resource Report

Complex slope

Irregular or variable slope. Planning or establishing terraces, diversions, and other water-control structures on a complex slope is difficult.

Complex, soil

A map unit of two or more kinds of soil or miscellaneous areas in such an intricate pattern or so small in area that it is not practical to map them separately at the selected scale of mapping. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas.

Concretions

See Redoximorphic features.

Conglomerate

A coarse grained, clastic sedimentary rock composed of rounded or subangular rock fragments more than 2 millimeters in diameter. It commonly has a matrix of sand and finer textured material. Conglomerate is the consolidated equivalent of gravel.

Conservation cropping system

Growing crops in combination with needed cultural and management practices. In a good conservation cropping system, the soil-improving crops and practices more than offset the effects of the soil-depleting crops and practices. Cropping systems are needed on all tilled soils. Soil-improving practices in a conservation cropping system include the use of rotations that contain grasses and legumes and the return of crop residue to the soil. Other practices include the use of green manure crops of grasses and legumes, proper tillage, adequate fertilization, and weed and pest control.

Conservation tillage

A tillage system that does not invert the soil and that leaves a protective amount of crop residue on the surface throughout the year.

Consistence, soil

Refers to the degree of cohesion and adhesion of soil material and its resistance to deformation when ruptured. Consistence includes resistance of soil material to rupture and to penetration; plasticity, toughness, and stickiness of puddled soil material; and the manner in which the soil material behaves when subject to compression. Terms describing consistence are defined in the "Soil Survey Manual."

Contour stripcropping

Growing crops in strips that follow the contour. Strips of grass or close-growing crops are alternated with strips of clean-tilled crops or summer fallow.

Control section

The part of the soil on which classification is based. The thickness varies among different kinds of soil, but for many it is that part of the soil profile between depths of 10 inches and 40 or 80 inches.

Custom Soil Resource Report

Coprogenous earth (sedimentary peat)

A type of limnic layer composed predominantly of fecal material derived from aquatic animals.

Corrosion (geomorphology)

A process of erosion whereby rocks and soil are removed or worn away by natural chemical processes, especially by the solvent action of running water, but also by other reactions, such as hydrolysis, hydration, carbonation, and oxidation.

Corrosion (soil survey interpretations)

Soil-induced electrochemical or chemical action that dissolves or weakens concrete or uncoated steel.

Cover crop

A close-growing crop grown primarily to improve and protect the soil between periods of regular crop production, or a crop grown between trees and vines in orchards and vineyards.

Crop residue management

Returning crop residue to the soil, which helps to maintain soil structure, organic matter content, and fertility and helps to control erosion.

Cropping system

Growing crops according to a planned system of rotation and management practices.

Cross-slope farming

Deliberately conducting farming operations on sloping farmland in such a way that tillage is across the general slope.

Crown

The upper part of a tree or shrub, including the living branches and their foliage.

Cryoturbate

A mass of soil or other unconsolidated earthy material moved or disturbed by frost action. It is typically coarser than the underlying material.

Cuesta

An asymmetric ridge capped by resistant rock layers of slight or moderate dip (commonly less than 15 percent slopes); a type of homocline produced by differential erosion of interbedded resistant and weak rocks. A cuesta has a long, gentle slope on one side (dip slope) that roughly parallels the inclined beds; on the other side, it has a relatively short and steep or clifflike slope (scarp) that cuts through the tilted rocks.

Custom Soil Resource Report

Culmination of the mean annual increment (CMAI)

The average annual increase per acre in the volume of a stand. Computed by dividing the total volume of the stand by its age. As the stand increases in age, the mean annual increment continues to increase until mortality begins to reduce the rate of increase. The point where the stand reaches its maximum annual rate of growth is called the culmination of the mean annual increment.

Cutbanks cave

The walls of excavations tend to cave in or slough.

Decreasers

The most heavily grazed climax range plants. Because they are the most palatable, they are the first to be destroyed by overgrazing.

Deferred grazing

Postponing grazing or resting grazing land for a prescribed period.

Delta

A body of alluvium having a surface that is fan shaped and nearly flat; deposited at or near the mouth of a river or stream where it enters a body of relatively quiet water, generally a sea or lake.

Dense layer

A very firm, massive layer that has a bulk density of more than 1.8 grams per cubic centimeter. Such a layer affects the ease of digging and can affect filling and compacting.

Depression, closed (map symbol)

A shallow, saucer-shaped area that is slightly lower on the landscape than the surrounding area and that does not have a natural outlet for surface drainage.

Depth, soil

Generally, the thickness of the soil over bedrock. Very deep soils are more than 60 inches deep over bedrock; deep soils, 40 to 60 inches; moderately deep, 20 to 40 inches; shallow, 10 to 20 inches; and very shallow, less than 10 inches.

Desert pavement

A natural, residual concentration or layer of wind-polished, closely packed gravel, boulders, and other rock fragments mantling a desert surface. It forms where wind action and sheetwash have removed all smaller particles or where rock fragments have migrated upward through sediments to the surface. It typically protects the finer grained underlying material from further erosion.

Diatomaceous earth

A geologic deposit of fine, grayish siliceous material composed chiefly or entirely of the remains of diatoms.

Custom Soil Resource Report

Dip slope

A slope of the land surface, roughly determined by and approximately conforming to the dip of the underlying bedrock.

Diversion (or diversion terrace)

A ridge of earth, generally a terrace, built to protect downslope areas by diverting runoff from its natural course.

Divided-slope farming

A form of field stripcropping in which crops are grown in a systematic arrangement of two strips, or bands, across the slope to reduce the hazard of water erosion. One strip is in a close-growing crop that provides protection from erosion, and the other strip is in a crop that provides less protection from erosion. This practice is used where slopes are not long enough to permit a full stripcropping pattern to be used.

Drainage class (natural)

Refers to the frequency and duration of wet periods under conditions similar to those under which the soil formed. Alterations of the water regime by human activities, either through drainage or irrigation, are not a consideration unless they have significantly changed the morphology of the soil. Seven classes of natural soil drainage are recognized—*excessively drained*, *somewhat excessively drained*, *well drained*, *moderately well drained*, *somewhat poorly drained*, *poorly drained*, and *very poorly drained*. These classes are defined in the "Soil Survey Manual."

Drainage, surface

Runoff, or surface flow of water, from an area.

Drainageway

A general term for a course or channel along which water moves in draining an area. A term restricted to relatively small, linear depressions that at some time move concentrated water and either do not have a defined channel or have only a small defined channel.

Draw

A small stream valley that generally is shallower and more open than a ravine or gulch and that has a broader bottom. The present stream channel may appear inadequate to have cut the drainageway that it occupies.

Drift

A general term applied to all mineral material (clay, silt, sand, gravel, and boulders) transported by a glacier and deposited directly by or from the ice or transported by running water emanating from a glacier. Drift includes unstratified material (till) that forms moraines and stratified deposits that form outwash plains, eskers, kames, varves, and glaciofluvial sediments. The term is generally applied to Pleistocene glacial deposits in areas that no longer contain glaciers.

Custom Soil Resource Report

Drumlin

A low, smooth, elongated oval hill, mound, or ridge of compact till that has a core of bedrock or drift. It commonly has a blunt nose facing the direction from which the ice approached and a gentler slope tapering in the other direction. The longer axis is parallel to the general direction of glacier flow. Drumlins are products of streamline (laminar) flow of glaciers, which molded the subglacial floor through a combination of erosion and deposition.

Duff

A generally firm organic layer on the surface of mineral soils. It consists of fallen plant material that is in the process of decomposition and includes everything from the litter on the surface to underlying pure humus.

Dune

A low mound, ridge, bank, or hill of loose, windblown granular material (generally sand), either barren and capable of movement from place to place or covered and stabilized with vegetation but retaining its characteristic shape.

Earthy fill

See Mine spoil.

Ecological site

An area where climate, soil, and relief are sufficiently uniform to produce a distinct natural plant community. An ecological site is the product of all the environmental factors responsible for its development. It is typified by an association of species that differ from those on other ecological sites in kind and/or proportion of species or in total production.

Eluviation

The movement of material in true solution or colloidal suspension from one place to another within the soil. Soil horizons that have lost material through eluviation are eluvial; those that have received material are illuvial.

Endosaturation

A type of saturation of the soil in which all horizons between the upper boundary of saturation and a depth of 2 meters are saturated.

Eolian deposit

Sand-, silt-, or clay-sized clastic material transported and deposited primarily by wind, commonly in the form of a dune or a sheet of sand or loess.

Ephemeral stream

A stream, or reach of a stream, that flows only in direct response to precipitation. It receives no long-continued supply from melting snow or other source, and its channel is above the water table at all times.

Custom Soil Resource Report

Episaturation

A type of saturation indicating a perched water table in a soil in which saturated layers are underlain by one or more unsaturated layers within 2 meters of the surface.

Erosion

The wearing away of the land surface by water, wind, ice, or other geologic agents and by such processes as gravitational creep.

Erosion (accelerated)

Erosion much more rapid than geologic erosion, mainly as a result of human or animal activities or of a catastrophe in nature, such as a fire, that exposes the surface.

Erosion (geologic)

Erosion caused by geologic processes acting over long geologic periods and resulting in the wearing away of mountains and the building up of such landscape features as flood plains and coastal plains. Synonym: natural erosion.

Erosion pavement

A surficial lag concentration or layer of gravel and other rock fragments that remains on the soil surface after sheet or rill erosion or wind has removed the finer soil particles and that tends to protect the underlying soil from further erosion.

Erosion surface

A land surface shaped by the action of erosion, especially by running water.

Escarpment

A relatively continuous and steep slope or cliff breaking the general continuity of more gently sloping land surfaces and resulting from erosion or faulting. Most commonly applied to cliffs produced by differential erosion. Synonym: scarp.

Escarpment, bedrock (map symbol)

A relatively continuous and steep slope or cliff, produced by erosion or faulting, that breaks the general continuity of more gently sloping land surfaces. Exposed material is hard or soft bedrock.

Escarpment, nonbedrock (map symbol)

A relatively continuous and steep slope or cliff, generally produced by erosion but in some places produced by faulting, that breaks the continuity of more gently sloping land surfaces. Exposed earthy material is nonsoil or very shallow soil.

Esker

A long, narrow, sinuous, steep-sided ridge of stratified sand and gravel deposited as the bed of a stream flowing in an ice tunnel within or below the ice (subglacial) or between ice walls on top of the ice of a wasting glacier and left

Custom Soil Resource Report

behind as high ground when the ice melted. Eskers range in length from less than a kilometer to more than 160 kilometers and in height from 3 to 30 meters.

Extrusive rock

Igneous rock derived from deep-seated molten matter (magma) deposited and cooled on the earth's surface.

Fallow

Cropland left idle in order to restore productivity through accumulation of moisture. Summer fallow is common in regions of limited rainfall where cereal grain is grown. The soil is tilled for at least one growing season for weed control and decomposition of plant residue.

Fan remnant

A general term for landforms that are the remaining parts of older fan landforms, such as alluvial fans, that have been either dissected or partially buried.

Fertility, soil

The quality that enables a soil to provide plant nutrients, in adequate amounts and in proper balance, for the growth of specified plants when light, moisture, temperature, tilth, and other growth factors are favorable.

Fibric soil material (peat)

The least decomposed of all organic soil material. Peat contains a large amount of well preserved fiber that is readily identifiable according to botanical origin. Peat has the lowest bulk density and the highest water content at saturation of all organic soil material.

Field moisture capacity

The moisture content of a soil, expressed as a percentage of the oven-dry weight, after the gravitational, or free, water has drained away; the field moisture content 2 or 3 days after a soaking rain; also called *normal field capacity*, *normal moisture capacity*, or *capillary capacity*.

Fill slope

A sloping surface consisting of excavated soil material from a road cut. It commonly is on the downhill side of the road.

Fine textured soil

Sandy clay, silty clay, or clay.

Firebreak

An area cleared of flammable material to stop or help control creeping or running fires. It also serves as a line from which to work and to facilitate the movement of firefighters and equipment. Designated roads also serve as firebreaks.

Custom Soil Resource Report

First bottom

An obsolete, informal term loosely applied to the lowest flood-plain steps that are subject to regular flooding.

Flaggy soil material

Material that has, by volume, 15 to 35 percent flagstones. Very flaggy soil material has 35 to 60 percent flagstones, and extremely flaggy soil material has more than 60 percent flagstones.

Flagstone

A thin fragment of sandstone, limestone, slate, shale, or (rarely) schist 6 to 15 inches (15 to 38 centimeters) long.

Flood plain

The nearly level plain that borders a stream and is subject to flooding unless protected artificially.

Flood-plain landforms

A variety of constructional and erosional features produced by stream channel migration and flooding. Examples include backswamps, flood-plain splays, meanders, meander belts, meander scrolls, oxbow lakes, and natural levees.

Flood-plain splay

A fan-shaped deposit or other outspread deposit formed where an overloaded stream breaks through a levee (natural or artificial) and deposits its material (commonly coarse grained) on the flood plain.

Flood-plain step

An essentially flat, terrace-like alluvial surface within a valley that is frequently covered by floodwater from the present stream; any approximately horizontal surface still actively modified by fluvial scour and/or deposition. May occur individually or as a series of steps.

Fluvial

Of or pertaining to rivers or streams; produced by stream or river action.

Foothills

A region of steeply sloping hills that fringes a mountain range or high-plateau escarpment. The hills have relief of as much as 1,000 feet (300 meters).

Footslope

The concave surface at the base of a hillslope. A footslope is a transition zone between upslope sites of erosion and transport (shoulders and backslopes) and downslope sites of deposition (toeslopes).

Forb

Any herbaceous plant not a grass or a sedge.

Custom Soil Resource Report

Forest cover

All trees and other woody plants (underbrush) covering the ground in a forest.

Forest type

A stand of trees similar in composition and development because of given physical and biological factors by which it may be differentiated from other stands.

Fragipan

A loamy, brittle subsurface horizon low in porosity and content of organic matter and low or moderate in clay but high in silt or very fine sand. A fragipan appears cemented and restricts roots. When dry, it is hard or very hard and has a higher bulk density than the horizon or horizons above. When moist, it tends to rupture suddenly under pressure rather than to deform slowly.

Genesis, soil

The mode of origin of the soil. Refers especially to the processes or soil-forming factors responsible for the formation of the solum, or true soil, from the unconsolidated parent material.

Gilgai

Commonly, a succession of microbasins and microknolls in nearly level areas or of microvalleys and microridges parallel with the slope. Typically, the microrelief of clayey soils that shrink and swell considerably with changes in moisture content.

Glaciofluvial deposits

Material moved by glaciers and subsequently sorted and deposited by streams flowing from the melting ice. The deposits are stratified and occur in the form of outwash plains, valley trains, deltas, kames, eskers, and kame terraces.

Glaciolacustrine deposits

Material ranging from fine clay to sand derived from glaciers and deposited in glacial lakes mainly by glacial meltwater. Many deposits are bedded or laminated.

Gleyed soil

Soil that formed under poor drainage, resulting in the reduction of iron and other elements in the profile and in gray colors.

Graded stripcropping

Growing crops in strips that grade toward a protected waterway.

Grassed waterway

A natural or constructed waterway, typically broad and shallow, seeded to grass as protection against erosion. Conducts surface water away from cropland.

Custom Soil Resource Report

Gravel

Rounded or angular fragments of rock as much as 3 inches (76 millimeters to 7.6 centimeters) in diameter. An individual piece is a pebble.

Gravel pit (map symbol)

An open excavation from which soil and underlying material have been removed and used, without crushing, as a source of sand or gravel.

Gravelly soil material

Material that has 15 to 35 percent, by volume, rounded or angular rock fragments, not prominently flattened, as much as 3 inches (7.6 centimeters) in diameter.

Gravelly spot (map symbol)

A spot where the surface layer has more than 35 percent, by volume, rock fragments that are mostly less than 3 inches in diameter in an area that has less than 15 percent rock fragments.

Green manure crop (agronomy)

A soil-improving crop grown to be plowed under in an early stage of maturity or soon after maturity.

Ground water

Water filling all the unblocked pores of the material below the water table.

Gully (map symbol)

A small, steep-sided channel caused by erosion and cut in unconsolidated materials by concentrated but intermittent flow of water. The distinction between a gully and a rill is one of depth. A gully generally is an obstacle to farm machinery and is too deep to be obliterated by ordinary tillage whereas a rill is of lesser depth and can be smoothed over by ordinary tillage.

Hard bedrock

Bedrock that cannot be excavated except by blasting or by the use of special equipment that is not commonly used in construction.

Hard to reclaim

Reclamation is difficult after the removal of soil for construction and other uses. Revegetation and erosion control are extremely difficult.

Hardpan

A hardened or cemented soil horizon, or layer. The soil material is sandy, loamy, or clayey and is cemented by iron oxide, silica, calcium carbonate, or other substance.

Custom Soil Resource Report

Head slope (geomorphology)

A geomorphic component of hills consisting of a laterally concave area of a hillside, especially at the head of a drainageway. The overland waterflow is converging.

Hemic soil material (mucky peat)

Organic soil material intermediate in degree of decomposition between the less decomposed fibric material and the more decomposed sapric material.

High-residue crops

Such crops as small grain and corn used for grain. If properly managed, residue from these crops can be used to control erosion until the next crop in the rotation is established. These crops return large amounts of organic matter to the soil.

Hill

A generic term for an elevated area of the land surface, rising as much as 1,000 feet above surrounding lowlands, commonly of limited summit area and having a well defined outline. Slopes are generally more than 15 percent. The distinction between a hill and a mountain is arbitrary and may depend on local usage.

Hillslope

A generic term for the steeper part of a hill between its summit and the drainage line, valley flat, or depression floor at the base of a hill.

Horizon, soil

A layer of soil, approximately parallel to the surface, having distinct characteristics produced by soil-forming processes. In the identification of soil horizons, an uppercase letter represents the major horizons. Numbers or lowercase letters that follow represent subdivisions of the major horizons. An explanation of the subdivisions is given in the "Soil Survey Manual." The major horizons of mineral soil are as follows:

Custom Soil Resource Report

O horizon: An organic layer of fresh and decaying plant residue.

L horizon: A layer of organic and mineral limnic materials, including coprogenous earth (sedimentary peat), diatomaceous earth, and marl.

A horizon: The mineral horizon at or near the surface in which an accumulation of humified organic matter is mixed with the mineral material. Also, a plowed surface horizon, most of which was originally part of a B horizon.

E horizon: The mineral horizon in which the main feature is loss of silicate clay, iron, aluminum, or some combination of these.

B horizon: The mineral horizon below an A horizon. The B horizon is in part a layer of transition from the overlying A to the underlying C horizon. The B horizon also has distinctive characteristics, such as (1) accumulation of clay, sesquioxides, humus, or a combination of these; (2) prismatic or blocky structure; (3) redder or browner colors than those in the A horizon; or (4) a combination of these.

C horizon: The mineral horizon or layer, excluding indurated bedrock, that is little affected by soil-forming processes and does not have the properties typical of the overlying soil material. The material of a C horizon may be either like or unlike that in which the solum formed. If the material is known to differ from that in the solum, an Arabic numeral, commonly a 2, precedes the letter C.

Cr horizon: Soft, consolidated bedrock beneath the soil.

R layer: Consolidated bedrock beneath the soil. The bedrock commonly underlies a C horizon, but it can be directly below an A or a B horizon.

M layer: A root-limiting subsoil layer consisting of nearly continuous, horizontally oriented, human-manufactured materials.

W layer: A layer of water within or beneath the soil.

Humus

The well decomposed, more or less stable part of the organic matter in mineral soils.

Hydrologic soil groups

Refers to soils grouped according to their runoff potential. The soil properties that influence this potential are those that affect the minimum rate of water infiltration on a bare soil during periods after prolonged wetting when the soil is not frozen. These properties include depth to a seasonal high water table, the infiltration rate, and depth to a layer that significantly restricts the downward movement of water. The slope and the kind of plant cover are not considered but are separate factors in predicting runoff.

Igneous rock

Rock that was formed by cooling and solidification of magma and that has not been changed appreciably by weathering since its formation. Major varieties include plutonic and volcanic rock (e.g., andesite, basalt, and granite).

Illuviation

The movement of soil material from one horizon to another in the soil profile. Generally, material is removed from an upper horizon and deposited in a lower horizon.

Custom Soil Resource Report

Impervious soil

A soil through which water, air, or roots penetrate slowly or not at all. No soil is absolutely impervious to air and water all the time.

Increasers

Species in the climax vegetation that increase in amount as the more desirable plants are reduced by close grazing. Increasers commonly are the shorter plants and the less palatable to livestock.

Infiltration

The downward entry of water into the immediate surface of soil or other material, as contrasted with percolation, which is movement of water through soil layers or material.

Infiltration capacity

The maximum rate at which water can infiltrate into a soil under a given set of conditions.

Infiltration rate

The rate at which water penetrates the surface of the soil at any given instant, usually expressed in inches per hour. The rate can be limited by the infiltration capacity of the soil or the rate at which water is applied at the surface.

Intake rate

The average rate of water entering the soil under irrigation. Most soils have a fast initial rate; the rate decreases with application time. Therefore, intake rate for design purposes is not a constant but is a variable depending on the net irrigation application. The rate of water intake, in inches per hour, is expressed as follows:

Very low: Less than 0.2

Low: 0.2 to 0.4

Moderately low: 0.4 to 0.75

Moderate: 0.75 to 1.25

Moderately high: 1.25 to 1.75

High: 1.75 to 2.5

Very high: More than 2.5

Interfluve

A landform composed of the relatively undissected upland or ridge between two adjacent valleys containing streams flowing in the same general direction. An elevated area between two drainageways that sheds water to those drainageways.

Interfluve (geomorphology)

A geomorphic component of hills consisting of the uppermost, comparatively level or gently sloping area of a hill; shoulders of backwearing hillslopes can narrow the upland or can merge, resulting in a strongly convex shape.

Custom Soil Resource Report

Intermittent stream

A stream, or reach of a stream, that does not flow year-round but that is commonly dry for 3 or more months out of 12 and whose channel is generally below the local water table. It flows only during wet periods or when it receives ground-water discharge or long, continued contributions from melting snow or other surface and shallow subsurface sources.

Invaders

On range, plants that encroach into an area and grow after the climax vegetation has been reduced by grazing. Generally, plants invade following disturbance of the surface.

Iron depletions

See Redoximorphic features.

Irrigation

Application of water to soils to assist in production of crops. Methods of irrigation are:

Basin: Water is applied rapidly to nearly level plains surrounded by levees or dikes.

Border: Water is applied at the upper end of a strip in which the lateral flow of water is controlled by small earth ridges called border dikes, or borders.

Controlled flooding: Water is released at intervals from closely spaced field ditches and distributed uniformly over the field.

Corrugation: Water is applied to small, closely spaced furrows or ditches in fields of close-growing crops or in orchards so that it flows in only one direction.

Drip (or trickle): Water is applied slowly and under low pressure to the surface of the soil or into the soil through such applicators as emitters, porous tubing, or perforated pipe.

Furrow: Water is applied in small ditches made by cultivation implements. Furrows are used for tree and row crops.

Sprinkler: Water is sprayed over the soil surface through pipes or nozzles from a pressure system.

Subirrigation: Water is applied in open ditches or tile lines until the water table is raised enough to wet the soil.

Wild flooding: Water, released at high points, is allowed to flow onto an area without controlled distribution.

Kame

A low mound, knob, hummock, or short irregular ridge composed of stratified sand and gravel deposited by a subglacial stream as a fan or delta at the margin of a melting glacier; by a supraglacial stream in a low place or hole on the surface of the glacier; or as a ponded deposit on the surface or at the margin of stagnant ice.

Custom Soil Resource Report

Karst (topography)

A kind of topography that formed in limestone, gypsum, or other soluble rocks by dissolution and that is characterized by closed depressions, sinkholes, caves, and underground drainage.

Knoll

A small, low, rounded hill rising above adjacent landforms.

Ksat

See Saturated hydraulic conductivity.

Lacustrine deposit

Material deposited in lake water and exposed when the water level is lowered or the elevation of the land is raised.

Lake plain

A nearly level surface marking the floor of an extinct lake filled by well sorted, generally fine textured, stratified deposits, commonly containing varves.

Lake terrace

A narrow shelf, partly cut and partly built, produced along a lakeshore in front of a scarp line of low cliffs and later exposed when the water level falls.

Landfill (map symbol)

An area of accumulated waste products of human habitation, either above or below natural ground level.

Landslide

A general, encompassing term for most types of mass movement landforms and processes involving the downslope transport and outward deposition of soil and rock materials caused by gravitational forces; the movement may or may not involve saturated materials. The speed and distance of movement, as well as the amount of soil and rock material, vary greatly.

Large stones

Rock fragments 3 inches (7.6 centimeters) or more across. Large stones adversely affect the specified use of the soil.

Lava flow (map symbol)

A solidified, commonly lobate body of rock formed through lateral, surface outpouring of molten lava from a vent or fissure.

Leaching

The removal of soluble material from soil or other material by percolating water.

Custom Soil Resource Report

Levee (map symbol)

An embankment that confines or controls water, especially one built along the banks of a river to prevent overflow onto lowlands.

Linear extensibility

Refers to the change in length of an unconfined clod as moisture content is decreased from a moist to a dry state. Linear extensibility is used to determine the shrink-swell potential of soils. It is an expression of the volume change between the water content of the clod at $1/3$ - or $1/10$ -bar tension (33kPa or 10kPa tension) and oven dryness. Volume change is influenced by the amount and type of clay minerals in the soil. The volume change is the percent change for the whole soil. If it is expressed as a fraction, the resulting value is COLE, coefficient of linear extensibility.

Liquid limit

The moisture content at which the soil passes from a plastic to a liquid state.

Loam

Soil material that is 7 to 27 percent clay particles, 28 to 50 percent silt particles, and less than 52 percent sand particles.

Loess

Material transported and deposited by wind and consisting dominantly of silt-sized particles.

Low strength

The soil is not strong enough to support loads.

Low-residue crops

Such crops as corn used for silage, peas, beans, and potatoes. Residue from these crops is not adequate to control erosion until the next crop in the rotation is established. These crops return little organic matter to the soil.

Marl

An earthy, unconsolidated deposit consisting chiefly of calcium carbonate mixed with clay in approximately equal proportions; formed primarily under freshwater lacustrine conditions but also formed in more saline environments.

Marsh or swamp (map symbol)

A water-saturated, very poorly drained area that is intermittently or permanently covered by water. Sedges, cattails, and rushes are the dominant vegetation in marshes, and trees or shrubs are the dominant vegetation in swamps. Not used in map units where the named soils are poorly drained or very poorly drained.

Mass movement

A generic term for the dislodgment and downslope transport of soil and rock material as a unit under direct gravitational stress.

Custom Soil Resource Report

Masses

See Redoximorphic features.

Meander belt

The zone within which migration of a meandering channel occurs; the flood-plain area included between two imaginary lines drawn tangential to the outer bends of active channel loops.

Meander scar

A crescent-shaped, concave or linear mark on the face of a bluff or valley wall, produced by the lateral erosion of a meandering stream that impinged upon and undercut the bluff.

Meander scroll

One of a series of long, parallel, close-fitting, crescent-shaped ridges and troughs formed along the inner bank of a stream meander as the channel migrated laterally down-valley and toward the outer bank.

Mechanical treatment

Use of mechanical equipment for seeding, brush management, and other management practices.

Medium textured soil

Very fine sandy loam, loam, silt loam, or silt.

Mesa

A broad, nearly flat topped and commonly isolated landmass bounded by steep slopes or precipitous cliffs and capped by layers of resistant, nearly horizontal rocky material. The summit width is characteristically greater than the height of the bounding escarpments.

Metamorphic rock

Rock of any origin altered in mineralogical composition, chemical composition, or structure by heat, pressure, and movement at depth in the earth's crust. Nearly all such rocks are crystalline.

Mine or quarry (map symbol)

An open excavation from which soil and underlying material have been removed and in which bedrock is exposed. Also denotes surface openings to underground mines.

Mine spoil

An accumulation of displaced earthy material, rock, or other waste material removed during mining or excavation. Also called earthy fill.

Mineral soil

Soil that is mainly mineral material and low in organic material. Its bulk density is more than that of organic soil.

Custom Soil Resource Report

Minimum tillage

Only the tillage essential to crop production and prevention of soil damage.

Miscellaneous area

A kind of map unit that has little or no natural soil and supports little or no vegetation.

Miscellaneous water (map symbol)

Small, constructed bodies of water that are used for industrial, sanitary, or mining applications and that contain water most of the year.

Moderately coarse textured soil

Coarse sandy loam, sandy loam, or fine sandy loam.

Moderately fine textured soil

Clay loam, sandy clay loam, or silty clay loam.

Mollic epipedon

A thick, dark, humus-rich surface horizon (or horizons) that has high base saturation and pedogenic soil structure. It may include the upper part of the subsoil.

Moraine

In terms of glacial geology, a mound, ridge, or other topographically distinct accumulation of unsorted, unstratified drift, predominantly till, deposited primarily by the direct action of glacial ice in a variety of landforms. Also, a general term for a landform composed mainly of till (except for kame moraines, which are composed mainly of stratified outwash) that has been deposited by a glacier. Some types of moraines are disintegration, end, ground, kame, lateral, recessional, and terminal.

Morphology, soil

The physical makeup of the soil, including the texture, structure, porosity, consistence, color, and other physical, mineral, and biological properties of the various horizons, and the thickness and arrangement of those horizons in the soil profile.

Mottling, soil

Irregular spots of different colors that vary in number and size. Descriptive terms are as follows: abundance—*few*, *common*, and *many*; size—*fine*, *medium*, and *coarse*; and contrast—*faint*, *distinct*, and *prominent*. The size measurements are of the diameter along the greatest dimension. *Fine* indicates less than 5 millimeters (about 0.2 inch); *medium*, from 5 to 15 millimeters (about 0.2 to 0.6 inch); and *coarse*, more than 15 millimeters (about 0.6 inch).

Mountain

A generic term for an elevated area of the land surface, rising more than 1,000 feet (300 meters) above surrounding lowlands, commonly of restricted summit area (relative to a plateau) and generally having steep sides. A mountain can

Custom Soil Resource Report

occur as a single, isolated mass or in a group forming a chain or range. Mountains are formed primarily by tectonic activity and/or volcanic action but can also be formed by differential erosion.

Muck

Dark, finely divided, well decomposed organic soil material. (See Sapric soil material.)

Mucky peat

See Hemic soil material.

Mudstone

A blocky or massive, fine grained sedimentary rock in which the proportions of clay and silt are approximately equal. Also, a general term for such material as clay, silt, claystone, siltstone, shale, and argillite and that should be used only when the amounts of clay and silt are not known or cannot be precisely identified.

Munsell notation

A designation of color by degrees of three simple variables—hue, value, and chroma. For example, a notation of 10YR 6/4 is a color with hue of 10YR, value of 6, and chroma of 4.

Natric horizon

A special kind of argillic horizon that contains enough exchangeable sodium to have an adverse effect on the physical condition of the subsoil.

Neutral soil

A soil having a pH value of 6.6 to 7.3. (See Reaction, soil.)

Nodules

See Redoximorphic features.

Nose slope (geomorphology)

A geomorphic component of hills consisting of the projecting end (laterally convex area) of a hillside. The overland waterflow is predominantly divergent. Nose slopes consist dominantly of colluvium and slope-wash sediments (for example, slope alluvium).

Nutrient, plant

Any element taken in by a plant essential to its growth. Plant nutrients are mainly nitrogen, phosphorus, potassium, calcium, magnesium, sulfur, iron, manganese, copper, boron, and zinc obtained from the soil and carbon, hydrogen, and oxygen obtained from the air and water.

Organic matter

Plant and animal residue in the soil in various stages of decomposition. The content of organic matter in the surface layer is described as follows:

Custom Soil Resource Report

Very low: Less than 0.5 percent

Low: 0.5 to 1.0 percent

Moderately low: 1.0 to 2.0 percent

Moderate: 2.0 to 4.0 percent

High: 4.0 to 8.0 percent

Very high: More than 8.0 percent

Outwash

Stratified and sorted sediments (chiefly sand and gravel) removed or "washed out" from a glacier by meltwater streams and deposited in front of or beyond the end moraine or the margin of a glacier. The coarser material is deposited nearer to the ice.

Outwash plain

An extensive lowland area of coarse textured glaciofluvial material. An outwash plain is commonly smooth; where pitted, it generally is low in relief.

Paleoterrace

An erosional remnant of a terrace that retains the surface form and alluvial deposits of its origin but was not emplaced by, and commonly does not grade to, a present-day stream or drainage network.

Pan

A compact, dense layer in a soil that impedes the movement of water and the growth of roots. For example, *hardpan*, *fragipan*, *claypan*, *plowpan*, and *traffic pan*.

Parent material

The unconsolidated organic and mineral material in which soil forms.

Peat

Unconsolidated material, largely undecomposed organic matter, that has accumulated under excess moisture. (See Fibric soil material.)

Ped

An individual natural soil aggregate, such as a granule, a prism, or a block.

Pedisediment

A layer of sediment, eroded from the shoulder and backslope of an erosional slope, that lies on and is being (or was) transported across a gently sloping erosional surface at the foot of a receding hill or mountain slope.

Pedon

The smallest volume that can be called "a soil." A pedon is three dimensional and large enough to permit study of all horizons. Its area ranges from about 10 to 100 square feet (1 square meter to 10 square meters), depending on the variability of the soil.

Custom Soil Resource Report

Percolation

The movement of water through the soil.

Perennial water (map symbol)

Small, natural or constructed lakes, ponds, or pits that contain water most of the year.

Permafrost

Ground, soil, or rock that remains at or below 0 degrees C for at least 2 years. It is defined on the basis of temperature and is not necessarily frozen.

pH value

A numerical designation of acidity and alkalinity in soil. (See Reaction, soil.)

Phase, soil

A subdivision of a soil series based on features that affect its use and management, such as slope, stoniness, and flooding.

Piping

Formation of subsurface tunnels or pipelike cavities by water moving through the soil.

Pitting

Pits caused by melting around ice. They form on the soil after plant cover is removed.

Plastic limit

The moisture content at which a soil changes from semisolid to plastic.

Plasticity Index

The numerical difference between the liquid limit and the plastic limit; the range of moisture content within which the soil remains plastic.

Plateau (geomorphology)

A comparatively flat area of great extent and elevation; specifically, an extensive land region that is considerably elevated (more than 100 meters) above the adjacent lower lying terrain, is commonly limited on at least one side by an abrupt descent, and has a flat or nearly level surface. A comparatively large part of a plateau surface is near summit level.

Playa

The generally dry and nearly level lake plain that occupies the lowest parts of closed depressions, such as those on intermontane basin floors. Temporary flooding occurs primarily in response to precipitation and runoff. Playa deposits are fine grained and may or may not have a high water table and saline conditions.

Custom Soil Resource Report

Plinthite

The sesquioxide-rich, humus-poor, highly weathered mixture of clay with quartz and other diluents. It commonly appears as red mottles, usually in platy, polygonal, or reticulate patterns. Plinthite changes irreversibly to an ironstone hardpan or to irregular aggregates on repeated wetting and drying, especially if it is exposed also to heat from the sun. In a moist soil, plinthite can be cut with a spade. It is a form of laterite.

Plowpan

A compacted layer formed in the soil directly below the plowed layer.

Ponding

Standing water on soils in closed depressions. Unless the soils are artificially drained, the water can be removed only by percolation or evapotranspiration.

Poorly graded

Refers to a coarse grained soil or soil material consisting mainly of particles of nearly the same size. Because there is little difference in size of the particles, density can be increased only slightly by compaction.

Pore linings

See Redoximorphic features.

Potential native plant community

See Climax plant community.

Potential rooting depth (effective rooting depth)

Depth to which roots could penetrate if the content of moisture in the soil were adequate. The soil has no properties restricting the penetration of roots to this depth.

Prescribed burning

Deliberately burning an area for specific management purposes, under the appropriate conditions of weather and soil moisture and at the proper time of day.

Productivity, soil

The capability of a soil for producing a specified plant or sequence of plants under specific management.

Profile, soil

A vertical section of the soil extending through all its horizons and into the parent material.

Proper grazing use

Grazing at an intensity that maintains enough cover to protect the soil and maintain or improve the quantity and quality of the desirable vegetation. This practice increases the vigor and reproduction capacity of the key plants and

Custom Soil Resource Report

promotes the accumulation of litter and mulch necessary to conserve soil and water.

Rangeland

Land on which the potential natural vegetation is predominantly grasses, grasslike plants, forbs, or shrubs suitable for grazing or browsing. It includes natural grasslands, savannas, many wetlands, some deserts, tundras, and areas that support certain forb and shrub communities.

Reaction, soil

A measure of acidity or alkalinity of a soil, expressed as pH values. A soil that tests to pH 7.0 is described as precisely neutral in reaction because it is neither acid nor alkaline. The degrees of acidity or alkalinity, expressed as pH values, are:

Ultra acid: Less than 3.5

Extremely acid: 3.5 to 4.4

Very strongly acid: 4.5 to 5.0

Strongly acid: 5.1 to 5.5

Moderately acid: 5.6 to 6.0

Slightly acid: 6.1 to 6.5

Neutral: 6.6 to 7.3

Slightly alkaline: 7.4 to 7.8

Moderately alkaline: 7.9 to 8.4

Strongly alkaline: 8.5 to 9.0

Very strongly alkaline: 9.1 and higher

Red beds

Sedimentary strata that are mainly red and are made up largely of sandstone and shale.

Redoximorphic concentrations

See Redoximorphic features.

Redoximorphic depletions

See Redoximorphic features.

Redoximorphic features

Redoximorphic features are associated with wetness and result from alternating periods of reduction and oxidation of iron and manganese compounds in the soil. Reduction occurs during saturation with water, and oxidation occurs when the soil is not saturated. Characteristic color patterns are created by these processes. The reduced iron and manganese ions may be removed from a soil if vertical or lateral fluxes of water occur, in which case there is no iron or manganese precipitation in that soil. Wherever the iron and manganese are oxidized and precipitated, they form either soft masses or hard concretions or nodules. Movement of iron and manganese as a result of redoximorphic processes in a soil may result in redoximorphic features that are defined as follows:

Custom Soil Resource Report

1. Redoximorphic concentrations.—These are zones of apparent accumulation of iron-manganese oxides, including:
 - A. Nodules and concretions, which are cemented bodies that can be removed from the soil intact. Concretions are distinguished from nodules on the basis of internal organization. A concretion typically has concentric layers that are visible to the naked eye. Nodules do not have visible organized internal structure; *and*
 - B. Masses, which are noncemented concentrations of substances within the soil matrix; *and*
 - C. Pore linings, i.e., zones of accumulation along pores that may be either coatings on pore surfaces or impregnations from the matrix adjacent to the pores.
2. Redoximorphic depletions.—These are zones of low chroma (chromas less than those in the matrix) where either iron-manganese oxides alone or both iron-manganese oxides and clay have been stripped out, including:
 - A. Iron depletions, i.e., zones that contain low amounts of iron and manganese oxides but have a clay content similar to that of the adjacent matrix; *and*
 - B. Clay depletions, i.e., zones that contain low amounts of iron, manganese, and clay (often referred to as silt coatings or skeletons).
3. Reduced matrix.—This is a soil matrix that has low chroma *in situ* but undergoes a change in hue or chroma within 30 minutes after the soil material has been exposed to air.

Reduced matrix

See Redoximorphic features.

Regolith

All unconsolidated earth materials above the solid bedrock. It includes material weathered in place from all kinds of bedrock and alluvial, glacial, eolian, lacustrine, and pyroclastic deposits.

Relief

The relative difference in elevation between the upland summits and the lowlands or valleys of a given region.

Residuum (residual soil material)

Unconsolidated, weathered or partly weathered mineral material that accumulated as bedrock disintegrated in place.

Rill

A very small, steep-sided channel resulting from erosion and cut in unconsolidated materials by concentrated but intermittent flow of water. A rill generally is not an obstacle to wheeled vehicles and is shallow enough to be smoothed over by ordinary tillage.

Custom Soil Resource Report

Riser

The vertical or steep side slope (e.g., escarpment) of terraces, flood-plain steps, or other stepped landforms; commonly a recurring part of a series of natural, steplike landforms, such as successive stream terraces.

Road cut

A sloping surface produced by mechanical means during road construction. It is commonly on the uphill side of the road.

Rock fragments

Rock or mineral fragments having a diameter of 2 millimeters or more; for example, pebbles, cobbles, stones, and boulders.

Rock outcrop (map symbol)

An exposure of bedrock at the surface of the earth. Not used where the named soils of the surrounding map unit are shallow over bedrock or where "Rock outcrop" is a named component of the map unit.

Root zone

The part of the soil that can be penetrated by plant roots.

Runoff

The precipitation discharged into stream channels from an area. The water that flows off the surface of the land without sinking into the soil is called surface runoff. Water that enters the soil before reaching surface streams is called ground-water runoff or seepage flow from ground water.

Saline soil

A soil containing soluble salts in an amount that impairs growth of plants. A saline soil does not contain excess exchangeable sodium.

Saline spot (map symbol)

An area where the surface layer has an electrical conductivity of 8 mmhos/cm more than the surface layer of the named soils in the surrounding map unit. The surface layer of the surrounding soils has an electrical conductivity of 2 mmhos/cm or less.

Sand

As a soil separate, individual rock or mineral fragments from 0.05 millimeter to 2.0 millimeters in diameter. Most sand grains consist of quartz. As a soil textural class, a soil that is 85 percent or more sand and not more than 10 percent clay.

Sandstone

Sedimentary rock containing dominantly sand-sized particles.

Custom Soil Resource Report

Sandy spot (map symbol)

A spot where the surface layer is loamy fine sand or coarser in areas where the surface layer of the named soils in the surrounding map unit is very fine sandy loam or finer.

Sapric soil material (muck)

The most highly decomposed of all organic soil material. Muck has the least amount of plant fiber, the highest bulk density, and the lowest water content at saturation of all organic soil material.

Saturated hydraulic conductivity (Ksat)

The ease with which pores of a saturated soil transmit water. Formally, the proportionality coefficient that expresses the relationship of the rate of water movement to hydraulic gradient in Darcy's Law, a law that describes the rate of water movement through porous media. Commonly abbreviated as "Ksat." Terms describing saturated hydraulic conductivity are:

Very high: 100 or more micrometers per second (14.17 or more inches per hour)

High: 10 to 100 micrometers per second (1.417 to 14.17 inches per hour)

Moderately high: 1 to 10 micrometers per second (0.1417 inch to 1.417 inches per hour)

Moderately low: 0.1 to 1 micrometer per second (0.01417 to 0.1417 inch per hour)

Low: 0.01 to 0.1 micrometer per second (0.001417 to 0.01417 inch per hour)

Very low: Less than 0.01 micrometer per second (less than 0.001417 inch per hour).

To convert inches per hour to micrometers per second, multiply inches per hour by 7.0572. To convert micrometers per second to inches per hour, multiply micrometers per second by 0.1417.

Saturation

Wetness characterized by zero or positive pressure of the soil water. Under conditions of saturation, the water will flow from the soil matrix into an unlined auger hole.

Scarification

The act of abrading, scratching, loosening, crushing, or modifying the surface to increase water absorption or to provide a more tillable soil.

Sedimentary rock

A consolidated deposit of clastic particles, chemical precipitates, or organic remains accumulated at or near the surface of the earth under normal low temperature and pressure conditions. Sedimentary rocks include consolidated equivalents of alluvium, colluvium, drift, and eolian, lacustrine, and marine deposits. Examples are sandstone, siltstone, mudstone, claystone, shale, conglomerate, limestone, dolomite, and coal.

Custom Soil Resource Report

Sequum

A sequence consisting of an illuvial horizon and the overlying eluvial horizon. (See Eluviation.)

Series, soil

A group of soils that have profiles that are almost alike, except for differences in texture of the surface layer. All the soils of a series have horizons that are similar in composition, thickness, and arrangement.

Severely eroded spot (map symbol)

An area where, on the average, 75 percent or more of the original surface layer has been lost because of accelerated erosion. Not used in map units in which "severely eroded," "very severely eroded," or "gullied" is part of the map unit name.

Shale

Sedimentary rock that formed by the hardening of a deposit of clay, silty clay, or silty clay loam and that has a tendency to split into thin layers.

Sheet erosion

The removal of a fairly uniform layer of soil material from the land surface by the action of rainfall and surface runoff.

Short, steep slope (map symbol)

A narrow area of soil having slopes that are at least two slope classes steeper than the slope class of the surrounding map unit.

Shoulder

The convex, erosional surface near the top of a hillslope. A shoulder is a transition from summit to backslope.

Shrink-swell

The shrinking of soil when dry and the swelling when wet. Shrinking and swelling can damage roads, dams, building foundations, and other structures. It can also damage plant roots.

Shrub-coppice dune

A small, streamlined dune that forms around brush and clump vegetation.

Side slope (geomorphology)

A geomorphic component of hills consisting of a laterally planar area of a hillside. The overland waterflow is predominantly parallel. Side slopes are dominantly colluvium and slope-wash sediments.

Silica

A combination of silicon and oxygen. The mineral form is called quartz.

Custom Soil Resource Report

Silica-sesquioxide ratio

The ratio of the number of molecules of silica to the number of molecules of alumina and iron oxide. The more highly weathered soils or their clay fractions in warm-temperate, humid regions, and especially those in the tropics, generally have a low ratio.

Silt

As a soil separate, individual mineral particles that range in diameter from the upper limit of clay (0.002 millimeter) to the lower limit of very fine sand (0.05 millimeter). As a soil textural class, soil that is 80 percent or more silt and less than 12 percent clay.

Siltstone

An indurated silt having the texture and composition of shale but lacking its fine lamination or fissility; a massive mudstone in which silt predominates over clay.

Similar soils

Soils that share limits of diagnostic criteria, behave and perform in a similar manner, and have similar conservation needs or management requirements for the major land uses in the survey area.

Sinkhole (map symbol)

A closed, circular or elliptical depression, commonly funnel shaped, characterized by subsurface drainage and formed either by dissolution of the surface of underlying bedrock (e.g., limestone, gypsum, or salt) or by collapse of underlying caves within bedrock. Complexes of sinkholes in carbonate-rock terrain are the main components of karst topography.

Site index

A designation of the quality of a forest site based on the height of the dominant stand at an arbitrarily chosen age. For example, if the average height attained by dominant and codominant trees in a fully stocked stand at the age of 50 years is 75 feet, the site index is 75.

Slickensides (pedogenic)

Grooved, striated, and/or glossy (shiny) slip faces on structural peds, such as wedges; produced by shrink-swell processes, most commonly in soils that have a high content of expansive clays.

Slide or slip (map symbol)

A prominent landform scar or ridge caused by fairly recent mass movement or descent of earthy material resulting from failure of earth or rock under shear stress along one or several surfaces.

Slope

The inclination of the land surface from the horizontal. Percentage of slope is the vertical distance divided by horizontal distance, then multiplied by 100. Thus, a slope of 20 percent is a drop of 20 feet in 100 feet of horizontal distance.

Custom Soil Resource Report

Slope alluvium

Sediment gradually transported down the slopes of mountains or hills primarily by nonchannel alluvial processes (i.e., slope-wash processes) and characterized by particle sorting. Lateral particle sorting is evident on long slopes. In a profile sequence, sediments may be distinguished by differences in size and/or specific gravity of rock fragments and may be separated by stone lines. Burnished peds and sorting of rounded or subrounded pebbles or cobbles distinguish these materials from unsorted colluvial deposits.

Slow refill

The slow filling of ponds, resulting from restricted water transmission in the soil.

Slow water movement

Restricted downward movement of water through the soil. See Saturated hydraulic conductivity.

Sodic (alkali) soil

A soil having so high a degree of alkalinity (pH 8.5 or higher) or so high a percentage of exchangeable sodium (15 percent or more of the total exchangeable bases), or both, that plant growth is restricted.

Sodic spot (map symbol)

An area where the surface layer has a sodium adsorption ratio that is at least 10 more than that of the surface layer of the named soils in the surrounding map unit. The surface layer of the surrounding soils has a sodium adsorption ratio of 5 or less.

Sodicity

The degree to which a soil is affected by exchangeable sodium. Sodicity is expressed as a sodium adsorption ratio (SAR) of a saturation extract, or the ratio of Na^+ to $\text{Ca}^{++} + \text{Mg}^{++}$. The degrees of sodicity and their respective ratios are:

Slight: Less than 13:1

Moderate: 13-30:1

Strong: More than 30:1

Sodium adsorption ratio (SAR)

A measure of the amount of sodium (Na) relative to calcium (Ca) and magnesium (Mg) in the water extract from saturated soil paste. It is the ratio of the Na concentration divided by the square root of one-half of the Ca + Mg concentration.

Soft bedrock

Bedrock that can be excavated with trenching machines, backhoes, small rippers, and other equipment commonly used in construction.

Custom Soil Resource Report

Soil

A natural, three-dimensional body at the earth's surface. It is capable of supporting plants and has properties resulting from the integrated effect of climate and living matter acting on earthy parent material, as conditioned by relief and by the passage of time.

Soil separates

Mineral particles less than 2 millimeters in equivalent diameter and ranging between specified size limits. The names and sizes, in millimeters, of separates recognized in the United States are as follows:

Very coarse sand: 2.0 to 1.0

Coarse sand: 1.0 to 0.5

Medium sand: 0.5 to 0.25

Fine sand: 0.25 to 0.10

Very fine sand: 0.10 to 0.05

Silt: 0.05 to 0.002

Clay: Less than 0.002

Solum

The upper part of a soil profile, above the C horizon, in which the processes of soil formation are active. The solum in soil consists of the A, E, and B horizons. Generally, the characteristics of the material in these horizons are unlike those of the material below the solum. The living roots and plant and animal activities are largely confined to the solum.

Spoil area (map symbol)

A pile of earthy materials, either smoothed or uneven, resulting from human activity.

Stone line

In a vertical cross section, a line formed by scattered fragments or a discrete layer of angular and subangular rock fragments (commonly a gravel- or cobble-sized lag concentration) that formerly was draped across a topographic surface and was later buried by additional sediments. A stone line generally caps material that was subject to weathering, soil formation, and erosion before burial. Many stone lines seem to be buried erosion pavements, originally formed by sheet and rill erosion across the land surface.

Stones

Rock fragments 10 to 24 inches (25 to 60 centimeters) in diameter if rounded or 15 to 24 inches (38 to 60 centimeters) in length if flat.

Stony

Refers to a soil containing stones in numbers that interfere with or prevent tillage.

Custom Soil Resource Report

Stony spot (map symbol)

A spot where 0.01 to 0.1 percent of the soil surface is covered by rock fragments that are more than 10 inches in diameter in areas where the surrounding soil has no surface stones.

Strath terrace

A type of stream terrace; formed as an erosional surface cut on bedrock and thinly mantled with stream deposits (alluvium).

Stream terrace

One of a series of platforms in a stream valley, flanking and more or less parallel to the stream channel, originally formed near the level of the stream; represents the remnants of an abandoned flood plain, stream bed, or valley floor produced during a former state of fluvial erosion or deposition.

Stripcropping

Growing crops in a systematic arrangement of strips or bands that provide vegetative barriers to wind erosion and water erosion.

Structure, soil

The arrangement of primary soil particles into compound particles or aggregates. The principal forms of soil structure are:

Platy: Flat and laminated

Prismatic: Vertically elongated and having flat tops

Columnar: Vertically elongated and having rounded tops

Angular blocky: Having faces that intersect at sharp angles (planes)

Subangular blocky: Having subrounded and planar faces (no sharp angles)

Granular: Small structural units with curved or very irregular faces

Structureless soil horizons are defined as follows:

Single grained: Entirely noncoherent (each grain by itself), as in loose sand

Massive: Occurring as a coherent mass

Stubble mulch

Stubble or other crop residue left on the soil or partly worked into the soil. It protects the soil from wind erosion and water erosion after harvest, during preparation of a seedbed for the next crop, and during the early growing period of the new crop.

Subsoil

Technically, the B horizon; roughly, the part of the solum below plow depth.

Subsoiling

Tilling a soil below normal plow depth, ordinarily to shatter a hardpan or claypan.

Custom Soil Resource Report

Substratum

The part of the soil below the solum.

Subsurface layer

Any surface soil horizon (A, E, AB, or EB) below the surface layer.

Summer fallow

The tillage of uncropped land during the summer to control weeds and allow storage of moisture in the soil for the growth of a later crop. A practice common in semiarid regions, where annual precipitation is not enough to produce a crop every year. Summer fallow is frequently practiced before planting winter grain.

Summit

The topographically highest position of a hillslope. It has a nearly level (planar or only slightly convex) surface.

Surface layer

The soil ordinarily moved in tillage, or its equivalent in uncultivated soil, ranging in depth from 4 to 10 inches (10 to 25 centimeters). Frequently designated as the "plow layer," or the "Ap horizon."

Surface soil

The A, E, AB, and EB horizons, considered collectively. It includes all subdivisions of these horizons.

Talus

Rock fragments of any size or shape (commonly coarse and angular) derived from and lying at the base of a cliff or very steep rock slope. The accumulated mass of such loose broken rock formed chiefly by falling, rolling, or sliding.

Taxadjuncts

Soils that cannot be classified in a series recognized in the classification system. Such soils are named for a series they strongly resemble and are designated as taxadjuncts to that series because they differ in ways too small to be of consequence in interpreting their use and behavior. Soils are recognized as taxadjuncts only when one or more of their characteristics are slightly outside the range defined for the family of the series for which the soils are named.

Terminal moraine

An end moraine that marks the farthest advance of a glacier. It typically has the form of a massive arcuate or concentric ridge, or complex of ridges, and is underlain by till and other types of drift.

Terrace (conservation)

An embankment, or ridge, constructed across sloping soils on the contour or at a slight angle to the contour. The terrace intercepts surface runoff so that water soaks into the soil or flows slowly to a prepared outlet. A terrace in a field

Custom Soil Resource Report

generally is built so that the field can be farmed. A terrace intended mainly for drainage has a deep channel that is maintained in permanent sod.

Terrace (geomorphology)

A steplike surface, bordering a valley floor or shoreline, that represents the former position of a flood plain, lake, or seashore. The term is usually applied both to the relatively flat summit surface (tread) that was cut or built by stream or wave action and to the steeper descending slope (scarp or riser) that has graded to a lower base level of erosion.

Terracettes

Small, irregular steplike forms on steep hillslopes, especially in pasture, formed by creep or erosion of surficial materials that may be induced or enhanced by trampling of livestock, such as sheep or cattle.

Texture, soil

The relative proportions of sand, silt, and clay particles in a mass of soil. The basic textural classes, in order of increasing proportion of fine particles, are *sand, loamy sand, sandy loam, loam, silt loam, silt, sandy clay loam, clay loam, silty clay loam, sandy clay, silty clay,* and *clay*. The sand, loamy sand, and sandy loam classes may be further divided by specifying "coarse," "fine," or "very fine."

Thin layer

Otherwise suitable soil material that is too thin for the specified use.

Till

Dominantly unsorted and nonstratified drift, generally unconsolidated and deposited directly by a glacier without subsequent reworking by meltwater, and consisting of a heterogeneous mixture of clay, silt, sand, gravel, stones, and boulders; rock fragments of various lithologies are embedded within a finer matrix that can range from clay to sandy loam.

Till plain

An extensive area of level to gently undulating soils underlain predominantly by till and bounded at the distal end by subordinate recessional or end moraines.

Tilth, soil

The physical condition of the soil as related to tillage, seedbed preparation, seedling emergence, and root penetration.

Toeslope

The gently inclined surface at the base of a hillslope. Toeslopes in profile are commonly gentle and linear and are constructional surfaces forming the lower part of a hillslope continuum that grades to valley or closed-depression floors.

Custom Soil Resource Report

Topsoil

The upper part of the soil, which is the most favorable material for plant growth. It is ordinarily rich in organic matter and is used to topdress roadbanks, lawns, and land affected by mining.

Trace elements

Chemical elements, for example, zinc, cobalt, manganese, copper, and iron, in soils in extremely small amounts. They are essential to plant growth.

Tread

The flat to gently sloping, topmost, laterally extensive slope of terraces, flood-plain steps, or other stepped landforms; commonly a recurring part of a series of natural steplike landforms, such as successive stream terraces.

Tuff

A generic term for any consolidated or cemented deposit that is 50 percent or more volcanic ash.

Upland

An informal, general term for the higher ground of a region, in contrast with a low-lying adjacent area, such as a valley or plain, or for land at a higher elevation than the flood plain or low stream terrace; land above the footslope zone of the hillslope continuum.

Valley fill

The unconsolidated sediment deposited by any agent (water, wind, ice, or mass wasting) so as to fill or partly fill a valley.

Variiegation

Refers to patterns of contrasting colors assumed to be inherited from the parent material rather than to be the result of poor drainage.

Varve

A sedimentary layer or a lamina or sequence of laminae deposited in a body of still water within a year. Specifically, a thin pair of graded glaciolacustrine layers seasonally deposited, usually by meltwater streams, in a glacial lake or other body of still water in front of a glacier.

Very stony spot (map symbol)

A spot where 0.1 to 3.0 percent of the soil surface is covered by rock fragments that are more than 10 inches in diameter in areas where the surface of the surrounding soil is covered by less than 0.01 percent stones.

Water bars

Smooth, shallow ditches or depressional areas that are excavated at an angle across a sloping road. They are used to reduce the downward velocity of water and divert it off and away from the road surface. Water bars can easily be driven over if constructed properly.

Custom Soil Resource Report

Weathering

All physical disintegration, chemical decomposition, and biologically induced changes in rocks or other deposits at or near the earth's surface by atmospheric or biologic agents or by circulating surface waters but involving essentially no transport of the altered material.

Well graded

Refers to soil material consisting of coarse grained particles that are well distributed over a wide range in size or diameter. Such soil normally can be easily increased in density and bearing properties by compaction. Contrasts with poorly graded soil.

Wet spot (map symbol)

A somewhat poorly drained to very poorly drained area that is at least two drainage classes wetter than the named soils in the surrounding map unit.

Wilting point (or permanent wilting point)

The moisture content of soil, on an oven-dry basis, at which a plant (specifically a sunflower) wilts so much that it does not recover when placed in a humid, dark chamber.

Windthrow

The uprooting and tipping over of trees by the wind.